



## **Manufacturer:**

ÅngströmBond®

### **Product Name:**

ÅngströmBond® AB9590 Thermally Conductive Black Epoxy, Room Temperature Cure (2.5g)

## **Manufacturer Part Number:**

AB9590-2.5G

Click here for more details on the ÅngströmBond® AB9590 Thermally Conductive Black Epoxy, Room Temperature Cure (2.5g)



Adhesives

The only adhesive line developed exclusively for fiber optics

 $m \mathring{A}ngstr\ddot{o}mBond^{\circ}AB9590$  Flexible potting/bonding compound

#### Description:

ÅngströmBond\* AB9590 is a two component, thermally conductive, high performance epoxy adhesive and potting compound. This room temperature curing adhesive is designed for use in applications that require a flexible material for sensitive or fragile components or fine electrical wires. AB9590 has a low mixed viscosity for ease of potting or brushing.

#### **Typical Physical Properties:**

 Color Mixed:
 Black

 Specific Gravity Mixed:
 1.28

 Viscosity, cps:
 30,000

 Hardness, Shore A:
 <80</td>

 Operating Temp, °C
 -20 to 100

 Thermal conductivity, @85°C
 W/m°K

 0.946

#### **Handling Characteristics:**

Working time @ 25°C (77F) - 45 minutes

#### Mix Ratio -

RESIN	HARDENER
Black	Lt. Yellow
3.67	1.00
100	15
1.56	1.01
	Black 3.67 100

Cure Schedule -80% strength – 16 hours @ 25°C 100% full strength – 112 hours @ 25°C

Filler may settle during shipping and storage. Thorough mixing of bulk containers is recommended before use.

ÅngströmBond® is a registered trademark of Fiber Optic Center, Inc., New Bedford MA, USA

Fiber Optic Center™, Inc. MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE, with respect to its products. In addition, while the information herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestion for use are made without guarantee — inasmuch as conditions of use are beyond our control. The properties given are typical values, and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of their own purposes.

# Contact the professionals at Fiber Optic Center for a quote or to get more details.