



Manufacturer:

Dymax

Product Name:

Dymax 3mm Lightguide Adapter for ACCU-CAL™ 50 UV Radiometer

Manufacturer Part Number:

39556

▶ [Click here for more details on the Dymax 3mm Lightguide Adapter for ACCU-CAL™ 50 UV Radiometer](#)

ACCU-CAL™ 50 Radiometer

- Simple to Operate
- Set Screw Locks Lightguide in Place
- PTB and NIST Traceable

Consistent UV light curing requires periodic monitoring of UV intensity or dose. The ACCU-CAL™ 50 radiometer is simple to operate and offers repeatable measurement of UV light. The ACCU-CAL™ 50 can measure UV light emitted from lightguides (3 mm, 5 mm, and 8 mm), UV flood systems, and UV conveyors. With a spectral sensitivity from 320 to 395 nm (UVA), the ACCU-CAL™ 50 measures intensities from 1 mW/cm² to 40 W/cm². A specially designed photo-sensor assembly protects the photo-sensor from the high temperatures sometimes associated with today's high intensity UV spot lamps.

Three Reasons to Use a UV/Visible Radiometer

- **Maintaining a Light-Curing Process** – A radiometer measures whether a light-curing system is providing intensity above the “bulb change” intensity. Radiometers provide the same monitoring control for light curing processes that thermometers provide for thermal processes.
- **Providing a Worker Friendly Light-Curing Process** – The ACCU-CAL™ 50 is sufficiently sensitive to measure the intensity of stray or reflected UV light (as little as 1 mW/cm²). Dymax recommends that worker UVA exposure not exceed 1 mW/cm². For reference, UV (320-395 nm) intensity on a sunny day can range from 2-6 mW/cm².
- **Measuring Transmission Rates Through Substrates** – A radiometer can be used to measure the transmission rates of various wavelengths through substrates that absorb UV and/or visible light. To assure an effective curing process it is critical to measure the light intensity reaching the resin below the intervening substrate.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice. FOC last update 4/22/2026.



Manufacturer:

Dymax

Product Name:

Dymax 3mm Lightguide Adapter for ACCU-CAL™ 50 UV Radiometer

Manufacturer Part Number:

39556

▶ [Click here for more details on the Dymax 3mm Lightguide Adapter for ACCU-CAL™ 50 UV Radiometer](#)

Specifications

| Specifications | |
|------------------------------|--|
| Spectral Sensitivity | 320 to 395 nm |
| Intensity Range | 1 mW/cm ² to 40 W/cm ² |
| Resolution | Intensity (1 mW/cm ² ; to three significant digits) Dose (1 mJ/cm ²) |
| Calibration Period | 12 months |
| Operating Temperature Ranges | Optometer: +5 to +40°C Detector: 120°C continuous, Peak 200°C |
| Measurement Modes | Intensity (mW/cm ² and W/cm ²) Peak Intensity (mW/cm ² and W/cm ²) Dose (J/cm ²) |
| Light Sources | Lightguides (3 mm, 5 mm, and 8 mm) Floods/Conveyors |
| Power Supply | Two (2) AA batteries |
| Battery Life | 250 hours (automatic shutoff after 1 hour) |
| Sensor Dimensions | Photo-Sensor Diameter = 9 mm Diameter = 37 mm Thickness = 8 mm Cable Length = 1 M |
| Meter Dimensions | 120 mm x 65 mm x 23 mm (Length x Width x Thickness) |

Radiometer Calibration

Dymax recommends calibrating the ACCU-CAL™ 50 radiometer annually to ensure proper operation of the instrument.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice. FOC last update 4/22/2026.



Manufacturer:

Dymax

Product Name:

Dymax 3mm Lightguide Adapter for ACCU-CAL™ 50 UV Radiometer

Manufacturer Part Number:

39556

▶ Click here for more details on the Dymax 3mm Lightguide Adapter for ACCU-CAL™ 50 UV Radiometer

Ordering Information

| Product | Part Number | Description |
|---|-------------|---|
| ACCU-CAL™ 50 for Flood Lamps and Conveyors | 39561 | Complete radiometer (without lightguide adapters or lightguide simulator*); includes storage/ carrying case |
| ACCU-CAL™ 50 for Spot and Flood Lamps and Conveyors | 39560 | Complete radiometer with lightguide adapters (3 mm, 5 mm, and 8 mm) and lightguide simulator*; includes storage/carrying case |
| Flood to Spot Adapter Kit | 39554 | Kit includes three lightguide adapters (3 mm, 5 mm, and 8 mm) and a lightguide simulator* |
| Lightguide Adapter | 39556 | Fits 3 mm ID lightguides (5 mm OD) |
| | 39557 | Fits 5 mm ID lightguides (7 mm OD) |
| | 39558 | Fits 8 mm ID lightguides (10 mm OD) |
| Lightguide Simulator (5 mm) | 38408 | 5 mm lightguide simulator with a standard D connection |


*A lightguide simulator is used to measure direct spot lamp intensity (required to calculate lightguide transmission)

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice. FOC last update 4/22/2026.



Manufacturer:
Dymax

Product Name:
Dymax 3mm Lightguide Adapter for ACCU-CAL™ 50 UV Radiometer

Manufacturer Part Number:
39556

▶ [Click here for more details on the Dymax 3mm Lightguide Adapter for ACCU-CAL™ 50 UV Radiometer](#)



ACCU-CAL™ 50 for measuring spots, floods, and conveyors PN 39560



ACCU-CAL™ 50 for measuring floods and conveyors only PN 39561

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice. FOC last update 4/22/2026.