

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (2.5g)

Manufacturer Part Number:
ET301-2.5G

▶ [Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure \(2.5g\)](#)



EPO-TEK® 301 PART B

Safety Data Sheet

A Meridian Adhesives Group Company

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 5/18/2022 Revision date: 5/22/2023 Supersedes: 5/18/2022 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : EPO-TEK® 301 PART B

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Adhesives
Recommended use : Adhesives
Restrictions on use : Not to be used for any purpose other than the one the product was designed for

1.3. Supplier

Epoxy Technology, Inc.
14 Fortune Drive
Billerica, MA 01821
USA
T 978-667-3805 - F 978-663-9782
www.epotek.com

1.4. Emergency telephone number

Emergency number : VelocityEHS: +1 (800) 255-3924, +1 (813) 248-0585

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Skin corrosion/irritation Category 1A	H314	Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Hazardous to the aquatic environment – Chronic Hazard Category 3	H412	Harmful to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H412 - Harmful to aquatic life with long lasting effects
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P272 - Contaminated work clothing must not be allowed out of the workplace.

Precautionary statements (GHS US) :

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 2/8/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (2.5g)

Manufacturer Part Number:
ET301-2.5G

▶ [Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure \(2.5g\)](#)

EPO-TEK® 301 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a poison center or doctor.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P330 - Rinse mouth.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Trimethyl-1, 6-Hexanediamine	CAS-No.: 25513-64-8	60 - 100	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412

Comments : Components not listed are either non-hazardous or are below reportable limits.
*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret
Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 2/8/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (2.5g)

Manufacturer Part Number:
ET301-2.5G

▶ [Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure \(2.5g\)](#)

EPO-TEK® 301 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 28, 2012 / Rules and Regulations

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Serious damage to eyes.
Symptoms/effects after ingestion : Burns.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Contact the professionals at Fiber Optic Center for a quote or to get more details.


23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 2/8/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (2.5g)

Manufacturer Part Number:
ET301-2.5G

▶ [Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure \(2.5g\)](#)

EPO-TEK® 301 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

EPO-TEK® 301 PART B

No additional information available

Trimethyl-1, 6-Hexanediamine (25513-64-8)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: clear
Odor	: Amine-like
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available

Contact the professionals at Fiber Optic Center for a quote or to get more details.


23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 2/8/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (2.5g)

Manufacturer Part Number:
ET301-2.5G

▶ [Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure \(2.5g\)](#)

EPO-TEK® 301 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

EPO-TEK® 301 PART B	
ATE US (oral)	910 mg/kg body weight
Trimethyl-1, 6-Hexanediamine (25513-64-8)	
LD50 oral rat	910 mg/kg body weight Animal: rat, Animal sex: male
ATE US (oral)	910 mg/kg body weight

Contact the professionals at Fiber Optic Center for a quote or to get more details.


23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 2/8/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (2.5g)

Manufacturer Part Number:
ET301-2.5G

▶ [Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure \(2.5g\)](#)

EPO-TEK® 301 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

Trimethyl-1, 6-Hexanediamine (25513-64-8)

LOAEL (oral, rat, 90 days)	60 mg/kg body weight Animal: rat
NOAEL (oral, rat, 90 days)	10 mg/kg body weight Animal: rat

Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

DOT NA No	: UN2327
UN-No. (TDG)	: UN2327
UN-No. (IMDG)	: 2327
UN-No. (IATA)	: 2327

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 2/8/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (2.5g)

Manufacturer Part Number:
ET301-2.5G

▶ [Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure \(2.5g\)](#)

EPO-TEK® 301 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Trimethylhexamethylenediamines (TRIMETHYLHEXAMETHYLENEDIAMINES)
Proper Shipping Name (TDG)	: TRIMETHYLHEXAMETHYLENEDIAMINES (TRIMETHYLHEXAMETHYLENEDIAMINES)
Proper Shipping Name (IMDG)	: TRIMETHYLHEXAMETHYLENEDIAMINES (TRIMETHYLHEXAMETHYLENEDIAMINES)
Proper Shipping Name (IATA)	: Trimethylhexamethylenediamines (TRIMETHYLHEXAMETHYLENEDIAMINES)

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



TDG
Transport hazard class(es) (TDG) : 8
Hazard labels (TDG) : 8



IMDG
Transport hazard class(es) (IMDG) : 8
Hazard labels (IMDG) : 8



IATA
Transport hazard class(es) (IATA) : 8
Hazard labels (IATA) : 8



14.4. Packing group

Packing group (DOT)	: III
Packing group (TDG)	: III
Packing group (IMDG)	: III
Packing group (IATA)	: III

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT
UN-No.(DOT) : UN2327

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 2/8/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (2.5g)

Manufacturer Part Number:
ET301-2.5G

▶ Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (2.5g)

EPO-TEK® 301 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 52 - Stow "separated from" acids
TDG	
UN-No. (TDG)	: UN2327
Explosive Limit and Limited Quantity Index	: 5 L
Excepted quantities (TDG)	: E1
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 5 L
Emergency Response Guide (ERG) Number	: 153
IMDG	
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Colourless, slightly hygroscopic, combustible liquids. Miscible with water. Irritating to skin, eyes and mucous membranes.
IATA	
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y841
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 852
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 856
CAO max net quantity (IATA)	: 60L
Special provision (IATA)	: A803
ERG code (IATA)	: 8L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 2/8/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure (2.5g)

Manufacturer Part Number:
ET301-2.5G

▶ [Click here for more details on the EPO-TEK® 301 Spectrally Transparent Epoxy, Room Temperature Cure \(2.5g\)](#)

EPO-TEK® 301 PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

Trimethyl-1, 6-Hexanediamine (25513-64-8)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/22/2023

Full text of H-phrases

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 2/8/2026.