

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Manufacturer Part Number:
ET305-4G

▶ [Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure \(4g\)](#)

Revision date: 10/9/2019

Revision: 2

Supersedes date: 9/6/2014



SAFETY DATA SHEET EPO-TEK® 305 Part B

1. Identification

Product identifier

Product name EPO-TEK® 305 Part B
Product number 305/B

Recommended use of the chemical and restrictions on use

Application Adhesive.
Uses advised against Use only for intended applications.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.
14 Fortune Drive
Billerica, MA 01821
USA
(978) 667-3805
(978) 663-9782
www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone ChemTel: +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified
Health hazards Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317
Environmental hazards Aquatic Chronic 3 - H412

Label elements

Hazard symbols



Signal word Danger

Hazard statements H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com
508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 3/1/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Manufacturer Part Number:
ET305-4G

▶ [Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure \(4g\)](#)

Revision date: 10/9/2019

Revision: 2

Supersedes date: 9/5/2014

EPO-TEK® 305 Part B

Precautionary statements

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501 Dispose of contents/ container in accordance with national regulations.

Contains Trimethyl-1, 6-Hexanediamine

3. Composition/information on ingredients

Mixtures

Trimethyl-1, 6-Hexanediamine	60-100%
CAS number: 25513-64-8	

Classification

Acute Tox. 4 - H302
Skin Corr. 1B - H314
Eye Dam. 1 - H318
Skin Sens. 1 - H317
Aquatic Chronic 3 - H412

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

Inhalation Move affected person to fresh air at once. Rinse nose and mouth with water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Keep affected person warm and at rest. Get medical attention immediately.

Ingestion Do not induce vomiting. Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention immediately.

Skin Contact Remove affected person from source of contamination. Rinse immediately with plenty of water. Get medical attention promptly if symptoms occur after washing.

Eye contact Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

Most important symptoms and effects, both acute and delayed

Inhalation Gas or vapor in high concentrations may irritate the respiratory system. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.

Ingestion Harmful if swallowed. May cause stomach pain or vomiting. May cause chemical burns in mouth, esophagus and stomach. May cause nausea, headache, dizziness and intoxication.

Skin contact Causes severe burns. May cause an allergic skin reaction. May cause sensitisation by skin contact.

Eye contact Causes serious eye damage.

Indication of immediate medical attention and special treatment needed

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 3/1/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Manufacturer Part Number:
ET305-4G

▶ [Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure \(4g\)](#)

Revision date: 10/9/2019

Revision: 2

Supersedes date: 9/5/2014

EPO-TEK® 305 Part B

Notes for the doctor Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Dry chemicals. Foam. Water spray.

Special hazards arising from the substance or mixture

Hazardous combustion products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapors.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Avoid release to the environment.

Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Avoid contamination of ponds or watercourses with washing down water.

Reference to other sections For personal protection, see Section 8.

7. Handling and storage

Precautions for safe handling

Usage precautions Handle all packages and containers carefully to minimize spills. Avoid inhalation of vapors and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Wash promptly if skin becomes contaminated. Wash hands thoroughly after handling. Take off contaminated clothing and wash before reuse. Use appropriate skin cream to prevent drying of skin.

Conditions for safe storage, including any incompatibilities

Storage precautions Store at room temperature. Keep container tightly sealed when not in use.

Storage class Corrosive storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure controls/Personal protection

Ingredient comments No exposure limits known for ingredient(s).

Exposure controls

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 3/1/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Manufacturer Part Number:
ET305-4G

▶ [Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure \(4g\)](#)

Revision date: 10/9/2019

Revision: 2

Supersedes date: 9/5/2014

EPO-TEK® 305 Part B

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eyeface protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body protection

Wear appropriate clothing to prevent skin contamination. Provide eyewash station.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes wet or contaminated.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Liquid.
Color	Clear.
Odor	Amine.
Odor threshold	No specific test data are available.
pH	No specific test data are available.
Melting point	No specific test data are available.
Initial boiling point and range	No specific test data are available.
Flash point	232°C
Evaporation rate	<BuAc
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	No specific test data are available.
Vapor pressure	No specific test data are available.
Vapor density	>1
Relative density	No specific test data are available.
Solubility(ies)	Insoluble in water.
Partition coefficient	No specific test data are available.
Auto-ignition temperature	No specific test data are available.
Decomposition Temperature	No specific test data are available.
Viscosity	No specific test data are available.
Other information	None.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com
508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 3/1/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Manufacturer Part Number:
ET305-4G

▶ [Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure \(4g\)](#)

Revision date: 10/9/2019

Revision: 2

Supersedes date: 9/5/2014

EPO-TEK® 305 Part B

10. Stability and reactivity

Reactivity	The following materials may react violently with the product: Acids. Alkalis. Strong oxidizing agents. Strong reducing agents.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	Will not polymerize.
Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid heat, flames and other sources of ignition.
Materials to avoid	Strong acids. Strong alkalis. Strong oxidizing agents. Strong reducing agents.
Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 500.0

Inhalation May cause respiratory system irritation.

Ingestion Causes burns. May cause chemical burns in mouth and throat. May cause stomach pain or vomiting.

Skin Contact May cause allergic contact eczema. May cause sensitisation by skin contact. Causes burns.

Eye contact Severe irritation, burning and tearing. Causes burns.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Acute aquatic toxicity

Acute toxicity - fish No information available.

Persistence and degradability

Persistence and degradability The product is biodegradable.

Bioaccumulative potential

Bio-Accumulative Potential The product is not bioaccumulating.

Partition coefficient No specific test data are available.

Mobility in soil

Mobility Mobile.

Other adverse effects

Other adverse effects Not known.

13. Disposal considerations

Waste treatment methods

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 3/1/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Manufacturer Part Number:
ET305-4G

▶ [Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure \(4g\)](#)

Revision date: 10/9/2019

Revision: 2

Supersedes date: 9/5/2014

EPO-TEK® 305 Part B

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

UN Number

UN No. (TDG) 2327

UN No. (IMDG) 2327

UN No. (ICAO) 2327

UN No. (DOT) UN2327

UN proper shipping name

Proper shipping name (TDG) TRIMETHYLHEXAMETHYLENEDIAMINES

Proper shipping name (IMDG) TRIMETHYLHEXAMETHYLENEDIAMINES

Proper shipping name (ICAO) TRIMETHYLHEXAMETHYLENEDIAMINES

Proper shipping name (DOT) TRIMETHYLHEXAMETHYLENEDIAMINES

Transport hazard class(es)

DOT hazard class 8

DOT hazard label 8

TDG class 8

TDG label(s) 8

IMDG Class 8

ICAO class/division 8

Transport labels



DOT transport labels



Packing group

TDG Packing Group III

IMDG packing group III

ICAO packing group III

DOT packing group III

Environmental hazards

Environmentally Hazardous Substance
No.

Special precautions for user

EmS F-A, S-B

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 3/1/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Manufacturer Part Number:
ET305-4G

▶ [Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure \(4g\)](#)

EPO-TEK® 305 Part B

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Regulatory References Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of Intellectual Property Rights (TRIPS), Section 7, Art. 39.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities
None of the ingredients are listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)
None of the ingredients are listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities
None of the ingredients are listed.

SARA 313 Emission Reporting
None of the ingredients are listed.

CAA Accidental Release Prevention
None of the ingredients are listed.

OSHA Highly Hazardous Chemicals
None of the ingredients are listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins
None of the ingredients are listed.

California Air Toxics "Hot Spots" (A-I)
None of the ingredients are listed.

California Air Toxics "Hot Spots" (A-II)
None of the ingredients are listed.

Massachusetts "Right To Know" List
None of the ingredients are listed.

Rhode Island "Right To Know" List
None of the ingredients are listed.

Minnesota "Right To Know" List
None of the ingredients are listed.

New Jersey "Right To Know" List
The following ingredients are listed:

Trimethyl-1, 6-Hexanediamine

Pennsylvania "Right To Know" List
None of the ingredients are listed.

Inventories

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 3/1/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Manufacturer Part Number:
ET305-4G

▶ [Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure \(4g\)](#)

Revision date: 10/9/2019

Revision: 2

Supersedes date: 9/5/2014

EPO-TEK® 305 Part B

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed.

Australia - AICS

All the ingredients are listed or exempt.

Japan - ENCS

None of the ingredients are listed.

Korea - KECI

None of the ingredients are listed.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

None of the ingredients are listed.

16. Other information

Revision date	10/9/2019
Revision	2
Supersedes date	9/5/2014
Hazard statements in full	H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H412 Harmful to aquatic life with long lasting effects.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 3/1/2026.