

# SAFETY DATA SHEET (SDS)



**Manufacturer:**  
Epoxy Technology

**Product Name:**  
EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure (4g)

**Manufacturer Part Number:**  
ET353NDBLK-4G

▶ [Click here for more details on the EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure \(4g\)](#)



## EPO-TEK® 353ND BLACK PART A Safety Data Sheet

A Meridian Adhesives Group Company

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Issue date: 7/13/2022 Revision date: 6/7/2023 Supersedes: 7/13/2022 Version: 2.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : EPO-TEK® 353ND BLACK PART A

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Adhesives  
Recommended use : Adhesives  
Restrictions on use : Not to be used for any purpose other than the one the product was designed for

#### 1.3. Supplier

**Manufacturer**  
Epoxy Technology, Inc.  
14 Fortune Drive  
Billerica, MA 01821  
USA  
T 978-667-3805 - F 978-663-9782  
[www.epotek.com](http://www.epotek.com)

#### 1.4. Emergency telephone number

Emergency number : VelocityEHS: +1 (800) 255-3924, +1 (813) 248-0585

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Hazardous to the aquatic environment – Chronic Hazard Category 2	H411	Toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS US) : P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 - If on skin: Wash with plenty of water.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P332+P313 - If skin irritation occurs: Get medical advice/attention.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • [focenter.com](http://focenter.com)

508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)



Data is subject to change without notice. FOC last update 2/8/2026.

# SAFETY DATA SHEET (SDS)



**Manufacturer:**  
Epoxy Technology

**Product Name:**  
EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure (4g)

**Manufacturer Part Number:**  
ET353NDBLK-4G

▶ [Click here for more details on the EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure \(4g\)](#)

## EPO-TEK® 353ND BLACK PART A

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 28, 2012 / Rules and Regulations

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P363 - Wash contaminated clothing before reuse.  
P391 - Collect spillage.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

#### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Epoxy phenol novolac resin	CAS-No.: 9003-36-5	≥ 60	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Comments : Components not listed are either non-hazardous or are below reportable limits.  
\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret  
Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse eyes with water as a precaution.  
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • [focenter.com](http://focenter.com)

508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)



Data is subject to change without notice. FOC last update 2/8/2026.

# SAFETY DATA SHEET (SDS)



**Manufacturer:**  
Epoxy Technology

**Product Name:**  
EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure (4g)

**Manufacturer Part Number:**  
ET353NDBLK-4G

▶ [Click here for more details on the EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure \(4g\)](#)

## EPO-TEK® 353ND BLACK PART A

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.  
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

EPO-TEK® 353ND BLACK PART A

No additional information available

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • [focenter.com](http://focenter.com)

508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)



Data is subject to change without notice. FOC last update 2/8/2026.

# SAFETY DATA SHEET (SDS)



**Manufacturer:**  
Epoxy Technology

**Product Name:**  
EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure (4g)

**Manufacturer Part Number:**  
ET353NDBLK-4G

▶ [Click here for more details on the EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure \(4g\)](#)

## EPO-TEK® 353ND BLACK PART A

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### Epoxy phenol novolac resin (9003-36-5)

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures/Personal protective equipment

##### Hand protection:

Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear

##### Eye protection:

Safety glasses

##### Skin and body protection:

Wear suitable protective clothing

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Black
Odor	: Mild odor
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • [focenter.com](http://focenter.com)

508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)



Data is subject to change without notice. FOC last update 2/8/2026.

# SAFETY DATA SHEET (SDS)



**Manufacturer:**  
Epoxy Technology

**Product Name:**  
EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure (4g)

**Manufacturer Part Number:**  
ET353NDBLK-4G

▶ [Click here for more details on the EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure \(4g\)](#)

## EPO-TEK® 353ND BLACK PART A

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 28, 2012 / Rules and Regulations

Explosive properties : No data available  
Oxidizing properties : No data available

#### 9.2. Other information

No additional information available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified  
Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitization : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified

#### Epoxy phenol novolac resin (9003-36-5)

NOAEL (oral, rat, 90 days)	≈ 250 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
----------------------------	--

Aspiration hazard : Not classified  
Viscosity, kinematic : No data available  
Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • [focenter.com](http://focenter.com)

508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)



Data is subject to change without notice. FOC last update 2/8/2026.

# SAFETY DATA SHEET (SDS)



**Manufacturer:**  
Epoxy Technology

**Product Name:**  
EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure (4g)

**Manufacturer Part Number:**  
ET353NDBLK-4G

▶ [Click here for more details on the EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure \(4g\)](#)

## EPO-TEK® 353ND BLACK PART A

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### SECTION 12: Ecological information

##### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

##### Epoxy phenol novolac resin (9003-36-5)

LC50 - Fish [1]	1.9 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Semi-static system, Fresh water, Weight of evidence)
EC50 - Crustacea [1]	3.5 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Weight of evidence, GLP)
LC50 - Fish [2]	1000 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

##### 12.2. Persistence and degradability

##### Epoxy phenol novolac resin (9003-36-5)

Persistence and degradability : Not readily biodegradable in water.

##### 12.3. Bioaccumulative potential

##### Epoxy phenol novolac resin (9003-36-5)

Partition coefficient n-octanol/water (Log Pow)	2.7 – 3.6 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

##### 12.4. Mobility in soil

##### Epoxy phenol novolac resin (9003-36-5)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.65 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.

##### 12.5. Other adverse effects

No additional information available

#### SECTION 13: Disposal considerations

##### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

#### SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

##### 14.1. UN number

DOT NA No : UN3082  
UN-No. (TDG) : UN3082

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • [focenter.com](http://focenter.com)

508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)



Data is subject to change without notice. FOC last update 2/8/2026.

# SAFETY DATA SHEET (SDS)



**Manufacturer:**  
Epoxy Technology

**Product Name:**  
EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure (4g)

**Manufacturer Part Number:**  
ET353NDBLK-4G

▶ Click here for more details on the EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure (4g)

## EPO-TEK® 353ND BLACK PART A

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No. (IMDG) : 3082  
UN-No. (IATA) : 3082

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Environmentally hazardous substances, liquid, n.o.s.  
Proper Shipping Name (TDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy Phenol Novolac)  
Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s. (Epoxy Phenol Novolac)

#### 14.3. Transport hazard class(es)

DOT  
Transport hazard class(es) (DOT) : 9  
Hazard labels (DOT) : 9



TDG  
Transport hazard class(es) (TDG) : 9  
Hazard labels (TDG) : 9



IMDG  
Transport hazard class(es) (IMDG) : 9  
Hazard labels (IMDG) : 9



IATA  
Transport hazard class(es) (IATA) : 9  
Hazard labels (IATA) : 9



#### 14.4. Packing group

Packing group (DOT) : III  
Packing group (TDG) : III  
Packing group (IMDG) : III  
Packing group (IATA) : III

#### 14.5. Environmental hazards

Dangerous for the environment : Yes

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • [focenter.com](http://focenter.com)

508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)



Data is subject to change without notice. FOC last update 2/8/2026.

# SAFETY DATA SHEET (SDS)



**Manufacturer:**  
Epoxy Technology

**Product Name:**  
EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure (4g)

**Manufacturer Part Number:**  
ET353NDBLK-4G

▶ [Click here for more details on the EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure \(4g\)](#)

## EPO-TEK® 353ND BLACK PART A

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Marine pollutant : Yes



Other information : No supplementary information available.

#### 14.6. Special precautions for user

**DOT**  
UN-No.(DOT) : UN3082  
DOT Special Provisions (49 CFR 172.102) : 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.  
146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.  
173 - An appropriate generic entry may be used for this material.  
335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s.," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging.  
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 155  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203  
DOT Packaging Bulk (49 CFR 173.xxx) : 241  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : No Limit  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : No Limit  
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

**TDG**  
UN-No. (TDG) : UN3082

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • [focenter.com](http://focenter.com)

508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)



Data is subject to change without notice. FOC last update 2/8/2026.

# SAFETY DATA SHEET (SDS)



**Manufacturer:**  
Epoxy Technology

**Product Name:**  
EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure (4g)

**Manufacturer Part Number:**  
ET353NDBLK-4G

▶ [Click here for more details on the EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure \(4g\)](#)

## EPO-TEK® 353ND BLACK PART A

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>TDG Special Provisions</b>	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S.; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S.; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S.; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S.; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS, 99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. may be handled, offered for transport or transported as UN3077 if there is no visible liquid when the dangerous goods are loaded into a means containment and during transport. (2) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.
<b>Explosive Limit and Limited Quantity Index</b>	: 5 L
<b>Excepted quantities (TDG)</b>	: E1
<b>Emergency Response Guide (ERG) Number</b>	: 171
<b>IMDG</b>	
Special provision (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
Stowage category (IMDG)	: A
<b>IATA</b>	
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • [focenter.com](http://focenter.com)

508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)



Data is subject to change without notice. FOC last update 2/8/2026.

# SAFETY DATA SHEET (SDS)



**Manufacturer:**  
Epoxy Technology

**Product Name:**  
EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure (4g)

**Manufacturer Part Number:**  
ET353NDBLK-4G

▶ [Click here for more details on the EPO-TEK® 353ND High Temperature Black Epoxy, Heat Cure \(4g\)](#)

## EPO-TEK® 353ND BLACK PART A

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Special provision (IATA) : A97, A158, A197, A215  
ERG code (IATA) : 9L

#### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

#### 15.2. International regulations

##### CANADA

#### Epoxy phenol novolac resin (9003-36-5)

Listed on the Canadian DSL (Domestic Substances List)

##### EU-Regulations

No additional information available

##### National regulations

#### Epoxy phenol novolac resin (9003-36-5)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Revision date : 06/07/2023

Full text of H-phrases	
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • [focenter.com](http://focenter.com)

508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)



Data is subject to change without notice. FOC last update 2/8/2026.