

## **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

### **Manufacturer Part Number:**

ET353NDBLK-8OZ

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)



## **EPO-TEK® 353ND BLACK PART B**

Safety Data Sheet

A Meridian Adhesives Group Company

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 7/13/2022 Revision date: 6/7/2023 Supersedes: 7/13/2022 Version: 2.0

#### SECTION 1: Identification

#### 1.1. Identification

Product form

Mixture

Product name

EPO-TEK® 353ND BLACK PART B

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture

: Adhesives

Recommended use Restrictions on use : Adhesives

: Not to be used for any purpose other than the one the product was designed for

#### 1.3. Supplier

#### Manufacturer

Epoxy Technology, Inc. 14 Fortune Drive

Billerica, MA 01821

USA

T 978-667-3805 - F 978-663-9782

www.epotek.com

#### 1.4. Emergency telephone number

Emergency number : VelocityEHS: +1 (800) 255-3924, +1 (813) 248-0585

#### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

#### GHS US classification

Acute toxicity (oral) Category 4 H302 Harmful if swallowed

Skin corrosion/irritation Category 1B H314 Causes severe skin burns and eye damage Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage

Skin sensitization, Category 1 H317 May cause an allergic skin reaction
Carcinogenicity Category 2 H351 Suspected of causing cancer
Reproductive toxicity Category 1B H360 May damage fertility or the unborn child

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

### GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US)

Precautionary statements (GHS US)

Hazard statements (GHS US)

: H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction H318 - Causes serious eye damage

H351 - Suspected of causing cancer

H360 - May damage fertility or the unborn child : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.







**Manufacturer:** 

**Epoxy Technology** 

**Product Name:** 

EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

**Manufacturer Part Number:** 

ET353NDBLK-8OZ

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

## **EPO-TEK® 353ND BLACK PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 - Wash hands, forearms and face thoroughly after handling

P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P302+P352 - If on skin: Wash with plenty of water.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a poison center or doctor.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P330 - Rinse mouth.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

#### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Substituted imidazole*	CAS-No.: Trade Secret	30 – 60	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1B, H317
Imidazole	CAS-No.: 288-32-4	≥ 30	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Repr. 1B, H360
Substituted imidazole*	CAS-No.: Trade Secret	5 – 10	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Carc. 2, H351





Manufacturer:

**Epoxy Technology** 

**Product Name:** 

EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

**Manufacturer Part Number:** 

ET353NDBLK-8OZ

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

### **EPO-TEK® 353ND BLACK PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Substituted imidazole*	CAS-No.: Trade Secret	< 5	Acute Tox. 3 (Oral), H301 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Substituted anhydride*	CAS-No.: Trade Secret	< 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314

\*Chemical name. CAS number and/or exact concentration have been withheld as a trade secret

Comments : Components not listed are either non-hazardous or are below reportable limits

Full text of hazard classes and H-statements : see section 16

#### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures after eye contact

First-aid measures general

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

: Call a physician immediately.

do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Rinse mouth. Do not induce vomiting. Call a physician immediately.

## 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Serious damage to eyes.

Symptoms/effects after ingestion : Burns.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

#### **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released

#### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

#### SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Do not

breathe dust/fume/gas/mist/vapors/spray.





**Manufacturer:** 

**Epoxy Technology** 

**Product Name:** 

EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

**Manufacturer Part Number:** 

ET353NDBLK-8OZ

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

## **EPO-TEK® 353ND BLACK PART B**

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

#### SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

Hygiene measures

: Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store locked up. Store in a well-ventilated place. Keep cool.

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

### **EPO-TEK® 353ND BLACK PART B**

No additional information available

#### Substituted anhydride

No additional information available

#### Substituted imidazole

No additional information available

## Substituted imidazole

No additional information available

#### Substituted imidazole

No additional information available

#### Imidazole (288-32-4)

No additional information available







## **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

## **Manufacturer Part Number:**

ET353NDBLK-8OZ

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (80z)

## **EPO-TEK® 353ND BLACK PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

#### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection.

#### Personal protective equipment symbol(s):



Physical state

Oxidizing properties





## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Color amber Odor slight Odor threshold No data available pΗ No data available Melting point No data available Freezing point No data available **Boiling point** No data available Flash point : No data available Relative evaporation rate (butyl acetate=1) No data available Flammability Not applicable. No data available Vapor pressure Relative vapor density at 20°C No data available No data available Relative density Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available : No data available Decomposition temperature Viscosity, kinematic No data available Viscosity, dynamic : No data available Explosion limits No data available Explosive properties : No data available

Contact the professionals at Fiber Optic Center for a quote or to get more details.

: No data avallable

Liquid





Manufacturer:

**Epoxy Technology** 

**Product Name:** 

EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

**Manufacturer Part Number:** 

ET353NDBLK-8OZ

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (80z)

## **EPO-TEK® 353ND BLACK PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 9.2. Other information

No additional information available

#### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

#### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced

## SECTION 11: Toxicological information

11.1. Information on toxicological effects	
Acute toxicity (dermal)	Harmful if swallowed. Not classified Not classified
EPO-TEK® 353ND BLACK PART B	
ATE US (oral)	490.339 mg/kg body weight
Substituted anhydride	
LD50 oral rat	≈ 1144 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other:
LD50 dermal rabbit	400 – 640 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
ATE US (oral)	500 mg/kg body weight
ATE US (dermal)	400 mg/kg body weight
Substituted imidazole	
LD50 oral rat	350 mg/kg Source: IUCLID
LD50 dermal rabbit	440 mg/kg Source: IUCLID
ATE US (oral)	173 mg/kg body weight
ATE US (dermal)	440 mg/kg body weight





**Manufacturer:** Epoxy Technology

## **Product Name:**

EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

## **Manufacturer Part Number:**

ET353NDBLK-8OZ

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

## **EPO-TEK® 353ND BLACK PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

I DEG	704 4 (5 )   1   2   4   0   0   0   0   0   0   0   0   0
LD50 oral rat	731 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral
LD50 dermal rabbit	> 400 mg/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal)
LC50 Inhalation - Rat	> 0.03 mg/l (Equivalent or similar to OECD 403, 8 h, Rat, Male / female, Experimental value (maximum achievable concentration), Inhalation (vapours))
ATE US (oral)	731 mg/kg body weight
Substituted imidazole	
ATE US (oral)	100 mg/kg body weight
lmidazole (288-32-4)	
LD50 oral rat	970 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 7 day(s))
ATE US (oral)	960 mg/kg body weight
Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Substituted imidazole	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: May damage fertility or the unborn child.
STOT-single exposure	: Not classified
Substituted imidazole	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Substituted anhydride	
NOAEL (oral,rat,90 days)	90 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
Substituted imidazole	
NOAEL (oral,rat,90 days)	150 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:EPA OPPTS 870.3650 (Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test)
lmidazole (288-32-4)	
NOAEL (oral,rat,90 days)	60 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Aspiration hazard	: Not classified
/iscosity, kinematic	: No data available
Symptoms/effects after skin contact	Burns. May cause an allergic skin reaction.     Serious damage to eyes.
Symptoms/effects after eye contact	





Manufacturer:

**Epoxy Technology** 

**Product Name:** 

EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

**Manufacturer Part Number:** 

ET353NDBLK-8OZ

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

## **EPO-TEK® 353ND BLACK PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.1. Toxicity	
cology - general	: Before neutralisation, the product may represent a danger to aquatic organisms.
Substituted anhydride	
LC50 - Fish [1]	100 – 215 mg/l Test organisms (species): Leuciscus idus
EC50 - Crustacea [1]	267.94 mg/l Test organisms (species): Daphnia magna
Substituted imidazole	
LC50 - Fish [1]	0.34 mg/l Source: IUCLID
EC50 - Crustacea [1]	180 mg/l Source: IUCLID
Substituted imidazole	
LC50 - Fish [1]	68.1 mg/l (DIN 38412-15, 96 h, Leuciscus idus, Static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	297.3 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimenta value)
Imidazole (288-32-4)	
LC50 - Fish [1]	283.6 mg/l (48 h, Leuciscus idus, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	341.5 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimenta value, Locomotor effect)
ErC50 algae	133 mg/l (DIN 38412: German standard methods for the examination of water, waste water sludge, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)
NOEC chronic algae	25 mg/l
12.2. Persistence and degradability	
Substituted anhydride	
Persistence and degradability	Not readily biodegradable in water.
Substituted imidazole	
Persistence and degradability	Inherently biodegradable.
Biochemical oxygen demand (BOD)	0.000002 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	0.0015 g O <sub>2</sub> /g substance
Substituted imidazole	
Persistence and degradability	Readily biodegradable in water.
Imidazole (288-32-4)	
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.
12.3. Bioaccumulative potential	
Substituted anhydride	
Partition coefficient n-octanol/water (Log Pow)	-0.06 Source: ChemiDplus





**Manufacturer:** Epoxy Technology

## **Product Name:**

EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

## **Manufacturer Part Number:**

ET353NDBLK-8OZ

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

## **EPO-TEK® 353ND BLACK PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Substituted imidazole		
Partition coefficient n-octanol/water (Log Pow)	0.35 (Experimental value)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Substituted imidazole		
Partition coefficient n-octanol/water (Log Pow)	1.13 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Imidazole (288-32-4)		
Partition coefficient n-octanol/water (Log Pow)	-0.02 (Weight of evidence approach, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)	
Bioaccumulative potential	Not bioaccumulative.	

#### 12.4. Mobility in soil

Substituted anhydride		
Mobility in soil	15.75 Source: Quantitative Structure Activity Relation	
Substituted imidazole		
Mobility in soil	28.23 Source: EPI SUITE	
Ecology - soil	No (test)data on mobility of the substance available.	
Substituted imidazole		
Organic Carbon Normalized Adsorption Coefficient (Log Koc, Calculated value, pH = 7)		
Ecology - soil	Low potential for mobility in soil.	
Imidazole (288-32-4)		
Surface tension	No data available in the literature	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.36 – 2.32 (log Koc, Calculated value)	
Ecology - soil	Low potential for adsorption in soil.	

#### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

## 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

## 14.1. UN number

DOT NA No : UN3082







# **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

## **Manufacturer Part Number:**

ET353NDBLK-8OZ

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

## **EPO-TEK® 353ND BLACK PART B**

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No. (TDG) : UN3082 UN-No. (IMDG) : 3082 UN-No. (IATA) : 3082

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) Environmentally hazardous substances, liquid, n.o.s. (Imidazole) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. Proper Shipping Name (TDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Imidazole) Proper Shipping Name (IMDG)

Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s. (Imidazole)

#### 14.3. Transport hazard class(es)

Transport hazard class(es) (DOT) Hazard labels (DOT)



TDG

Transport hazard class(es) (TDG)

Hazard labels (TDG)



Transport hazard class(es) (IMDG)

Hazard labels (IMDG)



IATA

Transport hazard class(es) (IATA)

Hazard labels (IATA)



#### 14.4. Packing group

: 111 Packing group (DOT) Packing group (TDG) : 111 Packing group (IMDG) : 111 Packing group (IATA) : 111

#### 14.5. Environmental hazards

Other information : No supplementary information available.



## **Manufacturer:**

**Epoxy Technology** 

#### **Product Name:**

EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

### **Manufacturer Part Number:**

ET353NDBLK-8OZ

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

## **EPO-TEK® 353ND BLACK PART B**

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### 14.6. Special precautions for user

DOT

UN-No.(DOT)

DOT Special Provisions (49 CFR 172.102)

: UN3082

: 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.

146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.

173 - An appropriate generic entry may be used for this material.

335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T4 - 2.65 178.274(d)(2) Normal...... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP

DOT Packaging Exceptions (49 CFR 173.xxx) : 155
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241
DOT Quantity Limitations Passenger aircraft/rail (49 : No Limit
CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 : No Limit

CFR 175 75)

CFR 1/5./5)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

TDG

UN-No. (TDG) : UN3082





# Manufacturer:

**Epoxy Technology** 

#### **Product Name:**

EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

## **Manufacturer Part Number:**

ET353NDBLK-8OZ

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (80z)

## **EPO-TEK® 353ND BLACK PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions

: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks).
(2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name:

(a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S;

(b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S;

(c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S;

(d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or

(e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S.

(3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment:

(a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or

(b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS,99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, may be handled, offered for transport or transported as UN3077 if there is no visible liquid when the dangerous goods are loaded into a means containment and during transport.

(2) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

Explosive Limit and Limited Quantity Index Excepted quantities (TDG) Emergency Response Guide (ERG) Number

IMDG

 Special provision (IMDG)
 : 274, 335, 969

 Limited quantities (IMDG)
 : 5 L

 Excepted quantities (IMDG)
 : E1

 Packing instructions (IMDG)
 : LP01, P001

 Packing provisions (IMDG)
 : PP1

 IBC packing instructions (IMDG)
 : IBC03

 Tank instructions (IMDG)
 : T4

 Tank special provisions (IMDG)
 : TP1, TP29

EmS-No. (Fire) : F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE

5L

E1

: 171

EmS-No. (Spillage) : S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS

Stowage category (IMDG)

IATA

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y964
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 964
PCA max net quantity (IATA) : 450L
CAO packing instructions (IATA) : 964
CAO max net quantity (IATA) : 450L





Manufacturer:

**Epoxy Technology** 

**Product Name:** 

EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

**Manufacturer Part Number:** 

ET353NDBLK-8OZ

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (80z)

## **EPO-TEK® 353ND BLACK PART B**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Special provision (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

#### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

#### 15.2. International regulations

CANADA

#### Substituted anhydride

Listed on the Canadian DSL (Domestic Substances List)

#### Substituted imidazole

Listed on the Canadian NDSL (Non-Domestic Substances List)

#### Substituted imidazole

Listed on the Canadian DSL (Domestic Substances List)

### Substituted imidazole

Listed on the Canadian DSL (Domestic Substances List)

#### Imidazole (288-32-4)

Listed on the Canadian DSL (Domestic Substances List)

#### **EU-Regulations**

No additional information available

National regulations

#### Substituted anhydride

Listed on INSQ (Mexican National Inventory of Chemical Substances)

### Substituted imidazole

Listed on IARC (International Agency for Research on Cancer)

#### Imidazole (288-32-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)





Manufacturer:

**Epoxy Technology** 

**Product Name:** 

EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

**Manufacturer Part Number:** 

ET353NDBLK-8OZ

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (8oz)

## **EPO-TEK® 353ND BLACK PART B**

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 15.3. US State regulations

MARNING:

This product can expose you to Substituted imidazole, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

#### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date : 06/07/2023

Full text of H-phrases		
H301	Toxic if swallowed	
H302	Harmful if swallowed	
H311	Toxic in contact with skin	
H312	Harmful in contact with skin	
H314	Causes severe skin burns and eye damage	
H315	Causes skin irritation	
H317	May cause an allergic skin reaction	
H318	Causes serious eye damage	
H335	May cause respiratory irritation	
H351	Suspected of causing cancer	
H360	May damage fertility or the unborn child	

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

