

## **Manufacturer:**

**Epoxy Technology** 

# **Product Name:**

EPO-TEK® HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

### **Manufacturer Part Number:**

ETHYB-353ND-TX2

Click here for more details on the EPO-TEK® HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Revision date: 12/15/2016

Revision: 1



## SAFETY DATA SHEET EPO-TEK HYB-353ND-TX2 PMF Syringe

1. Identification

Product identifier

Product name EPO-TEK HYB-353ND-TX2 PMF Syringe

Product number HYB-353ND-TX2

Recommended use of the chemical and restrictions on use

pplication Adhesive

Details of the supplier of the safety data sheet

upplier Epoxy Technology, Inc.

14 Fortune Drive Billerica, MA 01821

USA (978) 6

(978) 667-3805 (978) 663-9782

www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classifie

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Skin Sens. 1 - H317 Repr. 2 - H361f

Environmental hazards Aquatic Chronic 2 - H411

Label element

Pictogram








Signal word

warning

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H361f Suspected of damaging fertility.

H411 Toxic to aquatic life with long lasting effects.







## **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

### **Manufacturer Part Number:**

ETHYB-353ND-TX2

Click here for more details on the EPO-TEK\* HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Revision date: 12/15/2016

### EPO-TEK HYB-353ND-TX2 PMF Syringe

Revision: 1

Precautionary statements P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 If on skin: Wash with plenty of water

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337+P313 If eye irritation persists: Get medical advice/ attention.
P501 Dispose of contents/ container in accordance with national regulations

Contains Epoxy Acrylate, Epoxy Acrylate, Photoinitiator

Other hazards

Hazards not otherwise Contains epoxy constituents. May produce an allergic reaction.

classified (HNOC)

### 3. Composition/information on ingredients

#### Mixtures

Epoxy Acrylate	30-60%
CAS number: Proprietary	
Classification	
Skin Sens. 1 - H317	
Aquatic Chronic 3 - H412	

Epoxy Phenol Novolac 10-30%

CAS number: 9003-36-5

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

Epoxy Acrylate 10-30%

CAS number: Proprietary

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H335 Aquatic Chronic 2 - H411









### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

### **Manufacturer Part Number:**

ETHYB-353ND-TX2

 $Click here for more details on the EPO-TEK ^* HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat \& UV Cure - Pre-Mixed and Frozen (3cc Syringe) a$ 

Revision date: 12/15/2016

Revision:

### EPO-TEK HYB-353ND-TX2 PMF Syringe

Imidazole Blend	1-5%
CAS number: Proprietary	
Classification	
Acute Tox. 4 - H302	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
STOT SE 3 - H335	
Photoinitiator	1-5%
CAS number: Proprietary	
Classification	
Acute Tox. 4 - H302	
Photoinitiator	1-5%
CAS number: Proprietary	
Classification	

The full text for all hazard statements is displayed in Section 16

### 4. First-aid measures

## Description of first aid measures

Inhalation Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical

attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse

mouth thoroughly with water. Get medical attention if any discomfort continues.

Skin Contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

### Most important symptoms and effects, both acute and delayed

General information May damage fertility or the unborn child.

Inhalation Gas or vapor in high concentrations may irritate the respiratory system. Inhalation of dust

during cutting, grinding or sanding operations involving this product may cause irritation of the

respiratory tract.

Ingestion May cause discomfort if swallowed.

Skin contact Causes skin irritation. May cause sensitisation by skin contact.

Eye contact Causes serious eye irritation.

Indication of immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

5. Fire-fighting measures

3/9

Data is subject to change without notice.





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat & UV Cure -Pre-Mixed and Frozen (3cc Syringe)

### **Manufacturer Part Number:**

ETHYB-353ND-TX2

Click here for more details on the EPO-TEK® HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Revision date: 12/15/2016

### EPO-TEK HYB-353ND-TX2 PMF Syringe

Extinguishing media

Suitable extinguishing media Dry chemicals. Foam. Carbon dioxide (CO2).

Special hazards arising from the substance or mixture

Hazardous combustion Thermal decomposition or combustion products may include the following substances: products

Carbon dioxide (CO2). Carbon monoxide (CO).

Advice for firefighters

Protective actions during Avoid breathing fire gases or vapors. Use water to keep fire exposed containers cool and

firefiahtina disperse vapors.

Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

for firefighters clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Keep

unnecessary and unprotected personnel away from the spillage. Avoid contact with skin and

Environmental precautions

Environmental precautions Avoid discharge to the aquatic environment.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into

containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering

drains, sewers or watercourses.

Reference to other sections For personal protection, see Section 8.

7. Handling and storage

Precautions for safe handling

Usage precautions Handle all packages and containers carefully to minimize spills. Avoid contact with skin and

eves. Wear protective clothing as described in Section 8 of this safety data sheet

Advice on general occupational hygiene Provide eyewash station. Do not eat, drink or smoke when using this product. Wash promptly with soap and water if skin becomes contaminated. Wash after use and before eating,

smoking and using the toilet. Wash contaminated clothing before reuse. Use appropriate skin cream to prevent drying of skin.

Conditions for safe storage, including any incompatibilities

Store at -40 degrees C. Keep container tightly sealed when not in use. Storage precautions

Storage class Chemical storage

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Control parameters

No exposure limits known for ingredient(s). Ingredient comments

Exposure controls







### **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

### **Manufacturer Part Number:**

ETHYB-353ND-TX2

 $Click here for more details on the EPO-TEK ^* HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat \& UV Cure - Pre-Mixed and Frozen (3cc Syringe) a$ 

Revision date: 12/15/2016

Revision:

### EPO-TEK HYB-353ND-TX2 PMF Syringe

#### Protective equipment





Appropriate engineering controls Provide adequate general and local exhaust ventilation. Avoid inhalation of vapors.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that

shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do

not eat, drink or smoke

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

### 9. Physical and Chemical Properties

## Information on basic physical and chemical properties

Appearance Liquid.

Color Colorless to pale yellow.

Flash point > 93°C
Evaporation rate < BuAc
Vapor density > Air

Solubility(ies) Slightly soluble in water.

Other information None.

### 10. Stability and reactivity

Reactivity The following materials may react with the product: Strong oxidizing agents. Strong reducing

agents.

Stability Stable at normal ambient temperatures and when used as recommended.

Possibility of hazardous

actions

May polymerize.

Conditions to avoid Avoid excessive heat for prolonged periods of time

Materials to avoid Strong oxidizing agents. Strong reducing agents.

Hazardous decomposition Thermal decomposition or combustion products may include the following substances:

products Carbon monoxide (CO). Carbon dioxide (CO2).

11. Toxicological information

Information on toxicological effects







### **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat & UV Cure -Pre-Mixed and Frozen (3cc Syringe)

### **Manufacturer Part Number:**

ETHYB-353ND-TX2

Click here for more details on the EPO-TEK® HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Revision date: 12/15/2016

Revision: 1

### EPO-TEK HYB-353ND-TX2 PMF Syringe

General information Possible risk of adverse reproductive effects.

Inhalation Inhalation of dust during cutting, grinding or sanding operations involving this product may

cause irritation of the respiratory tract.

Ingestion May cause discomfort if swallowed.

Skin Contact Causes skin irritation. May cause sensitisation by skin contact.

Eve contact Causes serious eye irritation.

12. Ecological Information

**Ecotoxicity** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity

Acute toxicity - fish Not available.

Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Mobility in soil

No data available.

Results of PBT and vPvB assessment

Other adverse effects

Other adverse effects Not known.

13. Disposal considerations Waste treatment methods

General information

Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

14. Transport information

**UN Number** 

Data is subject to change without notice.

UN No. (TDG) 3082 UN No. (IMDG) 3082 UN No. (ICAO) UN No. (DOT) UN3082

UN proper shipping name







## **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

### **Manufacturer Part Number:**

ETHYB-353ND-TX2

Click here for more details on the EPO-TEK\* HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Revision date: 12/15/2016 Revision: 1

### EPO-TEK HYB-353ND-TX2 PMF Syringe

Proper shipping name (TDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Phenol Novolac) Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Phenol Novolac) Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Proper shipping name (DOT) ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Epoxy Phenol Novolac) Transport hazard class(es) DOT hazard class DOT hazard label TDG class TDG label(s) IMDG Class ICAO class/division Transport labels DOT transport labels

### Packing group

TDG Packing Group III
IMDG packing group III
ICAO packing group III
DOT packing group III

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

EmS F-A, S-F

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information







### **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

### **Manufacturer Part Number:**

ETHYB-353ND-TX2

Click here for more details on the EPO-TEK® HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Revision date: 12/15/2016 Revision: 1

### EPO-TEK HYB-353ND-TX2 PMF Syringe

Regulatory References Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of

Intellectual Property Rights (TRIPS), Section 7, Art. 39.

International Regulations

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are required to be listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are required to be listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are required to be listed.

SARA 313 Emission Reporting

None of the ingredients are required to be listed.

CAA Accidental Release Prevention

None of the ingredients are required to be listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are required to be listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are required to be listed.

California Air Toxics "Hot Spots" (A-I)

None of the ingredients are required to be listed.

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are required to be listed.

Massachusetts "Right To Know" List

None of the ingredients are required to be listed.

Rhode Island "Right To Know" List

None of the ingredients are required to be listed.

Minnesota "Right To Know" List

None of the ingredients are required to be listed.

New Jersey "Right To Know" List

None of the ingredients are required to be listed.

Pennsylvania "Right To Know" List

None of the ingredients are required to be listed.

Inventories

EU - EINECS/ELINCS

Some of the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

8/9

Data is subject to change without notice.





### **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

### **Manufacturer Part Number:**

ETHYB-353ND-TX2

 $Click here for more details on the EPO-TEK ^* HYB-353ND-TX2 High Temperature Epoxy, Hybrid Heat \& UV Cure - Pre-Mixed and Frozen (3cc Syringe) a$ 

Revision date: 12/15/2016

Revision: 1

### EPO-TEK HYB-353ND-TX2 PMF Syringe

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

Australia - AICS

All the ingredients are listed or exempt.

Japan - MITI

Some of the ingredients are listed or exempt.

Korea - KECI

Some of the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

Some of the ingredients are listed or exempt.

### 16. Other information

Revision date 12/15/2016

Revision

Hazard statements in full H302 Harmful if swallowed

H315 Causes skin irritation.

H317 May cause an allergic skin reaction H318 Causes serious eye damage. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H361f Suspected of damaging fertility.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

9/9

Data is subject to change without notice.

