

SAFETY DATA SHEET (SDS)



Manufacturer:
American Polywater Corporation

Product Name:
HydraSol® Cable Gel Remover Solvent - 1 Gallon Jug

Manufacturer Part Number:
1091GP

▶ [Click here for more details on the HydraSol® Cable Gel Remover Solvent - 1 Gallon Jug](#)

Revision Date: September 24, 2018
Revision Number: 7 supersedes 6

SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

Product Name:
HydraSol® Cable Gel Remover

Product ID numbers: HS-XXX (Where XXX is the package code.)

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Removing cable filling greases

List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation
11222 - 60th Street North
Stillwater, MN 55082 USA
Tel: 1-651-430-2270
Email: sds@polywater.com

1.4 Emergency telephone numbers

INFOTRAC: 1-800-535-5053 (USA) 1-352-323-3500 (INT'L)

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to USA OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

Asp Tox 1	H304
Skin Irrit 2	H315
Skin Sens 1	H317
Eye Irrit 2	H319
Flam Liq 4	H227

2.2 Label elements

Contains: Medium Aliphatic Petroleum Solvent, d-Limonene, Alcohols, C12-C15, ethoxylated.



Pictograms:

Signal word: Danger

Hazard Statements:

H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes mild irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation

Precautionary Statements:

P210	Keep away from flames and hot surfaces. No smoking.
P261	Avoid breathing spray or vapor.

Page 1 of 7

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 3/12/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
American Polywater Corporation

Product Name:
HydraSol® Cable Gel Remover Solvent - 1 Gallon Jug

Manufacturer Part Number:
1091GP

▶ [Click here for more details on the HydraSol® Cable Gel Remover Solvent - 1 Gallon Jug](#)

Product Name: HydraSol® Cable Gel Remover

Revision Date: September 24, 2018

P264	Wash hands after handling.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves and eye protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P331	Do NOT induce vomiting.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water
P333 + P313	If skin irritation or rash occurs: Get medical attention
P362 + P364	Take off contaminated clothing and wash it before reuse.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical attention.
P370 + P378	In case of fire: Use water fog, foam, dry chemical or carbon dioxide for extinction.
P403 + P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local and national regulations.
2.3 Other hazards:	No information available.

3. Composition/Information on Ingredients

Component	CAS #	Wt. %
Medium Aliphatic Petroleum Solvent	64742-47-8	20-25
d-Limonene	5989-27-5	20-25
Alcohols, C12-C15, Ethoxylated	68131-39-5	< 2

This product contains no other reportable hazardous components under OSHA 29 CFR 1910.1200 (2012) and Canada HPR (SOR/2015-17; WHMIS 2015).

4. First Aid Measures

4.1 Description of first aid measures

Eye Contact:	If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.
Skin Contact:	Remove contaminated clothing; flush skin thoroughly with water. If irritation occurs, seek medical attention.
Inhalation (Breathing):	If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention. If breathing is difficult, provide oxygen. If not breathing, give artificial respiration. Seek immediate medical attention.
Ingestion (Swallowing):	Do not induce vomiting or give anything by mouth. If victim is drowsy or unconscious, place on the left side with head down. Do not leave victim unattended. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed.

Aspiration hazard. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis.

5. Firefighting Measures

5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition and by-products:

Burning generates CO, CO₂ and smoke. Smoke may be acrid and fumes irritating.

Page 2 of 7

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 3/12/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
American Polywater Corporation

Product Name:
HydraSol® Cable Gel Remover Solvent - 1 Gallon Jug

Manufacturer Part Number:
1091GP

▶ [Click here for more details on the HydraSol® Cable Gel Remover Solvent - 1 Gallon Jug](#)

Product Name: HydraSol® Cable Gel Remover

Revision Date: September 24, 2018

5.3 Advice for firefighters

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. For a spill in a confined space, provide mechanical ventilation to disperse or exhaust vapors. For emergency responders: use respiratory protection: half-face or full-face respirator with filter(s) for organic vapor for spills in a confined space. Work gloves that are resistant to aromatic hydrocarbons are recommended. Chemical goggles are recommended if splashes or contact with eyes is possible. For small spills: normal antistatic work clothes are usually adequate.

6.2 Environmental precautions:

Avoid release to the environment. Dyke the spill to prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods materials for containment and cleaning up:

Absorb spill with sand or absorbents. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Remember, adding an absorbent material does not change the toxicity or flammability hazard.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage

7.1 Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only. Avoid contact with oxidizing agents (e.g. chlorine, chromic acid etc.)

7.2 Conditions for safe storage, including incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from acids and oxidizing agents.

7.3 Specific end uses

See technical data sheet on this product for further information.

8. Exposure Controls / Personal Protection

8.1 Control parameters

Exposure limits and recommendations:

Petroleum Distillates, hydrotreated light (64742-47-8)

Country/Source	Long-term exposure limit – 8 hr. TWA	Short-term exposure limit – 15 min
Manufacturer, RCP* TWA	1200 mg/m ³	--
USA, ACGIH TWA	Not established	Not established
USA, OSHA PEL	2000 mg/m ³ , 500 ppm (as petroleum distillates (naphtha))	--
British Columbia	200 mg/m ³	--
Alberta, Quebec, Yukon, Saskatchewan, Ontario*	Not established	--

D-Limonene (5989-27-5)

Country/Source	Long-term exposure limit –	Short-term exposure limit –
----------------	----------------------------	-----------------------------

Page 3 of 7

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 3/12/2026.



Manufacturer:
American Polywater Corporation

Product Name:
HydraSol® Cable Gel Remover Solvent - 1 Gallon Jug

Manufacturer Part Number:
1091GP

▶ Click here for more details on the HydraSol® Cable Gel Remover Solvent - 1 Gallon Jug

Product Name: HydraSol® Cable Gel Remover

Revision Date: September 24, 2018

	8 hr. TWA	15 min
USA ACGIH TWA	Not established	Not established
USA OSHA PEL	Not established	Not established
Alberta, Quebec, Yukon, British Columbia, Saskatchewan, Ontario*	Not established	Not established

* reciprocal calculation procedure for total hydrocarbons

** Manitoba, Newfoundland and Labrador, Nova Scotia, and Prince Edward Island are all based on the current ACGIH TLVs. New Brunswick is based on an older version ACGIH. Nunavut and Northwest Territories are based heavily on current ACGIH TLVs.

8.2 Exposure controls

Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

Protective gloves:

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Suggested Material:	Nitrile Rubber
Suggested Thickness:	For short term contact (<15 minutes), splashes use 0.2 mm. For full contact use 0.4 mm

Eye protection:

Safety glasses recommended.

Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

9. Physical and Chemical

9.1 Information of basic physical and chemical properties

Appearance:	Milky-white liquid with light citrus scent.
Odor threshold:	Not available
pH:	Neutral
Freezing point:	Not available
Boiling point:	212°F (100°C) Initial
Flash point:	155°F (68°C), Closed Cup (PMCC)
Evaporation rate:	<0.06 (n-butyl acetate = 1)
Flammability (solid, gas):	Not applicable to liquids
Upper/lower flammability or explosive limits:	Not available
Vapor pressure:	10.5 mm Hg @ 20°C
Vapor density (Air = 1):	Not available
Specific gravity (H₂O = 1):	0.91
Solubility in water:	Dilutes emulsion
Partition coefficient: n-octanol/water:	Not available
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
Viscosity:	Not available

9.2 Other Information

Volatiles (Weight %):	>97%
------------------------------	------

Page 4 of 7

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 3/12/2026.



Manufacturer:
American Polywater Corporation

Product Name:
HydraSol® Cable Gel Remover Solvent - 1 Gallon Jug

Manufacturer Part Number:
1091GP

▶ [Click here for more details on the HydraSol® Cable Gel Remover Solvent - 1 Gallon Jug](#)

Product Name: HydraSol® Cable Gel Remover

Revision Date: September 24, 2018

VOC Content: 375 g/l

10. Stability and Reactivity

10.1 Reactivity:

See remaining headings in Section 10.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

None known.

10.4 Conditions to avoid:

Avoid heat, flame, and sparks.

10.5 Incompatible materials :

Strong oxidizing agents.

10.6 Hazardous decomposition products:

Carbon dioxide, carbon monoxide.

11. Toxicological Information

11.1 Information on toxicological effects:

Acute toxicity

Eye contact:

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

Skin contact:

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

Irritation and Sensitization Potential:

Product may be irritating to skin and eyes. May cause skin sensitization.

Inhalation (Breathing):

Concentrated petroleum solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue). Persons with impaired lung function may experience additional breathing difficulties due to the irritant properties of this material.

Ingestion:

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

Toxicity to Animals:

Medium Aliphatic PetroleumSolvent:	LD ₅₀ (oral rat) >5000 mg/kg
	LD ₅₀ (dermal rabbit) >2000 mg/kg
	LC ₅₀ (inhl rat) >4.3mg/L, 4 hours
d-Limonene:	LD ₅₀ (oral rat) >5000 mg/kg
	LD ₅₀ (dermal rabbit) 5000 mg/kg
	RD ₅₀ 1000 ppm

Aspiration hazard

May be fatal if swallowed and enters airways. Based on physico-chemical properties of the material.

Chronic Exposure:

Reproductive Toxicity:	Not available.
Mutagenicity:	Not available.
Teratogenicity:	Not available.
Specific Target Organ	No end point data.

Page 5 of 7

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice. FOC last update 3/12/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
American Polywater Corporation

Product Name:
HydraSol® Cable Gel Remover Solvent - 1 Gallon Jug

Manufacturer Part Number:
1091GP

▶ [Click here for more details on the HydraSol® Cable Gel Remover Solvent - 1 Gallon Jug](#)

Product Name: HydraSol® Cable Gel Remover

Revision Date: September 24, 2018

Toxicity (STOT)

Toxicologically Synergistic Products:

Not available.

Carcinogenic Status:

This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.

12. Ecological Information

12.1 Toxicity:

Ecotoxicity:

No information available.

Aquatic Toxicity:

No information available.

12.2 Persistence and degradability:

Expected to be biodegradable.

12.3 Bioaccumulation potential:

No information available

12.4 Mobility in soil:

No information available.

12.5 Results of PBT and vPvB

Assessment:

This product is not, nor does it contain a substance that is a PBT or vPvB.

12.6 Other adverse effects:

None known.

13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

14. Transport Information

US DOT Domestic Ground Transportation:

Not Regulated (49 CFR 173.155).

UN Number:

3082

UN Proper shipping name:

Environmentally Hazardous Substance, Liquid, N.O.S., (Contains: d-Limonene) LTD QTY

Transport hazard class(es):

Class 9

Packing group:

III

Environmental hazards:

Marine Pollutant

ICAO/IATA-DGR:

Environmentally Hazardous Substance, Liquid, N.O.S., (Contains: d-Limonene) LTD QTY

IMDG:

Environmentally Hazardous Substance, Liquid, N.O.S., (Contains: d-Limonene) LTD QTY

US DOT Domestic Ground Transportation:

Not Regulated (49 CFR 173.155).

*LTD QTY does not apply for packages containing greater than 5 Liters Cleaner

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

USA Federal and State

All components are listed on the TSCA inventory.

Hazard Categories for SARA Section 311/312 Reporting

Acute
Yes

Chronic
No

Fire
Yes

Pressure
No

Reactive
No

Components

CERCLA/SARA Sec 302 Hazardous Substance RQ

EHS TPQ

SARA Sec. 313 Toxic Release

Components are not affected by these Superfund regulations.

NFPA Ratings:

Health: 2

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com





Manufacturer:
American Polywater Corporation

Product Name:
HydraSol® Cable Gel Remover Solvent - 1 Gallon Jug

Manufacturer Part Number:
1091GP

▶ [Click here for more details on the HydraSol® Cable Gel Remover Solvent - 1 Gallon Jug](#)

Product Name: HydraSol® Cable Gel Remover

Revision Date: September 24, 2018

Fire: 2
Reactivity: 0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

California Prop65

WARNING: This product can expose you to benzene, ethylbenzene, cumene, and naphthalene which are known to the state of California to cause cancer, and toluene and benzene which are known to the State of California to cause birth defects and/or other reproductive harm. For more information, go to www.p65warnings.ca.gov.

Canada

All components are listed on the DSL inventory.
This product has been classified according to the hazard criteria of the CPR.

Australia

All components are listed on the AICS.
Hazardous according to criteria of NOHSC Australia.

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

16. Other Information

Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration
CLP = Classification, Labeling and Packaging Regulation
STOT = Specific Target Organ Toxicity
LD₅₀ = Median Lethal Dose
DNEL = Derived No Effect Level
ACGIH = American Conference of Governmental Industrial Hygienists
TSCA = Toxic Substances Control Act (USA)
DSL = Domestic Substances List (Canada)
AICS = Australian Inventory of Chemical Substances

Revision Date: September 24, 2018
Revision Number: 8
Supersedes: March 14, 2018
Indication of Changes: Section 3, 15 updated; format updates and additional California Proposition 65 information.
Written in accordance with the provisions of OSHA 1910.1200 App D (2012) and Canada HPR (SOR/2015-17) (WHMIS 2015), (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com

