

**Manufacturer:**

LW Scientific

Product Name:

LW Scientific E8 Centrifuge - Touch Screen


Manufacturer Part Number:

E8C-U8AT-15T3

[Learn More](#)

▶ [Click here for more details on the LW Scientific E8 Centrifuge - Touch Screen](#)

USA E8 CENTRIFUGES

**E8 TOUCH****E8 VARIABLE****E8 FIXED**

FEATURES

Angled rotor, 8-tube capacity
3,500 rpm
Holds 3ml to 15ml size tubes
12 volt DC maintenance-free motor
Clear view port in lid for using tachometer
Suction-cupped feet prevent slipping
110/220v auto-switching power adapter
(CE, UL, cUL approved adapter)
Lid safety shut-off switch
Maximum RCF=1,534g
E8 Fixed & E8 Variable: Auto-off 30-minute timer with bell
E8 Touch: Touch screen, programmable

ADVANTAGES

Accurate speeds for specific g-forces
Proper separations without cell damage
Quiet, vibration-free operation
Auto-brake stops the rotor in less than 30 seconds
Designed, Engineered, and Assembled
Proudly in America

WEIGHT AND DIMS

Height: 9.5" (241mm)
Length: 11" (279mm)
Width: 11" (279mm)
Weight: 9.5 lbs (4.3kg)

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are
subject to change without notice.*



Learn More



Manufacturer:

LW Scientific

Product Name:

LW Scientific E8 Centrifuge - Touch Screen


Manufacturer Part Number:

E8C-U8AT-15T3



Click here for more details on the LW Scientific E8 Centrifuge - Touch Screen

USA E8 CENTRIFUGES



F	E8C-U8AF-1503	USA E8 Fixed-Speed, Angled 8-Place Centrifuge with Timer
V	E8C-U8AV-1503	USA E8 Variable-Speed, Angled 8-Place Centrifuge with Timer
T	E8C-U8AT-15T3	USA E8 Digital-Speed, Touch Screen, Angled 8-Place Centrifuge

INCLUDES

Eight-place rotor

Eight 15ml tube sleeves

Eight 13x75mm tube sleeve inserts



The USA E8 Centrifuge is designed, engineered, and assembled at LW Scientific's ISO-certified, FDA-registered manufacturing facility in Lawrenceville, GA. Expect American quality as well as customary LW Scientific support. This model is loaded with features, such as higher speeds for faster and cleaner separations, quieter operation for peaceful work environments, lower chamber temperatures for cooler test-tube samples, shorter height to fit under any cabinet, and auto-calibrating speed function for precision results. It even has an auto-brake to stop the rotor in less than 30 seconds to save time in busy labs.



Designed, Engineered &
Assembled Proudly in America

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are
subject to change without notice.*