




Learn More



**Manufacturer:**

Labnet

**Product Name:**

Labnet AccuBlock™ 24-Port Digital Dry Bath - 230V

**Manufacturer Part Number:**

D1301-230V-24

► Click here for more details on the Labnet AccuBlock™ 24-Port Digital Dry Bath - 230V

## Labnet AccuBlock™ Digital Dry Baths

The Labnet AccuBlock Digital Dry Baths are available in single, dual, and four block configurations and provide a broad temperature range up to 150°C, which makes them useful for a variety of applications in molecular biology, histology, clinical, environmental, and industrial laboratories.

They have been designed to incorporate the best combination of features including single, dual, and four block capacity, dual display, and an external temperature probe that gives life science researchers the confidence and efficiency they need when working with precious samples.

### Features

- Single, dual, and four block capacity to maximize sample processing (blocks sold separately)
- Dual display allows for easy monitoring of temperature and time
- USB connectivity enables traceability of data
- Molded block chamber provides excellent temperature uniformity



Each Labnet AccuBlock Digital Dry Bath includes an easy fit magnetic lid



**Contact the professionals at Fiber Optic Center for a quote or to get more details.**

[focenter.com](http://focenter.com) • 508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are subject to change without notice.*



**Manufacturer:**

Labnet

**Product Name:**

Labnet AccuBlock™ 24-Port Digital Dry Bath - 230V

**Manufacturer Part Number:**

D1301-230V-24

▶ [Click here for more details on the Labnet AccuBlock™ 24-Port Digital Dry Bath - 230V](#)



**Specifications**

Temperature range	Ambient +5°C to 150°C
Temperature display	4-digit LED, accurate to 0.1°C
Temperature uniformity	± 0.2°C (at 37°C in block)
Temperature accuracy	± 0.3°C
Temperature control	User calibratable microprocessor
Timer	1 minute to 99 hours 59 minutes, or continuous in 1-minute increments
Operating Altitude	Up to 2,000 meters
Dimensions (W x D x H)	
Single block	8.3 x 12.4 x 4.7 in. (21 x 31.5 x 12 cm)
Dual block	8.3 x 12.4 x 4.7 in. (21 x 31.5 x 12 cm)
Four block	8.3 x 16.3 x 4.7 in. (21 x 41.5 x 12 cm)
Weight	
Single block	7.0 lbs. (3.2 kg)
Dual block	7.0 lbs. (3.2 kg)
Four block	9.6 lbs. (4.4 kg)

**Ordering Information**

**Labnet AccuBlock™ Digital Dry Baths**

Cat. No.	Description
D1301	Digital dry bath, single block, 120V
<b>D1301-230V</b>	Digital dry bath, single block, 230V
D1302	Digital dry bath, dual block, 120V
D1302-230V	Digital dry bath, dual block, 230V
D1304	Digital dry bath, four block, 120V
D1304-230V	Digital dry bath, four block, 230V



**Contact the professionals at Fiber Optic Center for a quote or to get more details.**

[focenter.com](http://focenter.com) • 508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are subject to change without notice.*