



Manufacturer:

Lightel

Product Name:

Lightel DI-3000 400x Digital USB Inspection Probe w/ Autofocus and WiFi

Manufacturer Part Number:

DI-3000-B2

Click here for more details on the Lightel DI-3000 400x Digital USB Inspection Probe w/ Autofocus and WiFi



Wireless inspection made easy

Due to greater data rates and bandwidth expansion, fiber optic connector equipment and racks are becoming increasingly dense and difficult to access. Cramped communications closets, dense data centers, and tower installs make it difficult to carry and use traditional fiber optic connector inspection equipment.

Building upon our successful Digital Inspector (DI-) product suite, Lightel has developed the DI-3000 embedded WiFi and autofocus probe, eliminating the need for direct USB connectivity to display devices. The DI-3000 allows the user to effortlessly inspect, store, certify and analyze fiber optic connectors without a physical connection to your Android/iOS mobile device, PC laptops, or other test equipment.









Features

- USB connectivity can be used for secure facilities
- Embedded wireless functionality
- Rechargeable battery powered unit with longlasting battery life
- One-touch autofocus
- Capture and save endface images to smart device with the push of a button
- Built-in flashlight for use in dark conditions
- Compatible with more than 120 inspection tips
- ConnectorView™ Android/iOS apps available. Optional pass/fail software for Windows

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer:

Lightel

Product Name:

Lightel DI-3000 400x Digital USB Inspection Probe w/ Autofocus and WiFi

Manufacturer Part Number:

DI-3000-B2

Click here for more details on the Lightel DI-3000 400x Digital USB Inspection Probe w/ Autofocus and WiFi

→ Specifications

Field of View	~ 640μm x 480μm	
Detectable Resolution	0.5µm	
Focus	Autofocus or manual adjustment, 2mm max travel	
Autofocus Time	2-4 seconds	
Camera	1/4" CMOS	
Light Source	Blue LED	
Power Supply	Rechargeable Li-ion battery or USB2.0 (or higher) port	
Battery Life	Up to 7 hours	
Dimensions	205mm x 37mm x 48mm (probe with cap)	
Weight	187g (including battery)	
Operating Temperature	0°C to 50°C	
Storage Temperature	-20°C to 50°C	
Supported Operating Systems (ConnectorView Software/App)	Windows® 7, Windows® 8, Windows® 10, 32-bit and 64-bit processors. Android 6 and up, iOS 15.5 and up.	

→ Packages

PACKAGE	PART NUMBER	DESCRIPTION
DI-3000-B2	PT2-U2.5/PC/M	Universal tip for male 2.5mm PC connectors
	PT2-FS/PC/F	Tip for female FC and SC PC connectors
	PT2-U1.25/PC/M	Universal tip for male 1.25mm PC connectors
	PT2-LC/PC/F-1	Tip for female LC PC connectors
	DI1-CASE-S	Soft carrying case
	CVF-USB	Flash drive with ConnectorView (standard) software
DI-3000-B2/APC	PT2-U2.5/APC/M	Universal tip for male 2.5mm APC connectors
	PT2-FS/APC/F	Tip for female FC and SC APC connectors
	DI1-CASE-S	Soft carrying case
	CVF-USB	Flash drive with ConnectorView (standard) software

Contact the professionals at Fiber Optic Center for a quote or to get more details.