



Manufacturer:
Lightera

Product Name:
OFS FTEL S251A Optical Fiber Stripper

Manufacturer Part Number:
S251A



[Learn More](#)

▶ [Click here for more details on the OFS FTEL S251A Optical Fiber Stripper](#)

S251A



Compatible with 200-400 μm single fibers and ribbons

Speedy and consistent stripping

- Ready to strip in 5 sec*
- Lower pulling force for increased yield
- Easy cleaning with flat heater design

*from power-on to reaching 100 °C at room temperature

Easy heat and time settings for each fiber type and working environment

Equipped with USB-C connector for convenient charging with portable batteries

Ideal for outdoor operation with bright LEDs, sound & vibration notifications and water-resistant body



Flat heater design



USB-C connector




Bright LEDs

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.

[Learn More](#)**Manufacturer:**

Fitel

Product Name:

OFS FITEL S251A Optical Fiber Stripper

Manufacturer Part Number:

S251A

[Click here for more details on the OFS FITEL S251A Optical Fiber Stripper](#)**Specification**

Description	S251A
Applicable fibers	Optical fibers (glass)
Cladding diameter	125 μ m
Fiber count	1 to 12 16 (only 0.20 mm coating diameter)
Coating diameter	0.20 to 0.40 mm
Fiber ribbon size	0.20 to 0.40 mm (thickness)
Heating temperature	80, 100, 120, 140, 160 °C (5 steps of temperature)
Battery life	Approx. 10 hours (Normal mode), Approx. 600 stripping cycles
Charging time	Approx. 3 hours (with power off condition)
Power supply	DC: 5 V, 9 V 2 A, 9 V 3 A AC: 100-240 V: in use of S983A AC adapter
Dimensions	147W x 46D x 35H mm
Weight	Approx. 240 g (including battery)
Operating condition	Temperature: -10 to 50 °C Humidity: Max. 95%RH (non-condensing)
Storage condition	Temperature: -40 to 60 °C Humidity: Max. 95%RH (non-condensing)

Standard Package

Item	Model No.	Quantity
S251A Main Body	S251A-X-A-0002-A	1
Battery	S944D	1
AC Adapter	-	1
Cleaning Brush	VGC-01	1
Quick Reference Guide	FTS-B642	1

Export Control Regulations

The products and/or technical information presented in this publication may be subject to the application of the Foreign Exchange and Foreign Trade Act and other related laws and regulations in Japan. In addition, the Export Administration Regulations (EAR) of the United States may be applicable. In cases where exporting or reexporting the products and/or technical information presented in this publication, customers are requested to follow the necessary procedures at their own responsibility and cost. Please contact the Ministry of Economy, Trade and Industry of Japan or the Department of Commerce of the United States for details about procedures.

Contact the professionals at Fiber Optic Center for a quote or to get more details.focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are
subject to change without notice.*