



Manufacturer:

3SAE

Product Name: 3SAE Thermal Stripper, High Strength

Manufacturer Part Number: ACC-01-00XX

Click here for more details on the 3SAE High 3SAE Thermal Stripper, High Strength



3SAE Thermal Strippers are compact, easy-to-use optical fiber stripping units designed to thermo-mechanically remove coatings from optical fibers.

The Thermal Stripper High Strength supports standard 125 µm optical fibers, including 250 µm, 400 µm, and 900 µm coated fibers. Adjustable temperature and time settings allow it to adapt to stripping a variety of different coatings. The precision, self-centering blade design produces high strength stripping performance unmatched by previous flat blade strippers.

3SAE's complete line of fiber holder compatible optical fiber preparation tools incorporates the 3SAE Thermal Stripper, 3SAE Ultrasonic Cleaner, and 3SAE fiber cleavers. All are configurable for use with Fitel, Fujikura, or 3SAE fiber holders. Use of fiber holders provides a repeatable handling process across strip, clean, cleave and splice equipment for high strength fusion splicing and improved yield.

Key Features: 3SAE Thermal Stripper, High Strength

- Compact, low-maintenance bench top design
- Supports standard 125 μm acrylate coated fiber with buffer diameters up to 900 μm
- Adjustable temperature and time settings to accommodate different fiber coatings
- Fitel, Fujikura, and 3SAE fiber holder compatible platforms
- Optional generic clamp for use without fiber holders
- Maximum strip length: 68mm

Standard Packages

| Part Number | Product | Includes |
|-------------|--|--|
| ACC-01-0062 | Generic Platform (No Fiber Holder Required) | Includes power supply, cleaning brush, electronic user's manual, Manufacturer's 1-year parts and labor warranty |
| ACC-01-0044 | Fitel/Fujikura/3SAE Fiber Holder Compatible | |

Technical Specifications

| Feature | Specification |
|-------------------------|--|
| Dimensions | 158.5 (W) x 73.5 (D) x 74 (H) mm |
| Weight | 445 grams |
| Power Source | Input: 100-240 VAC, 50-60 Hz Output: 12 VDC 3 A |
| Supported Fiber Types | 125 μm coated |
| Supported Fiber Buffers | 250 – 900 μm |
| Temperature Range | 60 – 200 °C, or ambient |

Accessories and Consumables

| Part Number | Description | |
|-------------|---|--|
| ACC-01-0085 | Thermal Stripper Fitel/Fujikura/3SAE Compatible Fiber Holder Platform | |
| ACC-01-0087 | Thermal Stripper Universal Clamp | |
| ACC-10-0025 | Power Supply 40W 12V Barrel (Thermal Stripper) | |
| CON-10-0036 | Cleaning Brush, double-sided | |

Contact the professionals at Fiber Optic Center for a quote or to get more details.