

**Manufacturer:**

ÅngströmLap®

**Product Name:**ÅngströmLap® Aluminum Oxide Lapping Film Sheet -  
8.5 x 8.5 inch 9µm (micron)**Manufacturer Part Number:**

AO9F85853N100

[Learn More](#)

▶ [Click here for more details on the ÅngströmLap® Aluminum Oxide Lapping Film Sheet - 8.5 x 8.5 inch 9µm \(micron\)](#)

## PRODUCT SPECIFICATIONS:

**Description by Application**

FO Type Name: AO9-MF

Color: Blue

**Tape Specifications**Total Thickness:  $94.0 \pm 3.0 \mu\text{m}$ Surface Roughness(Sa):  $1.60 \pm 0.45 \mu\text{m}$ **Abrasive Type**

Particle Type: Aluminum Oxide

Grit Size: 9 µm

**Base Film Type**

Base Film Material: Poly-ethylene terephthalate

Base Film Thickness: 3 mil (75 µm)

**Process Parameters**

Type: MF

**Contact the professionals at Fiber Optic Center for a quote or to get more details.**

[focenter.com](http://focenter.com) • 508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are  
subject to change without notice.

**Manufacturer:**

ÅngströmLap®

**Product Name:**ÅngströmLap® Aluminum Oxide Lapping Film Sheet -  
8.5 x 8.5 inch 9µm (micron)**Manufacturer Part Number:**

AO9F85853N100

[Learn More](#)

▶ [Click here for more details on the ÅngströmLap® Aluminum Oxide Lapping Film Sheet - 8.5 x 8.5 inch 9µm \(micron\)](#)

## PRODUCT SPECIFICATIONS:

**Unit:** Standard packaging of 100

Roll - Product that has already been slit down for samples or to product specifications requested by the customer. This specification standard covers tapes for various applications.

Disc - Product that has been slit down into rolls then die cut into circular discs to conform to customer specified sizes. This specification standard covers discs for various applications

Sheet - Product that has been slit down into rolls then sheet cut into rectangular sheets to conform to customer specified sizes. This specification standard covers sheets for various applications

**Description:**

Example: AO9-MF

Abrasive Material	Average Grit Size	Process Type	
AO	9	M	F
Aluminum Oxide	9 µm	Mixing Ratio Type	Surface Shape Type

**Lot Description:**

Indicated by 10 digits number.

Automatic numbering by enterprise resource planning system.

Example: 0000012345

**Product Specifications:**

Mipox product standards are specified by the abrasive film Surface roughness and the total thickness diameter and length.

**Storage Environment:**

- Temperature: 10 to 50 centigrade
- Humidity: 20 to 80%

**Product Life:** Mipox product life is guaranteed up to 5 years from the manufactured date

**Recommended Usage:** Usage amounts are conservative estimates and may vary based on individual conditions. Please contact Fiber Optic Center to optimize these usage numbers. Specifications subject to change without notice.

**Contact the professionals at Fiber Optic Center for a quote or to get more details.**

[focenter.com](http://focenter.com) • 508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are  
subject to change without notice.*



**Manufacturer:**

ÅngströmLap®

**Product Name:**

ÅngströmLap® Aluminum Oxide Lapping Film Sheet -  
8.5 x 8.5 inch 9µm (micron)


**Manufacturer Part Number:**

AO9F85853N100



Learn More

▶ Click here for more details on the ÅngströmLap® Aluminum Oxide Lapping Film Sheet - 8.5 x 8.5 inch 9µm (micron)



**Contact the professionals at Fiber Optic Center for a quote or to get more details.**

[focenter.com](http://focenter.com) • 508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are  
subject to change without notice.