


SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe (5-Pack Sample)

Manufacturer Part Number:
ETHYB-353ND-LV-3CC-S5

▶ [Click here for more details on the EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe \(5-Pack Sample\)](#)

Revision date: 8/9/2016

Revision: 1



SAFETY DATA SHEET EPO-TEK HYB-353ND-LV PMF Syringe

1. Identification

Product identifier

Product name EPO-TEK HYB-353ND-LV PMF Syringe

Product number HYB-353ND-LV

Recommended use of the chemical and restrictions on use

Application Adhesive.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.
14 Fortune Drive
Billerica, MA 01821
USA
(978) 667-3805
(978) 663-9782
www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone +1 (800) 255-3924, +1 (813) 248-0585

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com
508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice.
FOC last update 5/3/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe (5-Pack Sample)

Manufacturer Part Number:
ETHYB-353ND-LV-3CC-S5

▶ [Click here for more details on the EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe \(5-Pack Sample\)](#)

Revision date: 8/9/2016

Revision: 1

EPO-TEK HYB-353ND-LV PMF Syringe

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Repr. 1B - H360 STOT SE 3 - H335

Environmental hazards Aquatic Chronic 2 - H411

Label elements

Pictogram



Signal word

Danger

Hazard statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H360 May damage fertility or the unborn child.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P302+P352 If on skin: Wash with plenty of water.
P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P501 Dispose of contents/ container in accordance with national regulations.

Contains

Specialty Acrylate Blend, Bisphenol A Diglycidyl Ether Resin, Epoxy Phenol Novolac, Substituted Imidazole Blend, Imidazole

Other hazards

Hazards not otherwise classified (HNOC)

Contains epoxy constituents. May produce an allergic reaction.


Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com
508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice.
FOC last update 5/3/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe (5-Pack Sample)

Manufacturer Part Number:
ETHYB-353ND-LV-3CC-S5

▶ [Click here for more details on the EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe \(5-Pack Sample\)](#)

Revision date: 8/9/2016

Revision: 1

EPO-TEK HYB-353ND-LV PMF Syringe

3. Composition/information on ingredients

Mixtures

Specialty Acrylate Blend CAS number: Proprietary	30-60%
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H335 Aquatic Chronic 2 - H411	
Bisphenol A Diglycidyl Ether Resin CAS number: 1675-54-3	10-30%
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	
Epoxy Phenol Novolac CAS number: 28064-14-4	10-30%
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	


Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com
508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice.
FOC last update: 5/3/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe (5-Pack Sample)

Manufacturer Part Number:
ETHYB-353ND-LV-3CC-S5

▶ [Click here for more details on the EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe \(5-Pack Sample\)](#)

Revision date: 8/9/2016

Revision: 1

EPO-TEK HYB-353ND-LV PMF Syringe

Substituted Imidazole Blend CAS number: Proprietary	1-5%
Classification Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318	
Imidazole CAS number: 288-32-4	1-5%
Classification Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Repr. 1B - H360	

The Full Text for all Hazard Statements are Displayed in Section 16.


Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com
508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice.
FOC last update 5/3/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe (5-Pack Sample)

Manufacturer Part Number:
ETHYB-353ND-LV-3CC-S5

▶ [Click here for more details on the EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe \(5-Pack Sample\)](#)

Revision date: 8/9/2016

Revision: 1

EPO-TEK HYB-353ND-LV PMF Syringe

4. First-aid measures

Description of first aid measures

Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin Contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

Most important symptoms and effects, both acute and delayed

General information	May damage fertility or the unborn child.
Inhalation	Gas or vapor in high concentrations may irritate the respiratory system. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.
Ingestion	May cause discomfort if swallowed.
Skin contact	Causes skin irritation. May cause sensitisation by skin contact.
Eye contact	Causes serious eye damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
----------------------	------------------------


Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com
508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice.
FOC last update: 5/3/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe (5-Pack Sample)

Manufacturer Part Number:
ETHYB-353ND-LV-3CC-S5

▶ [Click here for more details on the EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe \(5-Pack Sample\)](#)

Revision date: 8/9/2016

Revision: 1

EPO-TEK HYB-353ND-LV PMF Syringe

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Dry chemicals. Foam. Carbon dioxide (CO₂).

Special hazards arising from the substance or mixture

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO₂), Carbon monoxide (CO).

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapors. Use water to keep fire exposed containers cool and disperse vapors.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Keep unnecessary and unprotected personnel away from the spillage. Avoid contact with skin and eyes.

Environmental precautions

Environmental precautions Avoid discharge to the aquatic environment.

Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

Reference to other sections For personal protection, see Section 8.

Contact the professionals at Fiber Optic Center for a quote or to get more details.


23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice.
FOC last update 5/3/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe (5-Pack Sample)

Manufacturer Part Number:
ETHYB-353ND-LV-3CC-S5

▶ [Click here for more details on the EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe \(5-Pack Sample\)](#)

Revision date: 8/9/2016

Revision: 1

EPO-TEK HYB-353ND-LV PMF Syringe

7. Handling and storage

Precautions for safe handling

Usage precautions

Handle all packages and containers carefully to minimize spills. Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet.

Advice on general occupational hygiene

Provide eyewash station. Do not eat, drink or smoke when using this product. Wash promptly with soap and water if skin becomes contaminated. Wash after use and before eating, smoking and using the toilet. Wash contaminated clothing before reuse. Use appropriate skin cream to prevent drying of skin.

Conditions for safe storage, including any incompatibilities

Storage precautions

Store at -40 degrees C. Keep container tightly sealed when not in use.

Storage class

Chemical storage.

Specific end uses(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

8. Exposure Controls/personal protection

Ingredient comments

No exposure limits known for ingredient(s).

Exposure controls

Protective equipment



Contact the professionals at Fiber Optic Center for a quote or to get more details.


23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice.
FOC last update 5/3/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe (5-Pack Sample)

Manufacturer Part Number:
ETHYB-353ND-LV-3CC-S5

▶ [Click here for more details on the EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe \(5-Pack Sample\)](#)

Revision date: 8/9/2016

Revision: 1

EPO-TEK HYB-353ND-LV PMF Syringe

Appropriate engineering controls	Provide adequate general and local exhaust ventilation. Avoid inhalation of vapors.
Eye/face protection	Wear tight-fitting, chemical splash goggles or face shield.
Hand protection	It is recommended that chemical-resistant, impervious gloves are worn.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	Provide eyewash station. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Liquid.
Color	Colorless to pale yellow.
Flash point	> 93°C
Evaporation rate	< BuAc
Vapor density	> Air
Solubility(ies)	Slightly soluble in water.
Other information	None.


Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com
508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice.
FOC last update 5/3/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe (5-Pack Sample)

Manufacturer Part Number:
ETHYB-353ND-LV-3CC-S5

▶ [Click here for more details on the EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe \(5-Pack Sample\)](#)

Revision date: 8/9/2016

Revision: 1

EPO-TEK HYB-353ND-LV PMF Syringe

10. Stability and reactivity

Reactivity	The following materials may react with the product: Strong oxidizing agents. Strong reducing agents.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	May polymerize.
Conditions to avoid	Avoid excessive heat for prolonged periods of time.
Materials to avoid	Strong oxidizing agents. Strong reducing agents.
Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO ₂).

11. Toxicological information

Information on toxicological effects

General information	Possible risk of adverse reproductive effects.
Inhalation	May cause respiratory irritation. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.
Ingestion	May cause discomfort if swallowed.
Skin Contact	Causes skin irritation. May cause sensitisation by skin contact.
Eye contact	Causes serious eye damage.


Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com
508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice.
FOC last update 5/3/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe (5-Pack Sample)

Manufacturer Part Number:
ETHYB-353ND-LV-3CC-S5

▶ [Click here for more details on the EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe \(5-Pack Sample\)](#)

Revision date: 8/9/2016

Revision: 1

EPO-TEK HYB-353ND-LV PMF Syringe

12. Ecological Information

Ecotoxicity Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity

Acute toxicity - fish Not available.

Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Mobility in soil

Mobility No data available.

Other adverse effects

Other adverse effects Not known.

13. Disposal considerations

Waste treatment methods

General information Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

UN Number

UN No. (TDG) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

UN No. (DOT) UN3082

Contact the professionals at Fiber Optic Center for a quote or to get more details.


23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice.
FOC last update 5/3/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe (5-Pack Sample)

Manufacturer Part Number:
ETHYB-353ND-LV-3CC-S5

▶ [Click here for more details on the EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe \(5-Pack Sample\)](#)

Revision date: 8/9/2016

Revision: 1

EPO-TEK HYB-353ND-LV PMF Syringe

UN proper shipping name

- Proper shipping name (TDG)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Bisphenol A diglycidyl ether resin)
- Proper shipping name (IMDG)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Bisphenol A diglycidyl ether resin)
- Proper shipping name (ICAO)** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Bisphenol A diglycidyl ether resin)
- Proper shipping name (DOT)** ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Bisphenol A diglycidyl ether resin)

Transport hazard class(es)

DOT hazard class	9
DOT hazard label	9
TDG class	9
TDG label(s)	9
IMDG Class	9
ICAO class/division	9

Transport labels



DOT transport labels




Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com
508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice.
FOC last update 5/3/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe (5-Pack Sample)

Manufacturer Part Number:
ETHYB-353ND-LV-3CC-S5

▶ [Click here for more details on the EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe \(5-Pack Sample\)](#)

Revision date: 8/9/2016

Revision: 1

EPO-TEK HYB-353ND-LV PMF Syringe

Packing group

TDG Packing Group	III
IMDG packing group	III
ICAO packing group	III
DOT packing group	III

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

EmS F-A, S-F

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Regulatory References Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of Intellectual Property Rights (TRIPS), Section 7, Art. 39.

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities
None of the ingredients are required to be listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)
None of the ingredients are required to be listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities
None of the ingredients are required to be listed.


Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com
508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice.
FOC last update 5/3/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe (5-Pack Sample)

Manufacturer Part Number:
ETHYB-353ND-LV-3CC-S5

▶ [Click here for more details on the EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe \(5-Pack Sample\)](#)

Revision date: 8/9/2016

Revision: 1

EPO-TEK HYB-353ND-LV PMF Syringe

SARA 313 Emission Reporting

None of the ingredients are required to be listed.

CAA Accidental Release Prevention

None of the ingredients are required to be listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are required to be listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are required to be listed.

California Air Toxics "Hot Spots" (A-I)

None of the ingredients are required to be listed.

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are required to be listed.

Massachusetts "Right To Know" List

None of the ingredients are required to be listed.

Rhode Island "Right To Know" List

None of the ingredients are required to be listed.

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

Specialty Acrylate Blend

New Jersey "Right To Know" List

None of the ingredients are required to be listed.

Pennsylvania "Right To Know" List

None of the ingredients are required to be listed.

Contact the professionals at Fiber Optic Center for a quote or to get more details.


23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice.
FOC last update 5/3/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe (5-Pack Sample)

Manufacturer Part Number:
ETHYB-353ND-LV-3CC-S5

▶ [Click here for more details on the EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe \(5-Pack Sample\)](#)

Revision date: 8/9/2016

Revision: 1

EPO-TEK HYB-353ND-LV PMF Syringe

Inventories

EU - EINECS/ELINCS

Some of the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

Australia - AICS

Some of the ingredients are listed or exempt.

Japan - MITI

Some of the ingredients are listed or exempt.

Korea - KECI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

Some of the ingredients are listed or exempt.



Contact the professionals at Fiber Optic Center for a quote or to get more details.


23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice.
FOC last update 5/3/2026.

SAFETY DATA SHEET (SDS)



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe (5-Pack Sample)

Manufacturer Part Number:
ETHYB-353ND-LV-3CC-S5

▶ [Click here for more details on the EPO-TEK® HYB-353ND-LV Low Viscosity Epoxy, Hybrid Heat & UV Cure - Premixed and Frozen 3cc Syringe \(5-Pack Sample\)](#)

Revision date: 8/9/2016

Revision: 1

EPO-TEK HYB-353ND-LV PMF Syringe

16. Other information

Revision date 8/9/2016

Revision 1

Hazard statements in full
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H360 May damage fertility or the unborn child.
H411 Toxic to aquatic life with long lasting effects.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



Data is subject to change without notice.
FOC last update 5/3/2026.