

#### Manufacturer:

3SAE Technologies, Inc.

### **Product Name:**

3SAE Thermal Strippers

# **Manufacturer Part Number:**

ACC-01-00YY

# HERMAL STRIPPERS

The 3SAE Thermal Strippers are compact, easy-to-use fiber stripping units designed to thermo-mechanically remove coatings from optical fibers.

The High Strength Thermal Stripper supports standard 125 µm optical fibers, including 250 µm, 400 µm, and 900 µm coated fibers. Adjustable temperature and time settings allow it to adapt to stripping a variety of different coatings. The precision, self-centering blade design produces high strength stripping performance unmatched by previous flat blade strippers.

The High Strength Adjustable Thermal Stripper supports optical fibers with cladding diameters from 30 µm to 1000 µm, with buffer diameters up to 1200 µm. This includes standard 250 µm, 400 µm, and 900 µm coated fibers. Adjustable temperature and time settings allow it to adapt to stripping a variety of different coatings and cladding sizes.

High Strength Thermal Stripper

Generic Platform Shown Above

3SAE's complete line of preparation tools, including the 3SAE Thermal Strippers, are configurable for use with Fitel, Fujikura, 3SAE or Ericsson fiber holders. Use of fiber holders provides a repeatable handling process across strip, clean, cleave and splice equipment for high strength splicing and improved yield.

3SAE's complete line of fiber holder compatible preparation tools incorporates the 3SAE Thermal Stripper, 3SAE Ultrasonic Cleaner, and 3SAE fiber cleavers.

## **Key Features:**

- · Compact, low-maintenance bench top design
- High Strength version supports standard 125 µm acrylate coated fiber with buffer diameters up to 900 µm
- Adjustable temperature and time settings to accommodate different fiber coatings
- Available Fitel, Fujikura, 3SAE or Ericsson fiber holder compatible platforms
- · Optional generic clamp for use without fiber holders

#### **Technical Specifications:**

- Dimensions: 129.5 (W) x 73.5 (D) x 71 (H) mm
- · Weight: 445 grams
- Power Source: Input: 100 240 V AC, 50/60 Hz
- Supported Fiber Types: High Strength: 125 µm coated; Adjustable: 30
- 1000 um coated
- Supported Fiber Buffers: High Strength: 250  $\mu m$  900  $\mu m$ ; Adjustable:
- Adjustable Temperature Range: 60 200 °C, or ambient

## **Product**

Part Number

# Thermal Stripper (High Strength)

Fitel/Fujikura/3SAE Fiber Holder Compatible ACC-01-0044 Ericsson Fiber Holder Compatible ACC-01-0037 Generic (No Fiber Holder Required) ACC-01-0062

# Thermal Stripper (High Strength Adjustable)

Fitel/Fujikura/3SAE Fiber Holder Compatible ACC-01-0059 Ericsson Fiber Holder Compatible ACC-01-0060 Generic (No Fiber Holder Required) ACC-01-0055

### Standard Package

Power Supply SPT-10-0043 Power Cord FPU-02-0037 Cleaning Brush FPU-01-0124 1 User's Manual N/A

#### **Optional Components**

Fitel/Fujikura/3SAE Compatible ACC-01-0085

Fiber Holder Platform

Ericsson Compatible Fiber Holder Platform ACC-01-0086 Generic Platform (No Fiber Holder Required) ACC-01-0087

\*INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE.

Contact the professionals at Fiber Optic Center for a quote or to get more details.