

Manufacturer: 3SAE Technologies, Inc.

Product Name: 3SAE Thermal Strippers

Manufacturer Part Number: ACC-01-02XX

THERMAL STRIPPERS

The 3SAE Thermal Strippers are compact, easy-to-use fiber stripping units designed to thermo-mechanically remove coatings from optical fibers.

The High Strength Thermal Stripper supports standard 125 μ m optical fibers, including 250 μ m, 400 μ m, and 900 μ m coated fibers. Adjustable temperature and time settings allow it to adapt to stripping a variety of different coatings. The precision, self-centering blade design produces high strength stripping performance unmatched by previous flat blade strippers.

The High Strength Adjustable Thermal Stripper supports optical fibers with cladding diameters from 30 μ m to 1000 μ m, with buffer diameters up to 1200 μ m. This includes standard 250 μ m, 400 μ m, and 900 μ m coated fibers. Adjustable temperature and time settings allow it to adapt to stripping a variety of different coatings and cladding sizes.



High Strength Thermal Stripper Generic Platform Shown Above

3SAE's complete line of preparation tools, including the 3SAE Thermal

Strippers, are configurable for use with Fitel, Fujikura, 3SAE or Ericsson fiber holders. Use of fiber holders provides a repeatable handling process across strip, clean, cleave and splice equipment for high strength splicing and improved yield.

3SAE's complete line of fiber holder compatible preparation tools incorporates the 3SAE Thermal Stripper, 3SAE Ultrasonic Cleaner, and 3SAE fiber cleavers.

Key Features:	Product Part Nu	umber Qty
 Compact, low-maintenance bench top design High Strength version supports standard 125 μm acrylate coated fiber with buffer diameters up to 900 μm Adjustable temperature and time settings to accommodate different fiber coatings Available Fitel, Fujikura, 3SAE or Ericsson fiber holder compatible platforms Optional generic clamp for use without fiber holders 	Ericsson Fiber Holder Compatible ACC-0 Generic (No Fiber Holder Required) ACC-0 Thermal Stripper (High Strength Adjust Fitel/Fujikura/3SAE Fiber Holder Compatible ACC-01 Ericsson Fiber Holder Compatible ACC-02	
Technical Specifications:	Standard Package Power Supply SPT-10	-0043 1
• Dimensions: 129.5 (W) x 73.5 (D) x 71 (H) mm • Weight: 445 grams • Power Source: Input: 100 - 240 V AC, 50/60 Hz	Power Cord FPU-02 Cleaning Brush FPU-01 User's Manual N/A	
 Supported Fiber Types: High Strength: 125 μm coated; Adjustable: 30 1000 μm coated Supported Fiber Buffers: High Strength: 250 μm – 900 μm; Adjustable: 	Optional Components Fitel/Fujikura/3SAE Compatible ACC-0 Fiber Holder Platform	1-0085
 80 – 1200 μm Adjustable Temperature Range: 60 – 200 °C, or ambient 	Ericsson Compatible Fiber Holder Platform ACC-0	1-0086)1-0087

*INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com 23 Centre Street • New Bedford, MA 02740 USA