


## Riser Single-Jacket I/O Loose Tube (LV Series SJ)

Indoor/outdoor stranded loose tube combines the robust mechanical and environmental characteristics of an outside plant cable with the flexibility of an inside plant riser cable. By installing indoor/outdoor stranded loose tube, costly splice locations entering into a building are avoided, being routed directly from the outside plant to telecommunications closets, or main distribution frames (MDF) through the riser of a building and eliminating the "50-foot rule." Indoor/Outdoor Stranded Design loose tube cable is moisture and U.V. resistant, S-Z stranded for easy mid-span access, listed for OFNR use per UL standards, and can be used in both duct and lashed applications.

### Applications

- Building Interconnections (Campus LAN)
- Trunking Lines Direct to Telecommunications Closet
- Local Loop
- Distance Learning
- Distribution
- Intra-building Backbones
- MSHA Approved for Mining Applications

### Cable Components



### Temperature Specifications

TEMPERATURE RANGE	
INSTALLATION	-30°C to +70°C
OPERATING	-40°C to +70°C
STORAGE	-40°C to +75°C

### Typical Lengths

MAXIMUM LENGTHS*				
FIBER COUNT	SINGLE-MODE		MULTIMODE	
	FEET	METERS	FEET	METERS
6 - 144	22,900	7,000	22,900	7,000

\* Longer lengths may be available.

### Fiber Specifications

FIBER TYPE	MAXIMUM ATTENUATION (DB/KM)				OVERFILL LAUNCH MIN. BANDWIDTH (MHZ•KM)		GIGABIT ETHERNET MIN. LINK DISTANCE (METERS)	
	850 NM	1300 NM	1310 NM	1550 NM	850 NM	1300 NM	850 NM	1300 NM
(6) 62.5/125 GIGA-Link™ 300	3.5	1.2	N/A	N/A	200	600	300	550
(5) 50/125 GIGA-Link™ 600	2.9	0.9	N/A	N/A	500	500	600	600
(L) 50/125 Laser-Link™ 300	2.9	0.9	N/A	N/A	1500	500	900	550
(9) Single-mode	N/A	N/A	0.35	0.25	N/A	N/A	N/A	5000
(Q) Non-zero Dispersion-shifted Single-mode	N/A	N/A	N/A	0.25	N/A	N/A	N/A	N/A
(K) AFL G.657.A1 Single-mode	N/A	N/A	0.35	0.25	N/A	N/A	N/A	5000

Gigabit Ethernet Minimum Link Distances are based on "bandwidth"/modal dispersion constraints. Actual link distances may be constrained by attenuation, depending on specific loss budget.



## Riser Single-Jacket I/O Loose Tube (LV Series SJ)

### Ordering Information

AFL NO.	FIBER COUNT	NUMBER OF TUBES/FIBERS	NOMINAL DIAMETER	NOMINAL WEIGHT	MAXIMUM TENSILE LOAD		MINIMUM BEND RADIUS	
			INCHES (MM)	LBS/1,000 FT (KG/KM)	LBS. (N)		INCHES (CM)	
					SHORT TERM	LONG TERM	SHORT TERM	LONG TERM
LV006★C5101N1	6	1w/6 (4 fillers)	0.51 (12.9)	107 (159)	600 (2700)	200 (890)	10.2 (26)	5.1 (13)
LV012★C5101N1	12	1w/12 (4 fillers)	0.51 (12.9)	108 (160)	600 (2700)	200 (890)	10.2 (26)	5.1 (13)
LV018★C5101N1	18	1w/12, 1w/6 (3 fillers)	0.51 (12.9)	108 (161)	600 (2700)	200 (890)	10.2 (26)	5.1 (13)
LV024★C5101N1	24	2w/12 (3 fillers)	0.51 (12.9)	108 (161)	600 (2700)	200 (890)	10.2 (26)	5.1 (13)
LV030★C5101N1	30	2w/12, 1w/6 (2 fillers)	0.51 (12.9)	109 (162)	600 (2700)	200 (890)	10.2 (26)	5.1 (13)
LV036★C5101N1	36	3w/12 (2 fillers)	0.51 (12.9)	109 (162)	600 (2700)	200 (890)	10.2 (26)	5.1 (13)
LV048★C5101N1	48	4w/12 (1 filler)	0.51 (12.9)	110 (164)	600 (2700)	200 (890)	10.2 (26)	5.1 (13)
LV060★C5101N1	60	5w/12 (No fillers)	0.51 (12.9)	111 (165)	600 (2700)	200 (890)	10.2 (26)	5.1 (13)
LV072★C6101N1	72	6w/12 (No fillers)	0.54 (13.7)	128 (190)	600 (2700)	200 (890)	10.8 (28)	5.4 (14)
LV084★C8101N1	84	7w/12 (1 filler)	0.61 (15.5)	158 (236)	600 (2700)	200 (890)	12.2 (31)	6.1 (16)
LV096★C8101N1	96	8w/12 (No fillers)	0.61 (15.5)	159 (237)	600 (2700)	200 (890)	12.2 (31)	6.1 (16)
LV108★CA101N1	108	9w/12 (1 filler)	0.69 (17.4)	197 (294)	600 (2700)	200 (890)	14.0 (35)	7.0 (18)
LV120★CA101N1	120	10w/12 (No fillers)	0.69 (17.4)	198 (295)	600 (2700)	200 (890)	14.0 (35)	7.0 (18)
LV132★CC101N1	132	11w/12 (1 filler)	0.76 (19.3)	242 (360)	600 (2700)	200 (890)	15.2 (39)	7.6 (20)
LV144★CC101N1	144	12w/12 (No fillers)	0.76 (19.3)	243 (361)	600 (2700)	200 (890)	15.2 (39)	7.6 (20)

Note: Diameter and weight subject to change without notice

★ Fiber Types – Replace asterisk (★) in AFL number with number in the Fiber Specifications table on previous page.

### Reel Information

ITEM	REEL A		REEL B		REEL C		REEL D		REEL E	
	INCHES	CM	INCHES	CM	INCHES	CM	INCHES	CM	INCHES	CM
Reel Height	42	106.7	58	147.3	66	167.6	72	182.8	84	213.4
Reel Width Outside	36	91.4	38	96.5	42	106.7	42	106.7	40	101.6
Reel Width Inside	32	81.6	32	81.3	36	91.4	36	91.4	34	86.4
Drum Diameter	23	58.7	28	71.1	36	91.4	36	91.4	35	88.9
Arbor Hole Diameter	3	7.9	3	7.9	3	7.9	3	7.9	3	7.9
Reel Weight With Lagging	180 lbs	82 kg	420 lbs	191 kg	685 lbs	311 kg	710 lbs	320 kg	950 lbs	431 kg

AFL typically provides Loose Tube cable on several standard sizes of non-returnable wooden reels. Non-standard reel sizes are available upon request. Larger reel sizes may be required to accommodate long cable lengths.