



Manufacturer:
AFL

Product Name:
AFL CB-09 Cleaver Blade (for CT16 models)

Manufacturer Part Number:
S018335

▶ [Click here for more details on the AFL CB-09 Cleaver Blade \(for CT16 models\)](#)



Fusion Splicing



CT16 Fiber Cleaver

The CT16 fiber cleaver from Fujikura was designed for FTTH or other space constrained applications where ergonomics and durability are key. It is compact, can be operated ambidextrously, and features a unique fiber adapter, allowing users to cleave two bare fibers simultaneously when paired with the dual fiber stripper, the SS-05. The scrap collector and fiber adapter side can be swapped by the user for left or right-handed preference, or as environmental constraints dictate. Furthermore, the thumbwheel on the bottom of the cleaver is utilized for blade rotations as opposed to previous tedious processes to rotate a cleaver blade. The top lever opens past vertical allowing for easy viewing, cleaning, and adjustment of the cleave length. The blade is retracted when the top lever is opened and the blade activates to score the fiber when it is closed, making this a true one-step cleaver. Like its predecessor, this cleaver can withstand a 30" drop from any of six different orientations and still maintain factory specified cleave angle performance. The cleaver blade and fiber clamping mechanisms are easy to replace in the field, mitigating the need to send this cleaver in for service.

Cleavers



Features

- Dual fiber adapter plate for single or two fiber cleaving
- Ambidextrous operation available
- Field replaceable fiber clamp pads and cleaver blade
- Shock resistant for drops up to 30" in any of six different orientations
- Compact form factor and tool-less blade rotations

Applications

- Small cell site
- FTTx drops and terminations
- MDF/IDF splices and terminations
- Rural fiber deployments and restorations

Ordering Information

DESCRIPTION	AFL NO.
CT16 Fiber Cleaver includes: FDB-06 scrap collector, AD-16A fiber adapter, HEX-01 hex wrench (1.5 mm), M-CT16-E instruction manual, CC-46 carrying case	S018330
FDB-06 Scrap Collector	S018329
CB-09 Replacement Cleaver Blade	S018335
ARM-CT16-01 Replacement Fiber Clamp Pads	S018373
AD-16A Fiber Adapter (up to 900um coating)	S018328
AD-16B Fiber Adapter (up to 3.0mm jacket)	S018331
CC-46 Carrying Case	S018374

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.



Manufacturer:
AFL

Product Name:
AFL CB-09 Cleaver Blade (for CT16 models)

Manufacturer Part Number:
S018335

▶ [Click here for more details on the AFL CB-09 Cleaver Blade \(for CT16 models\)](#)



Fusion Splicing

Cleavers

CT16 Fiber Cleaver

Specifications

PARAMETER		VALUE
Applicable Fiber	Fiber type	Single-mode optical fiber
	Fiber count	Multimode optical fiber
	Cladding diameter	2 single fibers
Applicable Coating	Adapter plate	Approx. 125 µm
	Fiber holders	AD-16A: Max 900 µm coating diameter single fiber or 250 µm coating diameter for two fibers AD-16B: Max. 3 mm jacket diameter
Cleave Length	Adapter plate	FH-60 and FH-70 series – coating diameter dictated by specific fiber holder
	Fiber holder	AD-16A: 5 – 20 mm* ¹ AD-16B: Coating diameter – 250 µm or less: 5-20 mm* ¹ 251 µm-900 µm: 10-20 mm 901 µm-3 mm: 14-20 mm
Cleave Angle* ²	Single fiber	Approx. 10 mm
Blade Life* ³		Avg. 0.3 to 0.9 degrees
Physical description	Dimensions W	Approx. 48,000 fiber cleaves
	Dimensions D	Approx. 106 mm without projection* ⁴
	Dimensions H	Approx. 95.5 mm without projection* ⁴
	Weight	Approx. 49 mm without projection* ⁴
Environmental condition	Temperature	Approx. 190 g including AD-16A
	Humidity	Operate: -10 to 50°C Storage: -40 to 80°C
Other features	Blade rotation	Operate: 0 to 95%RH non-condensing Storage: 0 to 95%RH non-condensing
	Replaceable items	Manual dial underneath cleaver
	Fiber adapter base and scrap collector	Cleaver blade
	Cleave count	Fiber clamp pads
		Can be swapped position for ambidextrous operation
		Up to two individual bare fibers

Notes

- When the cleave length is less than 10 mm, the coating diameter should be 250 µm or less. Also, a blade height adjustment is required before cleaving. The average cleave angle is worse than the specification above when the cleave length is less than 10 mm.
- Measured with an interferometer at room temperature, no with a splicer. A new blade was used to cleave the single fibers. The average cleave angle changes depending on the environmental conditions, blade condition, operating method, and cleanliness.
- The blade life changes depending on the environmental conditions, operating method, and the fiber type cleaved.
- Measured with the top lever closed.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.