SAFETY DATA SHEET (SDS)



Manufacturer:

ÅngströmLap

Product Name:

ÅngströmBond AB9098 UV Optical Adhesive (3cc)

Manufacturer Part Number:

AB9098-3CC

Click here for more details on the ÅngströmBond AB9098 UV Optical Adhesive (3cc)

AB9098 from AngstromBond Page 1 of 3

Adhesives



GSTRÖMBONd®

Advanced Polymers for High Tech Applications

1. MATERIAL IDENTIFICATION

Product Name:

AB9098 from AngströmBond

For product emergencies involving spill, leak, fire, exposure, or accident call CHEMTREC at (800) 424-9300. For all other inquiries call Fiber Optic Center**, Inc. at (800) 473-4237. **Emergency Phone:**

2. COMPOSITION		Exposure Limits			
Hazardous Components	CAS No.	Percent	ACGIH TLV	OSHA PEL	OTHER
Isobornyl methacrylate	7534-94-3	25 - 50	N.E.	N.E.	N.E.
2-Hydroxyethyl methacrylate	868-77-9	25 - 50	N.E.	N.E.	N.E
Urethane Methacrylate Oligomer	Proprietary	25 - 50	N.E	N.E	N.E
Acrylic Acid	79-10-7	1 – 5	2 ppm	N.E.	N.E
Visible photoinitiator	Proprietary	1 – 5	N.E.	N.E.	N.E.

.Abbreviations: N.E. = Not Established

All hazardous ingredients are listed in the TCSA inventory as required

3. HEALTH HAZARDS IDENTIFICATION

Primary Routes of Exposure: Eyes: Yes Inhalation: Yes

Eye Contact: May cause irritation.

Skin Contact: May cause irritation and sensitization on contact.

Inhalation: May cause irritation. Ingestion: Effects are not known

4. PERSONAL PROTECTION

Eves: Splash proof Chemical safety glasses with side shields are recommended.

exceeded, if irritation occurs or other symptoms are experienced

Avoid skin contact. Wear gloves and impervious protective clothing if frequent direct contact is likely. Glove material

should be selected based on penetration time. Check with the manufacturer for exact times.

Inhalation: Local ventilation should be provided if general ventilation is not sufficient to keep vapor or mist concentrations below

permissible exposure limits. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if permissible exposure limits are

5. ACCIDENTIAL RELEASE MEASURES

Mount respiratory protective device. Wear protective clothing. Wear suitable gloves and eye/face protection. Inform authorities in case of seepage into water course or sewage system. Do not allow entry into sewers, surface or ground water. Absorb with liquid binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

AngströmBond® is a registered trademark of Fiber Optic Center, Inc., New Bedford MA, USA

Fiber Optic Center**, Inc. MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE, with respect to its products. In addition, while the information herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestion for use are made without guarantee – inasmuch as conditions of use are beyond our control. The properties given are typical values, and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes.

Rev. A Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.



SAFETY DATA SHEET (SDS)



Manufacturer:

ÅngströmLap

Product Name:

ÅngströmBond AB9098 UV Optical Adhesive (3cc)

Manufacturer Part Number:

AB9098-3CC

Click here for more details on the ÅngströmBond AB9098 UV Optical Adhesive (3cc)

AB9098 from AngstromBond Page 2 of 3

Adhesives



Advanced Polymers for High Tech Applications

6. HANDLING AND STORAGE

Storage: Store in unopened original receptacles. Keep tightly sealed. Protect from exposure to light. Avoid loss of dissolved air, loss of inhibitor, and contamination with incompatible materials.

Handling: Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. Keep respiratory devices available.

7. FIRE FIGHTING PROPERTIES

FLAMMABLE PROPERTIES

> 101℃(214℉) Explosive Limits (% volume in air): Not applicable. Not applicable. Auto-Ignition Temperature:

Hazardous Thermal Decomposition: Toxic fumes (oxides of carbon and nitrogen) may be evolved upon exposure

EXTINGUISHING MEDIA and FIRE FIGHTING INSTRUCTIONS
When sufficiently large quantities are present, firefighters should be equipped with full bunker gear, including a positive pressure, NIOSH approved, self-contained breathing apparatus.

Extinguishing Media: Use water spray, foam, dry chemical or carbon dioxide

8. EMERGENCY TREATMENT PROCEDURES

Remove affected person to fresh air. Seek medical attention

Inaestion: Low toxicity: Get medical attention. Skin Protection: Wash thoroughly with soap and water.

Eye Protection: Immediately flush eyes with water for at least 15 minutes. Get medical attention.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: Freezing Point: Specific Gravity: Liquid Characteristic Appearance/State: Not determined Not determined pH: Not determined Not determined Vap. Pressure (mmHg): Not determined Solubility in Water: Insoluable Not determined Vap. Density (air = 1): Evaporation Rate (Ether = 1): Not determined

10. STABILITY AND REACTIVITY

Hazardous Decomposition Products: None. Hazardous Polymerization: May occur.

Incompatibility: Oxidizers, amines, strong Lewis or mineral acids, thiosulfates. Smoke and toxic fumes may be

evolved as a result of uncontrolled exothermic reaction of large masses of material reacting with curing agents, such as peroxides, amines or exposure to light.

AngströmBond® is a registered trademark of Fiber Optic Center, Inc., New Bedford MA, USA

Fiber Optic Center**, Inc. MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE, with respect to its products. In addition, while the information herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestion for use are made without guarantee — inasmuch as conditions of use are beyond our control. The properties given are typical values, and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes.

Data is subject to change without notice.



Contact the professionals at Fiber Optic Center for a quote or to get more details.

SAFETY DATA SHEET (SDS)



Manufacturer:

ÅngströmLap

Product Name:

ÅngströmBond AB9098 UV Optical Adhesive (3cc)

Manufacturer Part Number:

AB9098-3CC

Click here for more details on the ÅngströmBond AB9098 UV Optical Adhesive (3cc)

AB9098 from AngstromBond Page 3 of 3

Adhesives



Advanced Polymers for High Tech Applications

11. REGULATORY INFORMATION

US FEDERAL REGULATIONS
TSCA: All Ingredients

SARA Title III Information

Section 313 - Toxic Chemicals:

Acrylic acid. Cas# 79-10-7 Methanol Cas# 67-56-1

DOT/IATA: Not restricted

Health: 2 HMIS:

Flammability: 1 Health: 2 Flammability: 1

Reactivity: 1 Reactivity: 1

STATE REGULATIONS / RIGHT TO KNOW

IARC: Acrylic acid: 3 Acrylic acid: A4 OSHA-Ca Visible photoinitiator

12. TOXICITY

Acute toxicity 7534-94-3 Isobornyl methacrylate

 $\begin{array}{ll} \text{Oral} & \text{LD50} > 2000 \text{ mg/kg (rat)} \\ \text{Dermal} & \text{LD50} > 3000 \text{ mg/kg(rabbit)} \end{array}$

868-77-9 2-Hydroxyethyl methacylate

LD50 5050 mg/kg (rat) Oral

79-10-7 Acrylic acid

LD50 250 mg/kg (rat) Dermal LD50 280 mg/kg (rabbit)

Ecological Information Harmful to fish

Slightly hazardous to water

Fiber Optic Center**, Inc. urges each customer or recipient of this MSDS to study it carefully in order to become aware of and understand the hazards associated with the product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, and/or fire prevention, as necessary to use and understand the data contained in this MSDS.

To promote safe handling, customers and recipients should: 1 – notify their employees, agents, contractors, and others whom they know or suspect will use this material or the information in this MSDS and any other information regarding hazards or safety; 2 – furnish this same information to each of their customers for the product; and 3 – request their customers to notify their employees, customers and other users of the product of this

The information contained herein is based on the data available to **Fiber Optic Center**, **Inc.**, and is believed to be correct. However, **Fiber Optic Center**, **Inc.** makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained from the use thereof. **Fiber Optic Center**, **Inc.** assumes no responsibility for injury from the use of the product described herein.

AngströmBond® is a registered trademark of Fiber Optic Center, Inc., New Bedford MA, USA

Fiber Optic Center™, Inc. MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE, with respect to its products. In addition, while the information herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestion for use are made without guarantee – inasmuch as conditions of use are beyond our control. The properties given are typical values, and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes.

Rev. A

Data is subject to change without notice.



