SAFETY DATA SHEET (SDS)



Manufacturer:

ÅngströmBond®

Product Name:

ÅngströmBond® AB9190 Low Viscosity Clear Epoxy, Room Temperature Cure (2.5g)

Manufacturer Part Number:

AB9190-2.5G

Click here for more details on the ÅngströmBond® AB9190 Low Viscosity Clear Epoxy, Room Temperature Cure (2.5q)

<u>igströ</u>mBond®

ÅngströmBond® AB9190 Hardene Page 1 of 3

<u>Adhesives</u>

Advanced Polymers for High Tech Applications

1. MATERIAL IDENTIFICATION

Product Name:

AngströmBond® AB9190 Hardener

For product emergencies involving spill, leak, fire, exposure, or accident call CHEMTREC at **Emergency Phone:**

(800) 424-9300. For all other inquiries call Fiber Optic Center™, Inc. at (800) 473-4237

| 2. COMPOSITION | Exposure Limits | | | | |
|---------------------------------------|-----------------|---------|------------------|-------------|--|
| Hazardous Components | CAS No. | Percent | ACGIH TLV-TWA | OSHA PEL | |
| Polyglycol Amine | Proprietary | < 100 | N.E. | N.E. | |
| Abbreviations: N.E. = Not Established | | | | | |

3. HEALTH HAZARDS IDENTIFICATION

Primary Routes of Exposure:

Inhalation: Yes

Eye Contact:

Corrosive. May cause burns and permanent injury. May cause lacrimation, conjunctivitis, and corneal edema when absorbed into the tissue of the eye from the atmosphere.

Skin Contact: Possible risk of irreversible effects in contact with the skin, Inhalation: May cause irritation

Ingestion: Moderately toxic. Will burn mucosae and stomach.

Other: Asthma, chronic respiratory diseases, eye diseases, and skin disorders may be aggravated by exposure to this product.

4. FIRST AID MEASURES

Eyes: Flush eyes thoroughly with water, for at least 15 minutes, while holding eyelids open. Seek immediate medical attention.

Skin: Generally does not irritate the skin. Obtain medical attention.

Inhalation: Remove to fresh air, and provide oxygen or artificial respiration if needed. Obtain immediate medical attention

Inaestion: Seek medical attention and show this container or label

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

Flash Point: > 261 F. estimated **Explosive Limits:** Auto - Ignition Temperature: Not determined **Hazardous Decomposition Products:** Nitrogen oxides

EXTINGUISHING MEDIA and FIRE FIGHTING INSTRUCTIONS

When sufficiently large quantities are present, firefighters should be equipped with full bunker gear, including a positive pressure, NIOSH approved, self-contained breathing apparatus.

Extinguishing Media: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

 ${f A}$ ngström ${f B}$ ond ${f @}$ is a registered trademark of Fiber Optic Center, Inc., New Bedford MA, USA

Fiber Optic CenterTM, Inc. MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE, with respect to its products. In addition, while the information herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestion for use are made without guarantee – inasmuch as conditions of use are beyond our control. The properties given are typical values, and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes.

11/2013 Rev. B

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.



SAFETY DATA SHEET (SDS)



Manufacturer:

ÅngströmBond®

Product Name:

ÅngströmBond® AB9190 Low Viscosity Clear Epoxy, Room Temperature Cure (2.5g)

Manufacturer Part Number:

AB9190-2.5G

Click here for more details on the ÅngströmBond® AB9190 Low Viscosity Clear Epoxy, Room Temperature Cure (2.5q)



ÅngströmBond® AB9190 Hardener Page 2 of 3

Adhesives

Advanced Polymers for High Tech Applications

6. ACCIDENTIAL RELEASE MEASURES

Do not allow to enter sewers/ surface or ground water. Absorb with liquid-binding material (sand, diatomite, acid binders universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

7. HANDLING AND STORAGE

Store in cool, dry place in tightly closed receptacles. Use only in well ventilated areas. Keep receptacle tightly sealed

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering / Ventilation Controls:

General ventilation may be acceptable under most conditions, although local ventilation is required

to control exposure whenever vapors, mists, or dusts are generated

Impervious gloves and protective clothing should be worn as necessary

Respiratory Protection:

When local ventilation is unavailable and airborne limits are exceeded, a NIOSH-approved respirator for organic vapors, a supplied-air respirator, or a self-contained breathing apparatus is required.

Skin Protection:

Eye Protection: Chemical splash goggles or safety glasses with side shields should be worn as appropriate.

9. STABILITY AND REACTIVITY

Chemical Stability:

Stable under normal conditions and use

Conditions and Materials to Avoid: Reacts with acids. Reacts with strong acids. Hazardous Decomposition Products: Nitrogen oxides, Irritant gases/vapors

Hazardous Polymerization:

Will not occur

10. PHYSICAL AND CHEMICAL PROPERTIES

Appearance / State: Odor:

Clear-colored liquid Mild ammonia odor

Freezing Point: Vap. Pressure (mmHG):

Boiling Point:

358°F Not determined

Specific Gravity: Solubility in Water:

Not miscible

Vap. Density (air = 1):

Not determined

Rev. B

11. TOXICOLOGICAL INFORMATION

This product is not known to have undergone toxicological testing.

12. DISPOSAL CONSIDERATIONS

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

 $\overline{ exttt{A}}$ ngström $\operatorname{\mathsf{Bond}}$ $\mathbb B$ is a registered trademark of Fiber Optic Center, Inc., New Bedford MA, USA

Fiber Optic Center**, Inc. MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE, with respect to its products. In addition, while the information herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestion for use are made without guarantee -- inasmuch as conditions of use are beyond our control. The properties given are typical values, and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this 11/2013

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.



SAFETY DATA SHEET (SDS)



Manufacturer:

ÅngströmBond®

Product Name:

ÅngströmBond® AB9190 Low Viscosity Clear Epoxy, Room Temperature Cure (2.5g)

Manufacturer Part Number:

AB9190-2.5G

Click here for more details on the ÅngströmBond® AB9190 Low Viscosity Clear Epoxy, Room Temperature Cure (2.5q)

<u>igst</u>römBond®

ÅngströmBond® AB9190 Hardener Page 3 of 3

Adhesives

Advanced Polymers for High Tech Applications

13. TRANSPORTATION INFORMATION

DOT/IATA: Proper Shipping Name: polyglycolamine, Liquid, Corrosive, N.O.S.

Hazard Class: 8 ID: UN1760 Label: Corrosive Packaging Group: III

 Land transport
 ADR/RID:
 Proper Shipping Name:
 polyglycolamine, Liquid, Corrosive, N.O.S.

 UN:
 1760
 Label:
 Corrosive
 ADR/RID Class:
 8
 Packaging Group:
 III
Danger Code: 80

Marine transport IMDG: Proper Shipping Name: polyglycolamine, Liquid, Corrosive, N.O.S.

UN: 1760 La Marine Pollutant: No Label: Corrosive IMDG Class: 8 Packaging Group: III EMS number: F-A.S-B

Air Transport ICAO-TI and IATA-DGR Proper Shipping Name: polyglycolamine, Liquid, Corrosive, N.O.S.

ID: 1760 Label: Corrosive Hazard Class: 8 Packaging Group: III

14. REGULATORY INFORMATION

TSCA The chemical components of this product are included in the TSCA Chemical Substance Inventory, as required.

SARA TITLE III

Section 313 - Toxic Chemicals

Pursuant to Section 313, this product does not contain any chemicals in a concentration equal to or greater than the de minimis level.

HMIS Ratings: Health:2 Fire: 1 Reactivity: 0

Fiber Optic Center***, Inc. urges each customer or recipient of this MSDS to study it carefully in order to become aware of and understand the hazards associated with the product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, and/or fire prevention, as necessary to use and understand the data contained in this MSDS.

To promote safe handling, customers and recipients should: 1 – notify their employees, agents, contractors, and others whom they know or suspect will use this material or the information in this MSDS and any other information regarding hazards or safety; 2 – furnish this same information to each of their customers for the product; and 3 - request their customers to notify their employees, customers and other users

The information contained herein is based on the data available to **Fiber Optic Center**TM, **Inc.**, and is believed to be correct. However, **Fiber Optic Center**TM, **Inc.** makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained from the use thereof. **Fiber Optic Center**TM, **Inc.** assumes no responsibility for injury from the use of the product described herein.

AngströmBond® is a registered trademark of Fiber Optic Center, Inc., New Bedford MA, USA

Fiber Optic CenterTM, Inc. MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE, with respect to its products. In addition, while the information herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestion for use are made without guarantee – inasmuch as conditions of use are beyond our control. The properties given are typical values, and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

