

SAFETY DATA SHEET (SDS)



Manufacturer:
ÅngströmBond®

Product Name:
ÅngströmBond® AB9266 Flexible, Casting Epoxy, Room Temperature Cure (2.5g)

Manufacturer Part Number:
AB9266-2.5G

▶ Click here for more details on the ÅngströmBond® AB9266 Flexible, Casting Epoxy, Room Temperature Cure (2.5g)



ADVANCED POLYMERS for High Tech Applications

ÅngströmBond 9266 Hardener
Page 1 of 3

Adhesives

1. MATERIAL IDENTIFICATION

Product Name:

ÅNGSTRÖMBOND 9266 HARDENER

Emergency Phone:

For product emergencies involving spill, leak, fire, exposure, or accident call CHEMTREC at (800) 424-9300. For all other inquiries call **Fiber Optic Center™, Inc.** at (800) 473-4237.

2. COMPOSITION

Hazardous Components	CAS No.	Exposure Limits		
		Percent	ACGIH TLV-TWA	OSHA PEL
N-Aminoethyl Piperazine	140-31-8	12-20	NE	NE
Nonyl Phenol	84852-15-3	30-50	NE	NE
Proprietary Mixture		20-32	NE	NE
2,4,6, Tris (dimethylamino) phenol	90-72-2	2-7	NE	NE
Abbreviations: N.E. = Not Established				

3. HEALTH HAZARDS IDENTIFICATION

Eye Contact: May cause slight irritation.
Skin Contact: May cause slight irritation, but no significant effect.
Ingestion: Harmful if swallowed..
Inhalation: Heating can generate vapors that may cause respiratory irritation, nausea, and headache. Inhalation hazard at Room temperature is unlikely, due to the low volatility of this product.

4. FIRST AID MEASURES

Eyes: Immediately flush with water for at least 15 minutes. Get medical attention.
Skin: Remove product from skin with dry cloth or paper towel, and wash exposed area with water and mild detergent.
Inhalation: Remove to fresh air, and provide oxygen if breathing is difficult. Obtain medical attention.
Ingestion: Wash out mouth with water provided person is conscious. Never give anything by mouth to an unconscious person. Call a physician immediately.

5. ACCIDENTAL RELEASE MEASURES

Small Spills
Activate available exhaust ventilation equipment in the immediate spill area. Wipe up or absorb spilled material with paper towels or other absorbent material. Wash area with soapy water to remove residue. Collect absorbed material and water rinses in appropriate containers. Dispose of in accordance with current Federal, State, and local regulations.
Large Spills
Limit access to the immediate spill area. Shut off source of the release if this can be done without risk of injury. Activate available exhaust ventilation equipment in the spill area. Dike area to contain the spill and prevent releases to sewers, drains or other waterways. Collect spilled material for salvage/disposal. Apply absorbent material to soak up residue. Wash area with soapy water. Prevent runoff from entering waterways. Transfer absorbed material and water rinses to appropriate waste containers. Dispose of in accordance with current Federal, State, and local regulations.

6. HANDLING AND STORAGE

Precaution to be taken in handling and storing:
Keep container closed when not in use. Vent the container properly to eliminate internal pressure. Store in a cool place (Qualitatively under 10 degrees C). Keep away from heat and flame. Do not lay the container on its side. Avoid contact with eyes and prolonged or repeated skin contact. Avoid contact with acidic, basic or oxidizing materials. Contact lens wearers take appropriate precaution. Keep out of reach of children. Do not re-use this container. Keep away from heat, sparks and flame. Do not puncture or cut this container. Do not weld on or near this container.

ÅNGSTRÖMBOND® is a REGISTERED TRADEMARK of FIBER OPTIC CENTER, INC., NEW BEDFORD MA, USA

Fiber Optic Center™, Inc. MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE, with respect to its products. In addition, while the information herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestion for use are made without guarantee – inasmuch as conditions of use are beyond our control. The properties given are typical values, and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes.

Rev. A 2/2009

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



SAFETY DATA SHEET (SDS)



Manufacturer:
ÅngströmBond®

Product Name:
ÅngströmBond® AB9266 Flexible, Casting Epoxy, Room Temperature Cure (2.5g)

Manufacturer Part Number:
AB9266-2.5G

▶ Click here for more details on the ÅngströmBond® AB9266 Flexible, Casting Epoxy, Room Temperature Cure (2.5g)



ÅngströmBond 9266 Hardener
Page 2 of 3

Adhesives

ADVANCED POLYMERS for High Tech Applications

7. FIRE FIGHTING PROPERTIES

FLAMMABLE PROPERTIES

Flash Point: > 275°F (based on Flash point of components)

EXTINGUISHING MEDIA and FIRE FIGHTING INSTRUCTIONS

Firefighters/rescue personnel should wear positive pressure self-contained breathing apparatus and full protective equipment. Cool exposed containers with water to prevent pressure buildup. If large quantities of material are involved, evacuate area and fight fire from a safe distance.

Extinguishing Media: Use sand, dry chemical, carbon dioxide, or an appropriate foam.

Unusual fire or Explosive Hazards:

Decomposition and combustion products may be toxic. Closed containers may violently rupture under fire condition.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering / Ventilation Controls: General ventilation is acceptable under most conditions, although local ventilation is required to control exposure whenever vapors, mists, or dusts are generated. Eye wash stations should be readily available.

Respiratory Protection: Provide effective mechanical exhaust ventilation to draw vapors, mists or fumes generated during processing away from the worker and prevent routine inhalation, especially during elevated temperature processing. Ventilation must be sufficient to maintain airborne levels of Section 2 ingredients below their PEL/TLV values. Use an appropriate, properly fitted respirator if exposures exceed PEL/TLV values. The type of protection selected (SCBA, air purifying) will depend upon the conditions of use. Observe OSHA regulations for respiratory protection (29 CFR 1910.134).

Skin Protection: Wear impervious gloves and protective clothing as necessary to prevent skin contact. Promptly remove contaminated clothing and launder thoroughly before reuse.

Eye Protection: Wear chemical safety glasses or goggles. Have Eyewash equipment available.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance/State:	Lt. Amber liquid	Boiling Point:	Not determined
Odor:	amine	Freezing Point:	Not determined
pH:	Not determined	Specific Gravity:	1.00 @25°C
Vap. Pressure (mmHg):	<1(mmHg@25°C)	Solubility in Water:	not soluble
Vap. Density (air = 1):	>1	Evaporation Rate (Butyl Acetate = 1):	<1

10 STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions and use.

Conditions and Materials to Avoid: Acidic, basic or oxidizing materials and certain petroleum compounds. Contact with acidic, basic or oxidizing materials. Avoid storage in open containers, exposure to open flame or uncontrolled exposure to heat, uncontrolled mixing or exposure to incompatible substances.

Hazardous Decomposition Products: Carbon oxides, aldehydes, amines, aniline, acids, and other organic substances may be formed during combustion. The chemical nature and quantity of decomposition by products will vary widely depending on the conditions of combustion.

Hazardous Polymerization: uncontrolled mixing with resins may cause hazardous Polymerization.

11 DISPOSAL CONSIDERATIONS

Can be burned in a chemical incinerator equipped with an afterburner and scrubber. Do not dispose of the emptied container unlawfully. Observe all federal, state and local laws.

ÅNGSTRÖMBOND® is a REGISTERED TRADEMARK of Fiber Optic Center, Inc., New Bedford MA, USA

Fiber Optic Center™, Inc. MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE, with respect to its products. In addition, while the information herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestion for use are made without guarantee -- inasmuch as conditions of use are beyond our control. The properties given are typical values, and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes.

Data is subject to change without notice.

Rev. A 02/2009

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com



SAFETY DATA SHEET (SDS)



Manufacturer:
ÅngströmBond®

Product Name:
ÅngströmBond® AB9266 Flexible, Casting Epoxy, Room Temperature Cure (2.5g)

Manufacturer Part Number:
AB9266-2.5G

▶ Click here for more details on the ÅngströmBond® AB9266 Flexible, Casting Epoxy, Room Temperature Cure (2.5g)



ADVANCED POLYMERS FOR HIGH TECH APPLICATIONS

AngstromBond 9266 Hardener
Page 3 of 3

Adhesives

12 TOXICOLOGICAL INFORMATION

Acute Toxicity (LD50): No information available
Acute Toxicity (LC50): Not Available
Chronic toxicity: Not Applicable
Carcinogen: NTP Not listed
IARC: not classified as carcinogen
OSHA regulated: not regulated

13 TRANSPORTATION INFORMATION

Not regulated by IATA.
Not regulated by DOT.

14 REGULATORY INFORMATION

US FEDERAL REGULATIONS

TSCA: The chemical components of this product are included in the TSCA Chemical Substance Inventory list, as required.

SARA Title III

Section 313 – Toxic chemicals:

Pursuant to section 313 or SARA Title III, this product does not contain any chemicals exceeding de minimis levels.

HMIS Ratings: Health: 2 Flammability: 0 Reactivity: 0

Fiber Optic Center™, Inc. urges each customer or recipient of this MSDS to study it carefully in order to become aware of and understand the hazards associated with the product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, and/or fire prevention, as necessary to use and understand the data contained in this MSDS.

To promote safe handling, customers and recipients should: 1 – notify their employees, agents, contractors, and others whom they know or suspect will use this material or the information in this MSDS and any other information regarding hazards or safety; 2 – furnish this same information to each of their customers for the product; and 3 – request their customers to notify their employees, customers and other users of the product of this information.

The information contained herein is based on the data available to **Fiber Optic Center™, Inc.**, and is believed to be correct. However, **Fiber Optic Center™, Inc.** makes no warranty, expressed or implied, regarding the accuracy of this data or the results to be obtained from the use thereof. **Fiber Optic Center™, Inc.** assumes no responsibility for injury from the use of the product described herein.

ÅNGSTRÖMBOND® is a REGISTERED TRADEMARK of Fiber Optic Center, Inc., New Bedford MA, USA

Fiber Optic Center™, Inc. MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE, with respect to its products. In addition, while the information herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestion for use are made without guarantee – inasmuch as conditions of use are beyond our control. The properties given are typical values, and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes.

Rev. A 02/2009

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

23 Centre Street • New Bedford, MA 02740 USA • focenter.com

508-992-6464 | (800) 473-4237 • sales@focenter.com

