

### **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Supersedes date: 9/6/2014

## **Manufacturer Part Number:**

ET305-4G

► Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4q)

Revision date: 10/9/2019



# SAFETY DATA SHEET EPO-TEK® 305 Part B

1. Identification

Product identifier

Product name EPO-TEK® 305 Part B

Product number 305/B

Recommended use of the chemical and restrictions on use

Application Adhesive.

Uses advised against Use only for intended applications.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.

14 Fortune Drive Billerica, MA 01821 USA (978) 667-3805 (978) 663-9782

www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone ChemTel: +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 3 - H412

Label elements

Hazard symbols





Signal word Danger

Hazard statements H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects.







### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

### **Manufacturer Part Number:**

ET305-4G

► Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4q)

Revision date: 10/9/2019

1 2 1 2 1

EPO-TEK® 305 Part B

Precautionary statements P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/ shower.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/ container in accordance with national regulations.

Contains Trimethyl-1, 6-Hexanediamine

### 3. Composition/information on ingredients

#### Mixtures

Trimethyl-1, 6-Hexanediamine

60-100%

Supersedes date: 9/5/2014

CAS number: 25513-64-8

#### Classification

Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412

The full text for all hazard statements is displayed in Section 16.

#### 4. First-aid measures

#### Description of first aid measures

Inhalation Move affected person to fresh air at once. Rinse nose and mouth with water. Never give

anything by mouth to an unconscious person. Do not induce vomiting. Keep affected person

warm and at rest. Get medical attention immediately.

Ingestion Do not induce vomiting. Never give anything by mouth to an unconscious person. Do not

induce vomiting. Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention

immediately

Skin Contact Remove affected person from source of contamination. Rinse immediately with plenty of

water. Get medical attention promptly if symptoms occur after washing.

Eye contact Remove affected person from source of contamination. Remove any contact lenses and open

eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

### Most important symptoms and effects, both acute and delayed

Inhalation Gas or vapor in high concentrations may irritate the respiratory system. Inhalation of dust

during cutting, grinding or sanding operations involving this product may cause irritation of the

respiratory tract

Ingestion Harmful if swallowed. May cause stomach pain or vomiting. May cause chemical burns in

mouth, esophagus and stomach. May cause nausea, headache, dizziness and intoxication.

Skin contact Causes severe burns. May cause an allergic skin reaction. May cause sensitisation by skin

contact.

Eye contact Causes serious eye damage.

Indication of immediate medical attention and special treatment needed







## Manufacturer:

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

## **Manufacturer Part Number:**

ET305-4G

Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Revision date: 10/9/2019	Revision: 2	Supersedes date: 9/5/2014		
EPO-TEK® 305 Part B				
Notes for the doctor	Treat symptomatically.			
5. Fire-fighting measures				
Extinguishing media				
Suitable extinguishing media	Extinguish with the following media: Dry chemicals. Foam. Water spr	ay.		
Special hazards arising from t	ne substance or mixture			
Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides ar vapors.	nd other toxic gases or		
Advice for firefighters				
Protective actions during firefighting	Avoid breathing fire gases or vapors.			
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) a clothing.	and appropriate protectiv		
6. Accidental release measure	s			
Personal precautions, protecti	e equipment and emergency procedures			
Personal precautions	Wear protective clothing as described in Section 8 of this safety data	sheet.		
Environmental precautions				
Environmental precautions	Avoid release to the environment.			
Methods and material for cont	ainment and cleaning up			
Methods for cleaning up	Wear suitable protective equipment, including gloves, goggles/face s clothing or apron, as appropriate. Stop leak if possible without risk. A sand or earth and place into containers. Avoid contamination of pond washing down water.	bsorb in vermiculite, dry		
Reference to other sections	For personal protection, see Section 8.			
7. Handling and storage				
Precautions for safe handling				
Usage precautions	Handle all packages and containers carefully to minimize spills. Avoi contact with skin and eyes. Wear protective clothing as described in data sheet.			
Advice on general occupational hygiene	Do not eat, drink or smoke when using this product. Wash promptly it contaminated. Wash hands thoroughly after handling. Take off conta wash before reuse. Use appropriate skin cream to prevent drying of	minated clothing and		
Conditions for safe storage, in	cluding any incompatibilities			
Storage precautions	Store at room temperature. Keep container tightly sealed when not in	i use.		
Storage class	Corrosive storage.			
Specific end uses(s)				
Specific end use(s)	The identified uses for this product are detailed in Section 1.			
8. Exposure controls/Persona	protection			
Ingredient comments	No exposure limits known for ingredient(s).			
Exposure controls				







### **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Supersedes date: 9/5/2014

## **Manufacturer Part Number:**

ET305-4G

Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4q)

EPO-TEK® 305 Part B

Revision date: 10/9/2019



Provide adequate general and local exhaust ventilation.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn.

Other skin and body

protection

Wear appropriate clothing to prevent skin contamination. Provide eyewash station.

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing

that becomes wet or contaminated.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be wom.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance Liquid. Color Clear. Odor Amine

Odor threshold No specific test data are available No specific test data are available pΗ No specific test data are available Melting point Initial boiling point and range No specific test data are available.

232°C Flash point Evaporation rate <BuAc

Flammability (solid, gas) No specific test data are available. Upper/lower flammability or No specific test data are available.

explosive limits

Vapor pressure No specific test data are available.

Vapor density

Relative density No specific test data are available.

Solubility(ies) Insoluble in water.

Partition coefficient No specific test data are available. Auto-ignition temperature No specific test data are available. Decomposition Temperature No specific test data are available. Viscosity No specific test data are available

Other information







## Manufacturer:

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

## **Manufacturer Part Number:**

ET305-4G

Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

	EPO-TEK® 305 Part B	
10. Stability and reactivity		
Reactivity	The following materials may react violently with the product: Acids. Alkalis. Strong oxidizing agents. Strong reducing agents.	
Stability	Stable at normal ambient temperatures and when used as recommendations	ded.
Possibility of hazardous reactions	Will not polymerize.	
Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid heat, flame ignition.	s and other sources of
Materials to avoid	Strong acids. Strong alkalis. Strong oxidizing agents. Strong reducing	agents.
Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and vapors.	d other toxic gases or
11. Toxicological information		
Information on toxicological eff	ects	
Acute toxicity - oral ATE oral (mg/kg)	500.0	
Inhalation	May cause respiratory system irritation.	
Ingestion	Causes burns. May cause chemical burns in mouth and throat. May committing.	ause stomach pain or
Skin Contact	May cause allergic contact eczema. May cause sensitisation by skin o	contact. Causes burns.
Eye contact	Severe irritation, burning and tearing. Causes burns.	
12. Ecological information		
Ecotoxicity	Harmful to aquatic life with long lasting effects.	
Acute aquatic toxicity  Acute toxicity - fish	No information available.	
Persistence and degradability		
	The product is biodegradable.	
Bioaccumulative potential		
Bio-Accumulative Potential	The product is not bioaccumulating.	
Partition coefficient	No specific test data are available.	
Mobility in soil	Mobile	
Mobility	modile.	
Other adverse effects Other adverse effects	Not known.	
13. Disposal considerations		





## Manufacturer:

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

## **Manufacturer Part Number:**

ET305-4G

Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Revision date: 10/9/2019	Revision: 2	Supersedes date: 9/5/2014
	EPO-TEK® 305 Part B	
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the local Waste Disposal Authority.	e requirements of the
14. Transport information		
UN Number		
UN No. (TDG)	2327	
UN No. (IMDG)	2327	
UN No. (ICAO)	2327	
UN No. (DOT)	UN2327	
UN proper shipping name		
Proper shipping name (TDG)	TRIMETHYLHEXAMETHYLENEDIAMINES	
Proper shipping name (IMDG)	TRIMETHYLHEXAMETHYLENEDIAMINES	
Proper shipping name (ICAO)	TRIMETHYLHEXAMETHYLENEDIAMINES	
Proper shipping name (DOT)	TRIMETHYLHEXAMETHYLENEDIAMINES	
Transport hazard class(es)		
DOT hazard class	8	
DOT hazard label	8	
TDG class	8	
TDG label(s)	8	
IMDG Class	8	
ICAO class/division	8	
Transport labels		
DOT transport labels		
Packing group		
TDG Packing Group	III	
IMDG packing group	III	
ICAO packing group	III	
DOT packing group	III	
Environmental hazards		
Environmentally Hazardous Su No.	ibstance	
Special precautions for user		
EmS	F-A, S-B	





### **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

### **Manufacturer Part Number:**

ET305-4G

Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4q)

#### EPO-TEK® 305 Part B

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

## 15. Regulatory information

Regulatory References

Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of Intellectual Property Rights (TRIPS), Section 7, Art. 39.

#### US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed.

SARA 313 Emission Reporting

None of the ingredients are listed.

CAA Accidental Release Prevention

None of the ingredients are listed.

OSHA Highly Hazardous Chemicals None of the ingredients are listed.

\_

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed.

California Air Toxics "Hot Spots" (A-I) None of the ingredients are listed.

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed.

Massachusetts "Right To Know" List

None of the ingredients are listed.

Rhode Island "Right To Know" List None of the ingredients are listed.

\_

Minnesota "Right To Know" List None of the ingredients are listed.

New Jersey "Right To Know" List

The following ingredients are listed:

Trimethyl-1, 6-Hexanediamine

Pennsylvania "Right To Know" List

None of the ingredients are listed.

Inventories





## **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

Supersedes date: 9/5/2014

### **Manufacturer Part Number:**

ET305-4G

Click here for more details on the EPO-TEK® 305 Spectrally Transparent Flexible Epoxy, Room Temperature Cure (4g)

#### EPO-TEK® 305 Part B

Revision: 2

**EU - EINECS/ELINCS** 

Revision date: 10/9/2019

All the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification None of the ingredients are listed.

Australia - AICS

All the ingredients are listed or exempt.

Japan - ENCS

None of the ingredients are listed.

Korea - KECI

None of the ingredients are listed.

China - IECSO

All the ingredients are listed or exempt.

Philippines - PICCS

None of the ingredients are listed.

### 16. Other information

 Revision date
 10/9/2019

 Revision
 2

 Supersedes date
 9/5/2014

Hazard statements in full

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.



