

Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:

ET323LP-8OZ

Click here for more details on the EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (80z)



EPOXY EPO-TEK® 323LP PART B

Safety Data Sheet

A Meridian Adhesives Group Company according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 3/23/2022 Revision date: 12/30/2022 Supersedes: 3/23/2022 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : EPO-TEK® 323LP PART B

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Adhesives Recommended use : Adhesives

Restrictions on use : Not to be used for any purpose other than the one the product was designed for

1.3. Supplier

Epoxy Technology, Inc. 14 Fortune Drive Billerica, MA 01821, 01821

USA

T 978-667-3805 - F 978-663-9782

www.epotek.com

1.4. Emergency telephone number

Emergency number : ChemTel: +1 (800) 255-3924, +1 (813) 248-0585

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

H301 Acute toxicity (oral) Category 3 Toxic if swallowed Skin corrosion/irritation Category 2 H315 Causes skin irritation Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage Skin sensitization, Category 1 H317 May cause an allergic skin reaction Reproductive toxicity Category 1B H360 May damage fertility or the unborn child Specific target organ toxicity - Single exposure, Category 3, H335 May cause respiratory irritation

Respiratory tract irritation

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)







Signal word (GHS US)

Precautionary statements (GHS US)

Hazard statements (GHS US) : H301 - Toxic if swallowed

H315 - Causes skin irritation H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H360 - May damage fertility or the unborn child
P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

Danger





Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:

ET323LP-8OZ

Click here for more details on the EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

EPO-TEK® 323LP PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 - If swallowed: Immediately call a poison center or doctor.

P302+P352 - If on skin: Wash with plenty of water.

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a poison center or doctor.

P312 - Call a poison center or doctor if you feel unwell.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P330 - Rinse mouth.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P363 - Wash contaminated clothing before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

2.4. Unknown acute toxicity (GH\$ U\$)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Substituted imidazole*	CAS-No.: Trade Secret	≥ 30	Acute Tox. 4 (Oral), H302
Substituted imidazole*	CAS-No.: Trade Secret	1 – 60	Acute Tox. 3 (Oral), H301 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
1H-Imidazole, 2-methyl-	CAS-No.: 693-98-1	<1	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314 Repr. 1B, H360
Reactive diluent*	CAS-No.: Trade Secret	<1	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317

Data is subject to change without notice.







Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:

ET323LP-8OZ

Click here for more details on the EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

EPO-TEK® 323LP PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regi

*Chemical name. CAS number and/or exact concentration have been withheld as a trade secret

: Components not listed are either non-hazardous or are below reportable limits.

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after ingestion

: Call a physician immediately. First-aid measures general

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison

center/doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs:

Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Call a physician immediately. : Rinse mouth. Call a physician immediately.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction

Symptoms/effects after eye contact : Serious damage to eyes.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

: Only qualified personnel equipped with suitable protective equipment may intervene. Avoid Emergency procedures

breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

: Do not attempt to take action without suitable protective equipment. For further information refer Protective equipment

to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

Data is subject to change without notice.





Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:

ET323LP-8OZ

Click here for more details on the EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

EPO-TEK® 323LP PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read
and understood. Wear personal protective equipment. Use only outdoors or in a well-ventilated

area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

eat, drink or smoke when using this product. Always wash hands after handling the product.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

Data is subject to change without notice.





Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:

: Liquid

ET323LP-8OZ

Click here for more details on the EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (80z)

EPO-TEK® 323LP PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment symbol(s):



Physical state





SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Color Odor : Mild odor Odor threshold : No data available : No data available pΗ Melting point : No data available Freezing point : No data available : No data available Boiling point Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available Flammability : Not applicable. : No data available Vapor pressure Relative vapor density at 20°C : No data available Relative density : No data available Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosion limits No data available Explosive properties No data available Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

Data is subject to change without notice.





Manufacturer: Epoxy Technology

Product Name:

EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:

ET323LP-8OZ

Click here for more details on the EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

EPO-TEK® 323LP PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information	on
11.1. Information on toxicological effects	
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	Toxic if swallowed. Not classified Not classified
EPO-TEK® 323LP PART B	
ATE US (oral)	177.522 mg/kg body weight
Substituted imidazole	
ATE US (oral)	100 mg/kg body weight
Substituted imidazole	
ATE US (oral)	500 mg/kg body weight
1H-Imidazole, 2-methyl- (693-98-1)	
LD50 oral rat	1500 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 7 day(s))
LD50 dermal rat	> 2000 mg/kg (Rat, Dermal)
ATE US (oral)	1400 mg/kg body weight
Reactive diluent	
ATE US (oral)	1120 mg/kg body weight
ATE US (dermal)	2150 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h
Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitization	Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified : Not classified
Carcinogenicity 1H-Imidazole, 2-methyl- (693-98-1)	. IYU Ciassilieu
NOAEL (chronic,oral,animal/male,2 years)	13 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Remarks on results: other:Effect type: carcinogenicity (migrated information)
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: May damage fertility or the unborn child.
STOT-single exposure	: May cause respiratory irritation.
Substituted imidazole	Warrange and the state of the Barrange and the Barrange
STOT-single exposure STOT-repeated exposure	May cause respiratory irritation. : Not classified
Aspiration hazard	: Not classified

Data is subject to change without notice.





Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:

ET323LP-8OZ

Click here for more details on the EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (80z)

EPO-TEK® 323LP PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic

: No data available

Symptoms/effects after inhalation

: May cause respiratory irritation.

Symptoms/effects after skin contact

: Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Serious damage to eyes.

SECTION	12: Ecolog	jicai informatio	on

2.			

Ecology - general

: The product is not considered harmful to aquatic organisms or to cause long-term adverse

effects in the environment.

1H-Imidazole, 2-methyl- (693-98-1)				
LC50 - Fish [1] 190 mg/l (DIN 38412: German standard methods for the examination of water, waste w sludge, 96 h, Leuciscus idus, Static system, Fresh water, Experimental value)				
EC50 - Crustacea [1] 225.31 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experime value)				
ErC50 algae	256.3 mg/l (DIN 38412-9, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)			
Reactive diluent				
LC50 - Fish [1] 13 mg/l				
NOEC chronic algae	29 mg/l			

12.2. Persistence and degradability

1 U Imidaz	ale 2 methy	L <i>(6</i> 93.98.1)

Persistence and degradability Readily biodegradable in water.

Reactive diluent

Persistence and degradability Not readily biodegradable in water.

12.3. Bioaccumulative potential

1H-Imidazole, 2-methy	vI_ ((693-98-1)
III-IIIIIuazoie, z-iiieui	y 1- \	(055-50-1)

Partition coefficient n-octanol/water (Log Pow) 0.22 (Experimental value, Equivalent or similar to OECD 107, 25 °C)		
Bioaccumulative potential Low potential for bioaccumulation (Log Kow < 4).		
Reactive diluent		
Partition coefficient n-octanol/water (Log Pow) -0.15		
Bioaccumulative potential	Not bioaccumulative.	

12.4. Mobility in soil

1H-Imidazole, 2-methyl- (693-98-1)

Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.94 (log Koc, Calculated value, pH = 7)
Ecology - soil	Low potential for adsorption in soil.

Data is subject to change without notice.







Manufacturer: Epoxy Technology

Product Name:

EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:

ET323LP-8OZ

Click here for more details on the EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (80z)

EPO-TEK® 323LP PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable
Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not applicable

TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available

14.6. Special precautions for user

DOT

No data available

TDG

No data available

IMDG

Data is subject to change without notice.

No data available





Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:

ET323LP-8OZ

Click here for more details on the EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

EPO-TEK® 323LP PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IATA No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act

15.2. International regulations

Substituted imidazole

Listed on the Canadian DSL (Domestic Substances List)

Substituted imidazole

Listed on the Canadian NDSL (Non-Domestic Substances List)

1H-Imidazole, 2-methyl- (693-98-1)

Listed on the Canadian DSL (Domestic Substances List)

Reactive diluent

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

1H-Imidazole, 2-methyl- (693-98-1)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

MARNING:

This product can expose you to 2-Methylimidazole, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date

Full text of H-phra	Full text of H-phrases	
H301	Toxic if swallowed	
H302	Harmful if swallowed	

Data is subject to change without notice.





Manufacturer: Epoxy Technology

Product Name:

EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

Manufacturer Part Number:

ET323LP-8OZ

Click here for more details on the EPO-TEK® 323LP High Temperature Epoxy, Heat Cure (8oz)

EPO-TEK® 323LP PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phra	Full text of H-phrases		
H314	Causes severe skin burns and eye damage		
H315	Causes skin irritation		
H317	May cause an allergic skin reaction		
H318	Causes serious eye damage		
H319	Causes serious eye irritation		
H332	Harmful if inhaled		
H335	May cause respiratory irritation		
H360	May damage fertility or the unborn child		

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

 $Data\ is\ subject\ to\ change\ without\ notice.$

