

Manufacturer:

Epoxy Technology

Product Name: EPO-TEK[®] 353ND High Temperature Epoxy, Heat Cure (2.5g)

Manufacturer Part Number: ET353ND-2.5G

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (2.5g)

EPO-TEK® 353ND PART B **J EPOXY** TECHNOLOGY Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 2/15/2022 Version: 1.0 SECTION 1: Identification 1.1. Identification Mixture Product form Product name : EPO-TEK® 353ND PART B 1.2. Recommended use and restrictions on use Use of the substance/mixture : adhesives Recommended use adhesives Restrictions on use : Not to be used for any purpose other than the one the product was designed for 1.3. Supplier Epoxy Technology, Inc. 14 Fortune Drive Billerica, MA, 01821 USA T 978-667-3805 www.epotek.com 1.4. Emergency telephone number Emergency number : ChemTel: +1 (800) 255-3924, +1 (813) 248-0585 SECTION 2: Hazard(s) identification 2.1. Classification of the substance or mixture GHS US classification Acute toxicity (oral) Category 4 H302 Harmful if swallowed Skin corrosion/irritation Category 1B H314 Causes severe skin burns and eye damage Serious eye damage/eye irritation Category 1 H318 Causes serious eye damage Skin sensitization, Category 1 H317 May cause an allergic skin reaction Carcinogenicity Category 2 H351 Suspected of causing cancer Reproductive toxicity Category 1B H360 May damage fertility or the unborn child Full text of H statements : see section 16 2.2. GHS Label elements, including precautionary statements GHS US labeling Hazard pictograms (GHS US) Signal word (GHS US) : Dange Hazard statements (GHS US) H302 - Harmful if swallo H314 - Causes severe skin burns and eye damage H317 - May cause an allergic skin reaction H318 - Causes serious eye damage H351 - Suspected of causing cancer H360 - May damage fertility or the unborn child Precautionary statements (GHS US) : P201 - Obtain special instructions before use P202 - Do not handle until all safety precautions have been read and understood. P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

Learn More

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.



Manufacturer:

Epoxy Technology

Product Name: EPO-TEK[®] 353ND High Temperature Epoxy, Heat Cure (2.5g)

Manufacturer Part Number: ET353ND-2.5G

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (2.5g)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse
skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove
contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P310 - Immediately call a poison center or doctor.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P330 - Rinse mouth.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in
accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures Product identifier **GHS US classification** Name % Substituted imidazole* CAS-No.: Trade Acute Tox. 4 (Oral), H302 30 - 60 Secret Skin Irrit. 2, H315 Eve Dam. 1, H318 Skin Sens. 1B, H317 Imidazole CAS-No.: 288-32-4 ≥ 30 Acute Tox. 4 (Oral), H302 Skin Corr. 1C. H314 Eye Dam. 1, H318 Repr. 1B. H360 5 - 10 Acute Tox. 4 (Oral), H302 Substituted imidazole* CAS-No : Trade Secret Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Carc. 2, H351

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer:

Epoxy Technology

Product Name: EPO-TEK[®] 353ND High Temperature Epoxy, Heat Cure (2.5g)

Manufacturer Part Number: ET353ND-2.5G

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (2.5g)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Substituted imidazole*	CAS-No.: Trade Secret	< 5	Acute Tox. 3 (Oral), H301 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Substituted anhydride*	CAS-No.: Trade Secret		Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Comments : Components not listed are either non-hazardous or are below reportable limits

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures		
4.1. Description of first aid measures		
First-aid measures general	: Call a physician immediately.	
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.	
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.	
First-aid measures after eye contact	 Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately. 	
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.	
4.2. Most important symptoms and ef	fects (acute and delayed)	
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.	
Symptoms/effects after eye contact	: Serious damage to eyes.	
Symptoms/effects after ingestion	: Burns.	
4.3. Immediate medical attention and	special treatment, if necessary	

Treat symptomatically.

5.1. Suitable (and unsuitable) extinguishing media		
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.	
5.2. Specific hazards arising from the chemical		
Hazardous decomposition products in case of fir	re : Toxic fumes may be released.	
5.3. Special protective equipment and precautions for fire-fighters		
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.	

6.1.1. For non-emergency personnel

Emergency procedures

: Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer:

Epoxy Technology

Product Name: EPO-TEK[®] 353ND High Temperature Epoxy, Heat Cure (2.5g)

Manufacturer Part Number: ET353ND-2.5G

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (2.5g)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations			
6.1.2. For emergency responders Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".		
6.2. Environmental precautions			
Avoid release to the environment. Notify auth	norities if product enters sewers or public waters.		
6.3. Methods and material for contain	iment and cleaning up		
Methods for cleaning up	: Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.		
Other information	: Dispose of materials or solid residues at an authorized site.		
6.4. Reference to other sections			
For further information refer to section 13.			
SECTION 7: Handling and storage	e		
7.1. Precautions for safe handling			
Precautions for safe handling Hygiene measures	 Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing 		
	before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not		

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store locked up. Store in a well-ventilated place. Keep cool.

eat, drink or smoke when using this product. Always wash hands after handling the product.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
EPO-TEK® 353ND PART B
No additional information available
Substituted imidazole
No additional information available
Imidazole (288-32-4)
No additional information available
Substituted anhydride
No additional information available
Substituted imidazole
No additional information available
Substituted imidazole
No additional information available

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer:

Epoxy Technology

Product Name: EPO-TEK[®] 353ND High Temperature Epoxy, Heat Cure (2.5g)

Manufacturer Part Number: ET353ND-2.5G

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (2.5g)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Appropriate engineering controls

Appropriate engineering controls Environmental exposure controls : Ensure good ventilation of the work station. : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	2	Liquid
Color	÷	amber
Odor	÷	slight
Odor threshold	2	No data available
pH	÷	No data available
Melting point	÷	Not applicable
Freezing point	2	No data available
Boiling point	2	No data available
Flash point	2	No data available
Relative evaporation rate (butyl acetate=1)	2	No data available
Flammability (solid, gas)	2	Not applicable.
Vapor pressure	2	No data available
Relative vapor density at 20 °C	2	No data available
Relative density	2	No data available
Solubility	2	No data available
Partition coefficient n-octanol/water (Log Pow)	2	No data available
Auto-ignition temperature	2	No data available
Decomposition temperature	2	No data available
Viscosity, kinematic	2	No data available
Viscosity, dynamic	2	No data available
Explosion limits	2	No data available
Explosive properties	2	No data available
Oxidizing properties	2	No data available

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer:

Epoxy Technology

Product Name: EPO-TEK[®] 353ND High Temperature Epoxy, Heat Cure (2.5g)

Manufacturer Part Number: ET353ND-2.5G

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (2.5g)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 1	1. Toyloo	logioal in	Formation
SECTION	I. IOXICO	iouical III	Iornation

11.1. Information on toxicological effects			
Acute toxicity (dermal)	Harmful if swallowed. Not classified Not classified		
EPO-TEK® 353ND PART B			
ATE US (oral)	490.339 mg/kg body weight		
Substituted imidazole			
ATE US (oral)	100 mg/kg body weight		
Imidazole (288-32-4)	dazole (288-32-4)		
LD50 oral rat	970 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Experimental value, Oral, 7 day(s))		
ATE US (oral)	960 mg/kg body weight		
Substituted anhydride			
LD50 oral rat	≈ 1144 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other:		
LD50 dermal rabbit	400 – 640 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)		
ATE US (oral)	500 mg/kg body weight		
ATE US (dermal)	400 mg/kg body weight		

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.







Manufacturer:

Epoxy Technology

Product Name: EPO-TEK[®] 353ND High Temperature Epoxy, Heat Cure (2.5g)

Manufacturer Part Number: ET353ND-2.5G

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (2.5g)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Substituted imidazole			
LD50 oral rat	350 mg/kg Source: IUCLID		
LD50 dermal rabbit	440 mg/kg Source: IUCLID		
ATE US (oral)	173 mg/kg body weight		
ATE US (dermal)	440 mg/kg body weight		
Substituted imidazole			
LD50 oral rat	731 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)		
LD50 dermal rabbit	> 400 mg/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Experimental value, Dermal)		
LC50 Inhalation - Rat	> 0.03 mg/l (Equivalent or similar to OECD 403, 8 h, Rat, Male / female, Experimental value, (maximum achievable concentration), Inhalation (vapours))		
ATE US (oral)	731 mg/kg body weight		
Skin corrosion/irritation Serious eye damage/irritation Respiratory or skin sensitization Germ cell mutagenicity Carcinogenicity	Causes severe skin burns. Causes serious eye damage. May cause an allergic skin reaction. Not classified Suspected of causing cancer.		
Substituted imidazole			
IARC group	2B - Possibly carcinogenic to humans		
Reproductive toxicity STOT-single exposure	: May damage fertility or the unborn child. : Not classified		
Substituted imidazole			
STOT-single exposure	May cause respiratory irritation.		
STOT-repeated exposure	: Not classified		
Imidazole (288-32-4)			
NOAEL (oral,rat,90 days)	60 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)		
Substituted anhydride			
NOAEL (oral,rat,90 days)	90 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)		
Substituted imidazole			
NOAEL (oral,rat,90 days)	150 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:EPA OPPTS 870.3650 (Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test)		
Aspiration hazard Viscosity, kinematic Symptoms/effects after skin contact Symptoms/effects after eye contact Symptoms/effects after ingestion	 Not classified No data available Burns. May cause an allergic skin reaction. Serious damage to eyes. Burns. 		

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer: Epoxy Technology

Product Name: EPO-TEK[®] 353ND High Temperature Epoxy, Heat Cure (2.5g)

Manufacturer Part Number: ET353ND-2.5G

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (2.5g)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information			
12.1. Toxicity			
Ecology - general :	Before neutralisation, the product may represent a danger to aquatic organisms.		
Imidazole (288-32-4)			
LC50 - Fish [1]	283.6 mg/l (48 h, Leuciscus idus, Static system, Fresh water, Experimental value, Nominal concentration)		
EC50 - Crustacea [1]	341.5 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)		
ErC50 algae	133 mg/l (DIN 38412: German standard methods for the examination of water, waste water and sludge, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, Nominal concentration)		
NOEC chronic algae	25 mg/l		
Substituted anhydride			
LC50 - Fish [1]	100 – 215 mg/l Test organisms (species): Leuciscus idus		
EC50 - Crustacea [1]	267.94 mg/l Test organisms (species): Daphnia magna		
Substituted imidazole			
LC50 - Fish [1]	0.34 mg/l Source: IUCLID		
EC50 - Crustacea [1]	180 mg/l Source: IUCLID		
Substituted imidazole			
LC50 - Fish [1]	68.1 mg/l (DIN 38412-15, 96 h, Leuciscus idus, Static system, Fresh water, Experimental value)		
EC50 - Crustacea [1]	297.3 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)		
12.2. Persistence and degradability			
Imidazole (288-32-4)			
Persistence and degradability	Readily biodegradable in the soil. Readily biodegradable in water.		
Substituted anhydride			
Persistence and degradability	Not readily biodegradable in water.		
Substituted imidazole			
Persistence and degradability	Inherently biodegradable.		
Biochemical oxygen demand (BOD)	0.000002 g O⊡/g substance		
Chemical oxygen demand (COD)	0.0015 g O⊡/g substance		
Substituted imidazole			
Persistence and degradability	Readily biodegradable in water.		
12.3. Bioaccumulative potential			
Imidazole (288-32-4)			
Partition coefficient n-octanol/water (Log Pow)	-0.02 (Weight of evidence approach, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)		

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer:

Epoxy Technology

Product Name: EPO-TEK[®] 353ND High Temperature Epoxy, Heat Cure (2.5g)

Manufacturer Part Number: ET353ND-2.5G

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (2.5g)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Imidazole (288-32-4)			
Bioaccumulative potential	Not bioaccumulative.		
Substituted anhydride			
Partition coefficient n-octanol/water (Log Pow)	-0.06 Source: ChemIDplus		
Substituted imidazole			
Partition coefficient n-octanol/water (Log Pow)	0.35 (Experimental value)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		
Substituted imidazole			
Partition coefficient n-octanol/water (Log Pow)	1.13 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)		
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).		
12.4. Mobility in soil			
Imidazole (288-32-4)			
Surface tension	No data available in the literature		
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.36 – 2.32 (log Koc, Calculated value)		
Ecology - soil	Low potential for adsorption in soil.		
Substituted anhydride			
Mobility in soil	15.75 Source: Quantitative Structure Activity Relation		
Substituted imidazole			
Mobility in soil	28.23 Source: EPI SUITE		
Ecology - soil	No (test)data on mobility of the substance available.		
Substituted imidazole			
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	3.71 (log Koc, Calculated value, pH = 7)		
Ecology - soil	Low potential for mobility in soil.		
12.5. Other adverse effects			

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods

: Dispose of contents/container in accordance with licensed collector's sorting instructions

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer:

Epoxy Technology

Product Name: EPO-TEK[®] 353ND High Temperature Epoxy, Heat Cure (2.5g)

Manufacturer Part Number: ET353ND-2.5G

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (2.5g)

EPO-TEK® 353ND PART B

Safety Data Sheet

14.1. UN number	
DOT NA No UN-No. (TDG) UN-No. (IMDG) UN-No. (IATA)	: UN3267 : UN3267 : 3267 : 3267
14.2. UN proper shipping name	
Proper Shipping Name (DOT) Proper Shipping Name (TDG) Proper Shipping Name (IMDG) Proper Shipping Name (IATA)	Corrosive liquid, basic, organic, n.o.s. (CONTAINS Imidazole) CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (CONTAINS Imidazole) CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (CONTAINS Imidazole) Corrosive liquid, basic, organic, n.o.s. (CONTAINS Imidazole)
14.3. Transport hazard class(es)	
DOT Transport hazard class(es) (DOT) Hazard labels (DOT)	: 8 : 8
TDG Transport hazard class(es) (TDG) Hazard labels (TDG)	
IMDG Transport hazard class(es) (IMDG) Hazard labels (IMDG)	
IATA Transport hazard class(es) (IATA) Hazard labels (IATA)	: 8 : 8
14.4. Packing group	▼
Packing group (DOT) Packing group (TDG) Packing group (IMDG) Packing group (IATA)	: III : III : III : III

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer:

Epoxy Technology

Product Name: EPO-TEK[®] 353ND High Temperature Epoxy, Heat Cure (2.5g)

Manufacturer Part Number: ET353ND-2.5G

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (2.5g)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.5. Environmental hazards		
Other information	: No supplementary information available.	
14.6. Special precautions for user		
DOT	. 1910007	
UN-No.(DOT) DOT Special Provisions (49 CFR 172.102)	 UN3267 IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31H21 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T7 - 4 178.274(d)(2) Normal	
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154	
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203	
DOT Packaging Bulk (49 CFR 173.xxx)	: 241	
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)		
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L	
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.	
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters",52 - Stow "separated from" acids	
TDG		
UN-No. (TDG)	: UN3267	
TDG Special Provisions	 16 - (1) The technical name of at least one of the most dangerous substances that predominanti contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (a) UN244, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or 	
	(b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS.	
Explosive Limit and Limited Quantity Index	: 5L	
Excepted quantities (TDG) Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: E1 : 5L	

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer:

Epoxy Technology

Product Name: EPO-TEK[®] 353ND High Temperature Epoxy, Heat Cure (2.5g)

Manufacturer Part Number: ET353ND-2.5G

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (2.5g)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

IMDG	
Special provision (IMDG)	: 223, 274
Limited quantities (IMDG)	: 5L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: 17
Tank special provisions (IMDG)	: TP1, TP28
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Reacts violently with acids. Causes burns to skin, eyes and mucous membranes.
IATA	
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y841
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 852
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 856
CAO max net quantity (IATA)	: 60L
Special provision (IATA)	: A3, A803
ERG code (IATA)	: 8L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

Substituted imidazole Listed on the Canadian DSL (Domestic Substances List)

Imidazole (288-32-4)

Listed on the Canadian DSL (Domestic Substances List)

Substituted anhydride Listed on the Canadian DSL (Domestic Substances List)

Substituted imidazole

Listed on the Canadian NDSL (Non-Domestic Substances List)

Substituted imidazole

Listed on the Canadian DSL (Domestic Substances List)

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer: Epoxy Technology

Product Name:

EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (2.5g)

Manufacturer Part Number: ET353ND-2.5G

Click here for more details on the EPO-TEK® 353ND High Temperature Epoxy, Heat Cure (2.5g)

EPO-TEK® 353ND PART B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

No additional information available

National regulations

Imidazole (288-32-4)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Substituted anhydride

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Substituted imidazole

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

WARNING:

This product can expose you to Substituted imidazole, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H301	Toxic if swallowed
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H360	May damage fertility or the unborn child

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.



