



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 353NDP High Temperature Epoxy, Humidity Resistant,
Low Outgassing, Heat Cure (4g)

Manufacturer Part Number:
ET353NDP-4G



▶ Click here for more details on the EPO-TEK® 353NDP High Temperature Epoxy, Humidity Resistant, Low Outgassing, Heat Cure (4g)

EPOXY TECHNOLOGY EPO-TEK® 353NDP High Temperature Humidity Resistant Epoxy Preliminary Product Information Sheet

Date: November 2025
Rev: IV
No. of Components: Two
Mix Ratio by Weight: 10 : 1
Specific Gravity: Bulk – Part A: 1.20, Part B: 1.02
Syringe: 1.18
Pot Life: Bulk: ≤3 Hours, Syringe: ≤2 Hours
Shelf Life- Bulk: One year at room temperature

Shelf Life- Syringe: Six months at -40°C
Recommended Cure: 120°C / 1 Hour
Alternative Cure(s): May not achieve performance properties below
150°C / 1 Minute
120°C / 5 Minutes
100°C / 10 Minutes
80°C / 30 Minutes

Product Description:

EPO-TEK® 353NDP is a two component, high temperature and high humidity resistance epoxy designed for optical, telecom, datacom, HI-REL microelectronics, semiconductor and hybrid applications. Also available in single component frozen syringe.

Typical Properties:

Cure condition: 120°C / 1 Hour

Different batches, conditions, and applications yield differing results.

Data contained herein is preliminary and subject to change without notice. To be used as guide only, not as a specification.

*denotes test on lot acceptance basis.

Notes:

- Container(s) should be kept closed when not in use.
- Performance properties (rheology, conductivity, others) of the product may vary from those stated on the data sheet when bi-pak/syringe packaging or post-processing of any kind is performed. Epoxy's warranties shall not apply to any products that have been reprocessed or repackaged from Epoxy's delivered status/container into any other containers of any kind, including but not limited to syringes, bi-paks, cartridges, pouches, tubes, capsules, films or other packages.
- Syringe packaging will impact initial viscosity and effective pot life, potentially beyond stated parameters.
- If product crystallizes in storage, place container in warm oven until crystallization disappears. Please refer to Tech Tip #7 on website.
- TOTAL MASS MIXED SHOULD NOT EXCEED 25 GRAMS

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice. FOC last update 6/11/2026.



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 353NDP High Temperature Epoxy, Humidity Resistant,
Low Outgassing, Heat Cure (4g)

Manufacturer Part Number:
ET353NDP-4G

▶ Click here for more details on the EPO-TEK® 353NDP High Temperature Epoxy, Humidity Resistant, Low Outgassing, Heat Cure (4g)

Physical Properties	Details
* Color (before cure)	Part A: Clear, Part B: Amber
* Consistency	Pourable liquid
* Viscosity (23°C) @ 50 rpm	3,600 cPs
Thixotropic Index	N/A
* Glass Transition Temp	≥ 90°C (Dynamic Cure: 20-200°C/ISO 25 Min; Ramp -10-200°C @20°C/Min)
Coefficient of Thermal Expansion (CTE)	Below Tg: 52 x 10 ⁻⁶ in/in°C, Above Tg: 185 x 10 ⁻⁶ in/in°C
Shore D Hardness	85
Lap Shear @ 23°C	> 2000 psi
Die Shear @ 23°C	38 Kg; 32 Kg (after 7d @ 85°C / 85% RH); 15 Kg (after 2000h @ 85°C / 85% RH)
Degradation Temp	410°C
Weight Loss:	@ 200°C: 0.09%, @ 250°C: 0.28%, @ 300°C: 0.72%
Suggested Operating Temperature	< 350°C (Intermittent)
Storage Modulus:	2213 MPa @ 23°C
Ion Content	Pending
*Particle Size	N/A

Electrical & Thermal Properties	Details
Thermal Conductivity	N/A
Volume Resistivity @ 23°C	≥ 1.8 x 10 ¹³ Ohm-cm
Dielectric Constant (1KHz)	3.17
Dissipation Factor (1KHz)	0.005

Optical Properties @23°C	Details
Spectral Transmission:	≥ 50% @ 550 nm ≥ 95% @ 1100-1600 nm ≥ 98% @ 800-1000 nm
Refractive Index:	1.569 @589 nm

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice. FOC last update 6/11/2026.



Manufacturer:
Epoxy Technology

Product Name:
EPO-TEK® 353NDP High Temperature Epoxy, Humidity Resistant,
Low Outgassing, Heat Cure (4g)

Manufacturer Part Number:
ET353NDP-4G



▶ [Click here for more details on the EPO-TEK® 353NDP High Temperature Epoxy, Humidity Resistant, Low Outgassing, Heat Cure \(4g\)](#)

EPO-TEK® 353NDP Advantages & Suggested Application Notes

- Reasonable pot-life that allows for low temperature curing to be realized. It has an amber color change upon cure.
- Passes NASA low outgassing standard ASTM E595 with proper cure.
- Semiconductor suggested applications: wafer-wafer bonding of CSP; fabrication of MEMs devices; flip chip underfill.
- Hybrid suggested applications: providing near hermetic seals and UHV seals in sensor devices, resisting high temperature packaging.
 - Down-Hole petrochemical fiber optic sensors, resisting >200°C field conditions.
 - HI-REL microelectronics assembly for automotive electronics, autonomous, aviation, and defense
- Optical, telecom, and datacom suggested applications:
 - Sealing fiber into ferrules, transmitting light in the optical pathway from 800- 1550 nm range.
 - High speed data transceiver device adhesive for active alignment of optics, environmental sealing of opto-package, V-groove arrays.
- Electronics Assembly suggested applications:
 - Used as dielectric layer in the fabrication of capacitors; laminating PZT ferroelectrics found in ultrasound or ink-jetting devices.
 - Impregnating and insulating copper coil windings in motors and inductor coils. Bonding ferrite cores and magnets.
 - Structural bonding of stainless steel, metals, Kapton®, and magnets.
- Special handling considerations:
 - Container(s) should be kept fully closed when not in use.
 - If stored before use at refrigerated conditions, container(s) should be kept fully closed until material is fully thawed or at room temperature.

SELLER MAKES NO OTHER WARRANTY OR GUARANTEE OF ANY KIND REGARDING FITNESS OF THE PRODUCT FOR A PARTICULAR PURPOSE.
BUYER ASSUMES FULL RESPONSIBILITY FOR QUALITY CONTROL, TESTING AND DETERMINATION OF SUITABILITY OF PRODUCT FOR ITS INTENDED APPLICATION OR USE.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are
subject to change without notice.
FOC last update 6/11/2026.