

### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (8oz)

### **Manufacturer Part Number:**

ET353NDTBLK-8OZ

Revision date: 6/8/2020 Revision: 3 Supersedes date: 11/21/2016

Click here for more details on the EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (8oz)



### SAFETY DATA SHEET EPO-TEK® 353ND-T Black Part A

1. Identification

Product identifier

Product name EPO-TEK® 353ND-T Black Part A

Product number 353ND-T Black/A

Recommended use of the chemical and restrictions on use

Application Adhesive.

Use only for intended applications.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.

14 Fortune Drive Billerica, MA 01821 USA

(978) 667-3805 (978) 663-9782

www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone ChemTel: +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Skin Sens. 1 - H317 STOT SE 1 - H370

Environmental hazards Aquatic Chronic 2 - H411

Label elements

Hazard symbols







Danger

Signal word

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H370 Causes damage to organs . H411 Toxic to aquatic life with long lasting effects.

Data is subject to change without notice.





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (8oz)

### **Manufacturer Part Number:**

ET353NDTBLK-8OZ

Revision date: 6/8/2020 Revision: 3 Supersedes date: 11/21/2016

Click here for more details on the EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (8oz)

### EPO-TEK® 353ND-T Black Part A

Precautionary statements P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 If on skin: Wash with plenty of water.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

60-100%

lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337+P313 If eye irritation persists: Get medical advice/ attention.
P501 Dispose of contents/ container in accordance with national regulations.

#### Other hazards

Harmful dust may be released during cutting or grinding process.

Hazards not otherwise classified (HNOC) Contains epoxy constituents. May produce an allergic reaction.

### 3. Composition/information on ingredients

#### Mixtures

Epoxy Phenol Novolac

CAS number: 9003-36-5

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2A - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

Polar Activator 1-5%

CAS number: Proprietary

Classification

Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311

Acute Tox. 3 - H331 STOT SE 1 - H370

The full text for all hazard statements is displayed in Section 16.

Ingredient notes The exact identity is withheld as a trade secret in accordance with 29 CFR 1910.1200. The

exact percentage/concentration is withheld as a trade secret in accordance with 29 CFR

1910.1200.

### 4. First-aid measures

Eye contact

### Description of first aid measures

Inhalation Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical

attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse

mouth thoroughly with water. Get medical attention if any discomfort continues.

Skin Contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

Data is subject to change without notice.



Click here for more details on the EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (8oz)



### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (8oz)

### **Manufacturer Part Number:**

ET353NDTBLK-8OZ

Revision date: 6/8/2020 Revision: 3 Supersedes date: 11/21/2016 EPO-TEK® 353ND-T Black Part A Most important symptoms and effects, both acute and delayed General information Causes damage to organs. Inhalation Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract. Gas or vapor in high concentrations may irritate the respiratory system. Ingestion May cause discomfort if swallowed. Skin contact Causes skin irritation. May cause an allergic skin reaction. May cause sensitisation by skin contact. Eve contact Causes serious eve irritation Indication of immediate medical attention and special treatment needed Notes for the doctor Treat symptomatically. 5. Fire-fighting measures Extinguishing media Suitable extinguishing media Extinguish with the following media: Dry chemicals. Foam. Carbon dioxide (CO2). Special hazards arising from the substance or mixture Hazardous combustion Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or products vapors. Advice for firefighters Protective actions during Avoid breathing fire gases or vapors. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. firefiahtina Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective for firefighters clothing. 6. Accidental release measures Personal precautions, protective equipment and emergency procedures Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. **Environmental precautions** Environmental precautions Do not discharge into drains or watercourses or onto the ground. Avoid release to the environment Methods and material for containment and cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into Methods for cleaning up containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses Reference to other sections For personal protection, see Section 8. 7. Handling and storage Precautions for safe handling

Handle all packages and containers carefully to minimize spills. Avoid inhalation of vapors and

contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety

Data is subject to change without notice.



### Contact the professionals at Fiber Optic Center for a quote or to get more details.

data sheet

Usage precautions



### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (8oz)

Supersedes date: 11/21/2016

### **Manufacturer Part Number:**

ET353NDTBLK-8OZ

Click here for more details on the EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (8oz)

### EPO-TEK® 353ND-T Black Part A

Advice on general Do not eat, drink or smoke when using this product. Wash promptly if skin becomes occupational hygiene contaminated. Wash hands thoroughly after handling. Wash contaminated clothing before

reuse

Conditions for safe storage, including any incompatibilities

Storage precautions Store at room temperature. Keep container tightly sealed when not in use.

Storage class Chemical storage.

Specific end uses(s)

Revision date: 6/8/2020

Specific end use(s) The identified uses for this product are detailed in Section 1.

#### 8. Exposure controls/Personal protection

### Control parameters

Occupational exposure limits

Polar Activator

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm Short-term exposure limit (15-minute): ACGIH 250 ppm

ACGIH = American Conference of Governmental Industrial Hygienists.

### Exposure controls





Appropriate engineering

Provide adequate general and local exhaust ventilation

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

Wear protective gloves made of the following material: Nitrile rubber. Neoprene. Butyl rubber.

Other skin and body

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes

contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat,

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

### 9. Physical and chemical properties

### Information on basic physical and chemical properties

Appearance Paste. Color Black Mild Odor

Odor threshold No specific test data are available. рΗ No specific test data are available. Melting point No specific test data are available. Initial boiling point and range No specific test data are available.

Data is subject to change without notice.





# Manufacturer:

**Epoxy Technology** 

# **Product Name:**

EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (8oz)

# **Manufacturer Part Number:**

ET353NDTBLK-8OZ

Click here for more details on the EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (80z)

Revision date: 6/8/2020	Revision: 3 Supersedes date: 11/21/2016
	EPO-TEK® 353ND-T Black Part A
Flash point	>93°C
Evaporation rate	<buac< td=""></buac<>
Evaporation factor	No specific test data are available.
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	No specific test data are available.
Vapor pressure	No specific test data are available.
Vapor density	>1
Relative density	No specific test data are available.
Bulk density	No specific test data are available.
Solubility(ies)	Slightly soluble in water.
Partition coefficient	No specific test data are available.
Auto-ignition temperature	No specific test data are available.
Decomposition Temperature	No specific test data are available.
Viscosity	No specific test data are available.
Other information	None.
10. Stability and reactivity	
Reactivity	The following materials may react with the product: Strong oxidizing agents. Strong reducing agents.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	Will not polymerize.
Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid contact with the following materials Oxidizing agents. Reducing agents. Avoid heat, flames and other sources of ignition.
Materials to avoid	Strong oxidizing agents. Strong reducing agents.
Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO2).
11. Toxicological information	
Information on toxicological eff	ects
Acute toxicity - oral	3,045.89
Acute toxicity - oral ATE oral (mg/kg) Acute toxicity - dermal	3,045.89 9,137.67
Acute toxicity - oral ATE oral (mg/kg) Acute toxicity - dermal ATE dermal (mg/kg) Acute toxicity - inhalation	
Acute toxicity - oral ATE oral (mg/kg) Acute toxicity - dermal ATE dermal (mg/kg) Acute toxicity - inhalation ATE inhalation (gases ppm) ATE inhalation (vapours mg/l)	9,137.67 21,321.22





Data is subject to change without notice.



# Manufacturer:

**Epoxy Technology** 

# **Product Name:**

EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (8oz)

# **Manufacturer Part Number:**

ET353NDTBLK-8OZ

Click here for more details on the EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (80z)

Revision date: 6/8/2020	Revision: 3	Supersedes date: 11/21/2016
	EPO-TEK® 353ND-T Black Part A	
ATE inhalation (dusts/mists mg/l)	15.23	
Inhalation	Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract. Gas or vapor in high concentrations may irritate the respiratory system.	
Ingestion	May cause discomfort if swallowed.	
Skin Contact	Causes skin irritation. May cause an allergic skin reaction. Ma contact.	ay cause sensitisation by skin
Eye contact	Causes serious eye irritation.	
Acute and chronic health hazards	Causes damage to organs .	
12. Ecological information		
Ecotoxicity	Toxic to aquatic organisms, may cause long-term adverse eff	ects in the aquatic environment.
Acute aquatic toxicity Acute toxicity - fish	Not available.	
Persistence and degradability		
Persistence and degradability	No data available.	
Bioaccumulative potential		
Bio-Accumulative Potential	No data available on bioaccumulation.	
Partition coefficient	No specific test data are available.	
Mobility in soil		
Mobility	The product has poor water-solubility.	
Other adverse effects		
Other adverse effects	Not known.	
13. Disposal considerations		
Waste treatment methods Disposal methods	Dispose of waste to licensed waste disposal site in accordance local Waste Disposal Authority.	ce with the requirements of the
14. Transport information		
UN Number		
UN No. (TDG)	3082	
UN No. (IMDG)	3082	
UN No. (ICAO)	3082	
UN No. (DOT)	UN3082	
UN proper shipping name		
Proper shipping name (TDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, Phenol Novolac)	N.O.S. (CONTAINS Epoxy

Contact the professionals at Fiber Optic Center for a quote or to get more details.



Data is subject to change without notice.



# **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (8oz)

### **Manufacturer Part Number:**

ET353NDTBLK-8OZ

Click here for more details on the EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (80z)

Revision date: 6/8/2020 Revision: 3 Supersedes date: 11/21/2016 EPO-TEK® 353ND-T Black Part A Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Phenol Novolac) Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Proper shipping name (DOT) ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Epoxy Phenol Novolac) Transport hazard class(es) DOT hazard class DOT hazard label TDG class TDG label(s) IMDG Class ICAO class/division Transport labels ЛIII DOT transport labels Allh Packing group TDG Packing Group IMDG packing group ICAO packing group DOT packing group Environmental hazards Environmentally Hazardous Substance Special precautions for user F-A, S-F EmS Transport in bulk according to Not applicable Annex II of MARPOL 73/78 and the IBC Code 15. Regulatory information Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of Regulatory References

Data is subject to change without notice.



Intellectual Property Rights (TRIPS), Section 7, Art. 39.



### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (8oz)

### **Manufacturer Part Number:**

ET353NDTBLK-8OZ

Click here for more details on the EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (8oz)

Revision date: 6/8/2020 Revision: 3 Supersedes date: 11/21/2016

### EPO-TEK® 353ND-T Black Part A

### **US Federal Regulations**

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed:

Polar Activator

5,000 lbs (2270 Kg)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed.

SARA 313 Emission Reporting

The following ingredients are listed:

Polar Activator

**CAA Accidental Release Prevention** 

None of the ingredients are listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are listed.

### **US State Regulations**

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed:

Polar Activator

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed.

Massachusetts "Right To Know" List

The following ingredients are listed:

Polar Activator

Rhode Island "Right To Know" List

The following ingredients are listed:

Polar Activator

Minnesota "Right To Know" List

The following ingredients are listed:

Polar Activator

New Jersey "Right To Know" List

The following ingredients are listed:

Polar Activator

Pennsylvania "Right To Know" List

The following ingredients are listed:

Polar Activator

Data is subject to change without notice.





# **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (8oz)

Supersedes date: 11/21/2016

### **Manufacturer Part Number:**

ET353NDTBLK-8OZ

Click here for more details on the EPO-TEK® 353NDT Thixotropic High Temperature Black Epoxy, Heat Cure (8oz)

Revision: 3

### EPO-TEK® 353ND-T Black Part A

#### Inventories

EU - EINECS/ELINCS

Revision date: 6/8/2020

Some of the ingredients are listed or exempt

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification None of the ingredients are listed.

Australia - AICS

All the ingredients are listed or exempt.

Japan - ENCS

Some of the ingredients are listed or exempt.

Korea - KFCI

All the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

All the ingredients are listed or exempt.

### 16. Other information

Revision date 6/8/2020 Revision 3 Supersedes date 11/21/2016

Hazard statements in full H225 Highly flammable liquid and vapor.

> H301 Toxic if swallowed. H311 Toxic in contact with skin. H315 Causes skin irritation H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H370 Causes damage to organs.

H411 Toxic to aquatic life with long lasting effects.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Data is subject to change without notice.

