

Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Manufacturer Part Number:

ETHYB-353ND-HV-3CC

Click here for

▶ Click here for more details on the EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Revision date: 11/7/2016

Revision: 1



SAFETY DATA SHEET EPO-TEK HYB-353ND-HV PMF Syringe

1. Identification

Product identifier

Product name EPO-TEK HYB-353ND-HV PMF Syringe

Product number HYB-353ND-HV

Recommended use of the chemical and restrictions on use

Application Adhesive.

Details of the supplier of the safety data sheet

Supplier Epoxy Technology, Inc.

14 Fortune Drive Billerica, MA 01821

USA (978) 667-3805 (978) 663-9782

www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone +1 (800) 255-3924, +1 (813) 248-0585

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Repr. 1B - H360

Environmental hazards Aquatic Chronic 2 - H411

Label elements

Pictogram









Signal word

Danger

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H360 May damage fertility or the unborn child. H411 Toxic to aquatic life with long lasting effects

1/9



Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure -Pre-Mixed and Frozen (3cc Syringe)

Manufacturer Part Number:

ETHYB-353ND-HV-3CC

Click here for more details on the EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Revision date: 11/7/2016

EPO-TEK HYB-353ND-HV PMF Syringe

Precautionary statements P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 If on skin: Wash with plenty of water

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact

30-60%

30-60%

1-5%

1-5%

lenses, if present and easy to do. Continue rinsing.

P308+P313 If exposed or concerned: Get medical advice/ attention. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention P501 Dispose of contents/ container in accordance with national regulations.

Contains Specialty Acrylate Blend, Substituted Imidazole Blend, Imidazole

Other hazards

3. Composition/information on ingredients

Mixtures

Epoxy Phenol Novolac CAS number: 9003-36-5

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

Specialty Acrylate Blend

CAS number: Proprietary

Classification

Skin Sens. 1 - H317 Aquatic Chronic 3 - H412

Substituted Imidazole Blend

CAS number: Proprietary

Classification

Acute Tox 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318

Imidazole

CAS number: 288-32-4

Classification

Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eve Dam 1 - H318 Repr. 1B - H360

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

2/9





Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure -Pre-Mixed and Frozen (3cc Syringe)

Manufacturer Part Number:

ETHYB-353ND-HV-3CC

Click here for more details on the EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Revision date: 11/7/2016 Revision: 1

EPO-TEK HYB-353ND-HV PMF Syringe

Inhalation Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical

attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting, Rinse

Remove affected person from source of contamination. Remove contaminated clothing. Wash

mouth thoroughly with water. Get medical attention if any discomfort continues

Skin Contact skin thoroughly with soap and water. Get medical attention if any discomfort continues

Remove affected person from source of contamination. Remove any contact lenses and open

eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

Most important symptoms and effects, both acute and delayed

General information May damage fertility or the unborn child.

Gas or vapor in high concentrations may irritate the respiratory system. Inhalation of dust

during cutting, grinding or sanding operations involving this product may cause irritation of the

respiratory tract

Ingestion May cause discomfort if swallowed.

Skin contact Causes skin irritation. May cause sensitisation by skin contact.

Eve contact Causes serious eve damage.

Indication of immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically

5. Fire-fighting measures

Extinguishing media

Eye contact

Suitable extinguishing media Dry chemicals. Foam. Carbon dioxide (CO2).

Special hazards arising from the substance or mixture

Thermal decomposition or combustion products may include the following substances: Hazardous combustion

Carbon dioxide (CO2). Carbon monoxide (CO).

Advice for firefighters

Protective actions during Avoid breathing fire gases or vapors. Use water to keep fire exposed containers cool and

firefighting disperse vapors.

Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective clothing as described in Section 8 of this safety data sheet. Keep Personal precautions

unnecessary and unprotected personnel away from the spilage. Avoid contact with skin and

Environmental precautions

Environmental precautions Avoid discharge to the aquatic environment.

Methods and material for containment and cleaning up

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into Methods for cleaning up

containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering

drains, sewers or watercourses





Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Manufacturer Part Number:

ETHYB-353ND-HV-3CC

▶ Click here for more details on the EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Revision date: 11/7/2016

Revision: 1

EPO-TEK HYB-353ND-HV PMF Syringe

Reference to other sections For personal protection, see Section 8.

7. Handling and storage

Precautions for safe handling

Usage precautions

Handle all packages and containers carefully to minimize spills. Avoid contact with skin and

eyes. Wear protective clothing as described in Section 8 of this safety data sheet.

Advice on general occupational hygiene

Provide eyewash station. Do not eat, drink or smoke when using this product. Wash promptly with soap and water if skin becomes contaminated. Wash after use and before eating,

smoking and using the toilet. Wash contaminated clothing before reuse. Use appropriate skin

cream to prevent drying of skin.

Conditions for safe storage, including any incompatibilities

Storage precautions Store at -40 degrees C. Keep container tightly sealed when not in use.

Storage class Chemical storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2

8. Exposure Controls/personal protection

Control parameters

Ingredient comments

No exposure limits known for ingredient(s)

Exposure controls





Appropriate engineering

Provide adequate general and local exhaust ventilation. Avoid inhalation of vapors.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

Other skin and body

It is recommended that chemical-resistant, impervious gloves are worn.

Wear appropriate clothing to prevent any possibility of skin contact.

protection

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do

not eat, drink or smoke.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Liquid.

Color Colorless to pale yellow

Flash point > 93°C
Evaporation rate < BuAc

4/9





Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure -Pre-Mixed and Frozen (3cc Syringe)

Manufacturer Part Number:

ETHYB-353ND-HV-3CC

Click here for more details on the EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Revision date: 11/7/2016

Revision: 1

EPO-TEK HYB-353ND-HV PMF Syringe

Vapor density > Air

Solubility(ies) Slightly soluble in water.

Other information None

10. Stability and reactivity

Reactivity The following materials may react with the product: Strong oxidizing agents. Strong reducing

Stability Stable at normal ambient temperatures and when used as recommended.

Possibility of hazardous

reactions

May polymerize.

Conditions to avoid Avoid excessive heat for prolonged periods of time.

Materials to avoid Strong oxidizing agents. Strong reducing agents.

Hazardous decomposition Thermal decomposition or combustion products may include the following substances: products

Carbon monoxide (CO). Carbon dioxide (CO2).

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 11,007.41

General information Possible risk of adverse reproductive effects

Inhalation May cause respiratory irritation. Inhalation of dust during cutting, grinding or sanding

operations involving this product may cause irritation of the respiratory tract

Ingestion May cause discomfort if swallowed.

Skin Contact Causes skin irritation. May cause sensitisation by skin contact.

Eve contact Causes serious eve damage.

12. Ecological Information

Ecotoxicity Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity

Acute toxicity - fish Not available

Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Bioaccumulative potential

No data available on bioaccumulation. Bio-Accumulative Potential

Mobility in soil

Mobility No data available

Results of PBT and vPvB assessment

5/9





Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure -Pre-Mixed and Frozen (3cc Syringe)

Manufacturer Part Number:

ETHYB-353ND-HV-3CC

Click here for more details on the EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Revision date: 11/7/2016

EPO-TEK HYB-353ND-HV PMF Syringe

Other adverse effects	
Other adverse effects	Not known.
13. Disposal considerations	
Waste treatment methods	
General information	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
14. Transport information	
UN Number	
UN No. (TDG)	3082
UN No. (IMDG)	3082
UN No. (ICAO)	3082
UN No. (DOT)	UN3082
UN proper shipping name	
Proper shipping name (TDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Phenol Novolac)
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Phenol Novolac)
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Phenol Novolac)
Proper shipping name (DOT)	${\bf ENVIRONMENTALLY\ HAZARDOUS\ SUBSTANCES,\ LIQUID,\ N.O.S.\ (CONTAINS\ Epoxy\ Phenol\ Novolac)}$
Transport hazard class(es)	
DOT hazard class	9
DOT hazard label	9
TDG class	9
TDG label(s)	9
IMDG Class	9
ICAO class/division	9
Transport labels	
DOT transport labels	
Packing group	
Packing group TDG Packing Group	III

6/9





Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure -Pre-Mixed and Frozen (3cc Syringe)

Manufacturer Part Number:

ETHYB-353ND-HV-3CC

Click here for more details on the EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Revision date: 11/7/2016

Revision: 1

EPO-TEK HYB-353ND-HV PMF Syringe

ICAO packing group DOT packing group Ш

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

F-A, S-F **EmS**

Transport in bulk according to Not applicable Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

Regulatory References

Proprietary information protected pursuant to WTO's Agreement on Trade-Related Aspects of

Intellectual Property Rights (TRIPS), Section 7, Art. 39.

International Regulations

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are required to be listed.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

None of the ingredients are required to be listed.

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are required to be listed.

SARA 313 Emission Reporting

None of the ingredients are required to be listed.

CAA Accidental Release Prevention

None of the ingredients are required to be listed.

OSHA Highly Hazardous Chemicals

None of the ingredients are required to be listed.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are required to be listed.

California Air Toxics "Hot Spots" (A-I)

None of the ingredients are required to be listed.

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are required to be listed.

Massachusetts "Right To Know" List

None of the ingredients are required to be listed.

7/9





Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Manufacturer Part Number:

ETHYB-353ND-HV-3CC

Click here for more details on the EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Revision date: 11/7/2016

Revision: 1

EPO-TEK HYB-353ND-HV PMF Syringe

Rhode Island "Right To Know" List

None of the ingredients are required to be listed.

Minnesota "Right To Know" List

None of the ingredients are required to be listed.

New Jersey "Right To Know" List

None of the ingredients are required to be listed.

Pennsylvania "Right To Know" List

None of the ingredients are required to be listed.

Inventories

EU - EINECS/ELINCS

Some of the ingredients are listed or exempt.

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

Australia - AICS

All the ingredients are listed or exempt.

Japan - MITI

Some of the ingredients are listed or exempt.

Korea - KECI

Some of the ingredients are listed or exempt.

China - IECSC

All the ingredients are listed or exempt.

Philippines - PICCS

Some of the ingredients are listed or exempt.

16. Other information

 Revision date
 11/7/2016

 Revision
 1

Hazard statements in full H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation.

H360 May damage fertility or the unborn child. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

8/9





Manufacturer:

Epoxy Technology

Product Name:

EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure -Pre-Mixed and Frozen (3cc Syringe)

Manufacturer Part Number:

ETHYB-353ND-HV-3CC

Click here for more details on the EPO-TEK® HYB-353ND-HV High Temperature Epoxy, Hybrid Heat & UV Cure - Pre-Mixed and Frozen (3cc Syringe)

Revision date: 11/7/2016

EPO-TEK HYB-353ND-HV PMF Syringe

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

