

# **Manufacturer:**

**Epoxy Technology** 

#### **Product Name:**

EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

## **Manufacturer Part Number:**

ETOE138-4G

Click here for more details on the EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

Revision date: 3/24/2017 Revision: 2 Supersedes date: 2/24/2015



#### SAFETY DATA SHEET EPO-TEK OE138 Part A

1. Identification

Product identifier

Product name EPO-TEK OE138 Part A

Product number OE138/A

Recommended use of the chemical and restrictions on use

Application Adhesive.

Details of the supplier of the safety data sheet

Supplier

Epoxy Technology, Inc. 14 Fortune Drive Billerica, MA 01821 USA (978) 667-3805 (978) 663-9782

www.epotek.com, SDS@epotek.com

Emergency telephone number

Emergency telephone +1 (800) 255-3924, +1 (813) 248-0585

#### 2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 1 - H370

Environmental hazards Aquatic Chronic 2 - H411

Label elements

Pictogram







Signal word

Danger

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H370 Causes damage to organs.

H411 Toxic to aquatic life with long lasting effects.







# Manufacturer:

**Epoxy Technology** 

#### **Product Name:**

EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

#### **Manufacturer Part Number:**

ETOE138-4G

Click here for more details on the EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

Revision date: 3/24/2017 Revision: 2 Supersedes date: 2/24/2015 **EPO-TEK OE138 Part A** Precautionary statements P260 Do not breathe vapor/ spray. P261 Avoid breathing vapor/ spray. P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product P272 Contaminated work clothing must not be allowed out of the workplace P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 If on skin: Wash with plenty of water P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P311 If exposed or concerned: Call a poison center or doctor. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse P391 Collect spillage. P405 Store locked up. P501 Dispose of contents/ container in accordance with national regulations. Contains Epoxy Phenol Novolac, Polar Activator Other hazards Harmful dust may be released during cutting or grinding process. Contains epoxy constituents. May produce an allergic reaction. classified (HNOC) 3. Composition/information on ingredients **Epoxy Phenol Novolac** 60-100% CAS number: 9003-36-5 Classification Skin Irrit. 2 - H315 Eve Irrit 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411 Polar Activator 1-5% CAS number: Proprietary Classification Flam. Lig. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370 The full text for all hazard statements is displayed in Section 16. 4. First-aid measures Description of first aid measures





## Manufacturer:

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

## **Manufacturer Part Number:**

ETOE138-4G

Click here for more details on the EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

Revision date: 3/24/2017	Revision: 2	Supersedes date: 2/24/2015
	EPO-TEK OE 138 Part A	
Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.	
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.	
Skin Contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.	
Eye contact	Remove affected person from source of contamination. Re eyelids wide apart. Continue to rinse for at least 15 minutes	
Most important symptoms and	effects, both acute and delayed	
General information	Causes damage to organs .	
Inhalation	Inhalation of dust during cutting, grinding or sanding open cause irritation of the respiratory tract. Gas or vapor in hig respiratory system.	
Ingestion	May cause discomfort if swallowed.	
Skin contact	Skin irritation. Allergic rash.	
Eye contact	Irritating to eyes. Symptoms following overexposure may i Pain.	nclude the following: Redness.
Indication of immediate medic	al attention and special treatment needed	
Notes for the doctor	Treat symptomatically.	
5. Fire-fighting measures		
Extinguishing media		
Suitable extinguishing media	Extinguish with the following media: Dry chemicals. Foam.	. Carbon dioxide (CO2).
Special hazards arising from the	he substance or mixture	
Hazardous combustion products	Thermal decomposition or combustion may liberate carbo vapors.	n oxides and other toxic gases or
Advice for firefighters		
Protective actions during firefighting	Avoid breathing fire gases or vapors. Cool containers exporemove them from the fire area if it can be done without ri	
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus clothing.	s (SCBA) and appropriate protective
6. Accidental release measure	us .	
Personal precautions, protecti	ve equipment and emergency procedures	
Personal precautions	Wear protective clothing as described in Section 8 of this s	safety data sheet.
•	Wear protective clothing as described in Section 8 of this s	safety data sheet.
Environmental precautions	Wear protective clothing as described in Section 8 of this some section 8 of this some section 8 of this some section 8 of this sec	
Personal precautions  Environmental precautions  Environmental precautions  Methods and material for cont	Do not discharge into drains or watercourses or onto the genvironment.	

 ${\it Data is subject to change without notice}.$ 



## Contact the professionals at Fiber Optic Center for a quote or to get more details.



#### **Manufacturer:**

**Epoxy Technology** 

#### **Product Name:**

EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

#### **Manufacturer Part Number:**

ETOE138-4G

Click here for more details on the EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

Revision date: 3/24/2017 Revision: 2 Supersedes date: 2/24/2015 **EPO-TEK OE138 Part A** Reference to other sections For personal protection, see Section 8. 7. Handling and storage Precautions for safe handling Usage precautions Handle all packages and containers carefully to minimize spills. Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet Advice on general Do not eat, drink or smoke when using this product. Wash promptly with soap and water if occupational hygiene skin becomes contaminated. Wash after use and before eating, smoking and using the toilet. Wash contaminated clothing before reuse. Use appropriate skin cream to prevent drying of Conditions for safe storage, including any incompatibilities Storage precautions Store at room temperature. Keep container tightly sealed when not in use. Storage class Chemical storage Specific end uses(s) Specific end use(s) The identified uses for this product are detailed in Section 1. 8. Exposure Controls/personal protection Control parameters Occupational exposure limits Long-term exposure limit (8-hour TWA): ACGIH 200 ppm Short-term exposure limit (15-minute): ACGIH 250 ppm ACGIH = American Conference of Governmental Industrial Hygienists. Exposure controls Protective equipmen Appropriate engineering Provide adequate general and local exhaust ventilation Eye/face protection Wear tight-fitting, chemical splash goggles or face shield. Hand protection Wear protective gloves made of the following material: Impermeable material. Other skin and body Wear appropriate clothing to prevent any possibility of skin contact. Hygiene measures Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. 9. Physical and Chemical Properties Information on basic physical and chemical properties Appearance Paste Color Tan.





## **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

## **Manufacturer Part Number:**

ETOE138-4G

Click here for more details on the EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

Revision date: 3/24/2017	Revision: 2	Supersedes date: 2/24/2015
	EPO-TEK OE138 Part A	
Odor	Mild.	
Flash point	>93°C	
Evaporation rate	<buac< td=""><td></td></buac<>	
Vapor density	>1	
Solubility(ies)	Slightly soluble in water.	
Other information	None.	
10. Stability and reactivity		
Reactivity	The following materials may react with the product: Strong agents.	oxidizing agents. Strong reducing
Stability	Stable at normal ambient temperatures and when used as	recommended.
Possibility of hazardous reactions	Will not polymerize.	
Conditions to avoid	Avoid excessive heat for prolonged periods of time. Avoid ignition.	heat, flames and other sources of
Materials to avoid	Strong oxidizing agents. Strong reducing agents.	
Hazardous decomposition products	Thermal decomposition or combustion products may inclu Carbon monoxide (CO). Carbon dioxide (CO2).	de the following substances:
11. Toxicological information		
Information on toxicological e	ffects	
Inhalation	Gas or vapor in high concentrations may irritate the respin during cutting, grinding or sanding operations involving thi respiratory tract.	
Ingestion	May cause discomfort if swallowed.	
Skin Contact	May cause sensitisation by skin contact. Irritating to skin.	
Eye contact	Causes serious eye irritation.	
Acute and chronic health hazards	Causes damage to organs .	





## Manufacturer:

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

## **Manufacturer Part Number:**

ETOE138-4G

Click here for more details on the EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

Revision date: 3/24/2017	Revision: 2 Supersedes date: 2/24/2015	
	EPO-TEK OE138 Part A	
12. Ecological Information		
Ecotoxicity	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.	
Acute toxicity - fish	Not available.	
Persistence and degradability		
Persistence and degradability	The product is biodegradable.	
Bioaccumulative potential		
Bio-Accumulative Potential	The product contains potentially bioaccumulating substances.	
Mobility in soil		
Mobility	Mobile.	
Other adverse effects		
Other adverse effects	Not known.	
13. Disposal considerations		
Waste treatment methods		
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.	
14. Transport information		
UN Number		
UN No. (TDG)	3082	
UN No. (IMDG)	3082	
UN No. (ICAO)	3082	
UN No. (DOT)	UN3082	
UN proper shipping name		
Proper shipping name (TDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Phenol Novolac)	
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Phenol Novolac)	
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS Epoxy Phenol Novolac)	
Proper shipping name (DOT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (CONTAINS Epoxy	
	Phenol Novolac)	
Transport hazard class(es)	Phenol Novolac)	
Transport hazard class(es) DOT hazard class	Phenol Novolac) 9	
DOT hazard class	9	
DOT hazard class	9	
DOT hazard class DOT hazard label TDG class	9 9 9	

Contact the professionals at Fiber Optic Center for a quote or to get more details.





**Manufacturer:** Epoxy Technology


#### **Product Name:**

EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

#### **Manufacturer Part Number:**

ETOE138-4G

Click here for more details on the EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)







# Manufacturer:

**Epoxy Technology** 

#### **Product Name:**

EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

#### **Manufacturer Part Number:**

ETOE138-4G

Click here for more details on the EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

Revision date: 3/24/2017 Supersedes date: 2/24/2015 EPO-TEK OE138 Part A **OSHA Highly Hazardous Chemicals** None of the ingredients are listed. **US State Regulations** California Proposition 65 Carcinogens and Reproductive Toxins None of the ingredients are listed. California Air Toxics "Hot Spots" (A-I) The following ingredients are listed: Polar Activator California Air Toxics "Hot Spots" (A-II) None of the ingredients are listed. Massachusetts "Right To Know" List The following ingredients are listed: Polar Activator Rhode Island "Right To Know" List The following ingredients are listed: Polar Activator Minnesota "Right To Know" List The following ingredients are listed: Polar Activator New Jersey "Right To Know" List The following ingredients are listed: Polar Activator Pennsylvania "Right To Know" List The following ingredients are listed: Polar Activator Inventories EU - EINECS/ELINCS Some of the ingredients are listed or exempt. Canada - DSL/NDSL All the ingredients are listed or exempt. US - TSCA All the ingredients are listed or exempt. US - TSCA 12(b) Export Notification None of the ingredients are listed. Australia - AICS All the ingredients are listed or exempt. Some of the ingredients are listed or exempt





**Manufacturer:** Epoxy Technology

#### **Product Name:**

EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

#### **Manufacturer Part Number:**

ETOE138-4G

Click here for more details on the EPO-TEK® OE138 Thixotropic High Temperature Epoxy, Heat Cure (4g)

Revision date: 3/24/2017 Revision: 2 Supersedes date: 2/24/2015 EPO-TEK OE138 Part A Korea - KECI All the ingredients are listed or exempt. China - IECSC All the ingredients are listed or exempt. Philippines - PICCS All the ingredients are listed or exempt. 16. Other information Revision date 3/24/2017 Revision 2 2/24/2015 Hazard statements in full H225 Highly flammable liquid and vapor. H301 Toxic if swallowed. H311 Toxic in contact with skin H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H331 Toxic if inhaled H370 Causes damage to organs. H411 Toxic to aquatic life with long lasting effects.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Epoxy Technology, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Epoxy Technology, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.



