

### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

### **Manufacturer Part Number:**

OG198-54-3CC

Click here for more details on the EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)



## **EPO-TEK® OG198-54 PMF SYRINGE**

HNOLOGY Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 7/1/2022 Version: 1.0

#### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture

Product name : EPO-TEK® OG198-54 PMF SYRINGE

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : adhesives Recommended use : adhesives

Restrictions on use : Not to be used for any purpose other than the one the product was designed for

#### 1.3. Supplier

Epoxy Technology, Inc. 14 Fortune Drive Billerica, MA 01821, 01821 USA 1978-667-3805 - F 978-663-9782

1 9/8-66/-3805 - F 9/8-663-

www.epotek.com

## 1.4. Emergency telephone number

Emergency number : ChemTel: +1 (800) 255-3924, +1 (813) 248-0585

## SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

### GHS US classification

Skin sensitization, Category 1 H317 May cause an allergic skin reaction

Hazardous to the aquatic environment – Acute Hazard Category 3 H402 Harmful to aquatic life

Hazardous to the aquatic environment – Chronic Hazard Category 3 H412 Harmful to aquatic life with long lasting effects

Full text of H statements : see section 16

## 2.2. GHS Label elements, including precautionary statements

## GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

7/1/2022 (Issue date)

Hazard statements (GHS US) : H317 - May cause an allergic skin reaction

H402 - Harmful to aquatic life

H412 - Harmful to aquatic life with long lasting effects
Precautionary statements (GHS US) : P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - If on skin: Wash with plenty of water.

P321 - Specific treatment (see supplemental first aid instruction on this label). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

EN (English US)

P501 - Dispose of contents/container to hazardous or special waste collection point, in

Data is subject to change without notice.





### **Manufacturer:**

Epoxy Technology

### **Product Name:**

EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

### **Manufacturer Part Number:**

OG198-54-3CC

Click here for more details on the EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

## **EPO-TEK® OG198-54 PMF SYRINGE**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

2.4. Unknown acute toxicity (GHS US)

Not applicable

#### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

| Name            | Product identifier       | %       | GHS US classification  |
|-----------------|--------------------------|---------|--|
| Epoxy resin*    | CAS-No.: Trade<br>Secret | 30 – 60 | Skin Sens. 1, H317<br>Aquatic Chronic 3, H412  |
| Photoinitiator* | CAS-No.: Trade<br>Secret | <1      | Eye Irrit. 2, H319<br>Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 |
| Photoinitiator* | CAS-No.: Trade<br>Secret | <1      | Eye Irrit. 2, H319<br>Skin Sens. 1, H317   |

<sup>\*</sup>Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Comments : Components not listed are either non-hazardous or are below reportable limits.

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs:

Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

## 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : May cause an allergic skin reaction.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## **S**ECTION 5: Fire-fighting measures

## 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide

7/1/2022 (Issue date) EN (English US) 2/9

Data is subject to change without notice.





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

### **Manufacturer Part Number:**

OG198-54-3CC

Click here for more details on the EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

### **EPO-TEK® OG198-54 PMF SYRINGE**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing

dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer

to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing

dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.

Hygiene measures : Contaminated work dothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

## SECTION 8: Exposure controls/personal protection

8.1. Control parameters

## EPO-TEK® OG198-54 PMF SYRINGE

No additional information available

7/1/2022 (Issue date) EN (English US) 3//

Data is subject to change without notice.





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

### **Manufacturer Part Number:**

OG198-54-3CC

Click here for more details on the EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

### **EPO-TEK® OG198-54 PMF SYRINGE**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Epoxy resir

No additional information available

Photoinitiator

No additional information available

Photoinitiator

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):







## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid Color Colorless Odor slight Odor threshold No data available pН No data available Melting point : Not applicable : No data available Freezing point : No data available Boiling point Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available Flammability Not applicable. Vapor pressure : No data available Relative vapor density at 20 °C : No data available Relative density : No data available

7/1/2022 (Issue date) EN (English US) 4/9

Data is subject to change without notice.





### **Manufacturer:**

**Epoxy Technology** 

### **Product Name:**

EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

## **Manufacturer Part Number:**

OG198-54-3CC

Click here for more details on the EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

### **EPO-TEK® OG198-54 PMF SYRINGE**

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available Explosion limits No data available : No data available Explosive properties Oxidizing properties : No data available

#### 9.2. Other information

No additional information available

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

## 10.5. Incompatible materials

No additional information available

## 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

| Epoxy resin           |   |  |
|-----------------------|---|--|
| LD50 oral rat         | 4490 mg/kg (Rat, Oral)  |  |
| LD50 dermal rat       | > 2000 mg/kg (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value,<br>Dermal) |  |
| LD50 dermal rabbit    | > 2000 mg/kg (Rabbit, Dermal)   |  |
| LC50 Inhalation - Rat | > 20 mg/l (4 h, Rat, Inhalation)  |  |
| ATE US (oral)         | 4490 mg/kg body weight  |  |

7/1/2022 (Issue date) EN (English US) 5/9







## **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

## **Manufacturer Part Number:**

OG198-54-3CC

Click here for more details on the EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

## **EPO-TEK® OG198-54 PMF SYRINGE**

### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Photoinitiator                      |  |  |
|-------------------------------------|--|--|
| LD50 oral rat                       | > 5110 mg/kg body weight (EU Method B.1: Acute Toxicity (Oral), Rat, Male / female,<br>Experimental value, Oral) |  |
| Skin corrosion/irritation           | : Not classified   |  |
| Serious eye damage/irritation       | : Not classified   |  |
| Respiratory or skin sensitization   | : May cause an allergic skin reaction.   |  |
| Germ cell mutagenicity              | : Not classified   |  |
| Carcinogenicity                     | : Not classified   |  |
| Reproductive toxicity               | : Not classified   |  |
| STOT-single exposure                | : Not classified   |  |
| STOT-repeated exposure              | : Not classified   |  |
| Aspiration hazard                   | : Not classified   |  |
| Viscosity, kinematic                | : No data available  |  |
| Symptoms/effects after skin contact | : May cause an allergic skin reaction.   |  |

| Symptoms/ellects after skin contact | • | may cause an allergic skin reaction. |
|-------------------------------------|---|--------------------------------------|
|                                     |   |                                      |

| SECTION 12: Ecological information              |   |  |
|---|---|--|
| 12.1. Toxicity                                  |   |  |
| Ecology - general                               | : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.   |  |
| Epoxy resin                                     |   |  |
| LC50 - Fish [1]                                 | 24 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, GLP) |  |
| EC50 - Crustacea [1]                            | 40 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP) |  |
| Photoinitiator                                  |   |  |
| EC50 - Crustacea [1]                            | 0.8 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia sp., Experimental value)                                   |  |
| ErC50 algae                                     | 0.184 mg/l (EU Method C.3, 72 h, Selenastrum capricomutum, Experimental value, GLP)   |  |
| Photoinitiator                                  |   |  |
| EC50 - Crustacea [1]                            | 0.148 mg/l  |  |
| 12.2. Persistence and degradability             |   |  |
| Epoxy resin                                     |   |  |
| Persistence and degradability                   | Biodegradability in soil: no data available. Readily biodegradable in water.  |  |
| ThOD  | 2.16 g O□/g substance   |  |
| 12.3. Bioaccumulative potential                 |   |  |
| Epoxy resin                                     |   |  |
| Partition coefficient n-octanol/water (Log Pow) | 1.34 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)                             |  |
| Bioaccumulative potential                       | Low potential for bioaccumulation (Log Kow < 4).  |  |
| Photoinitiator                                  |   |  |
| Partition coefficient n-octanol/water (Log Pow) | 1 (Practical experience/observation, EU Method A.8: Partition Coefficient, 20 °C)   |  |

EN (English US)

Data is subject to change without notice.

7/1/2022 (Issue date)



6/9



## **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

## **Manufacturer Part Number:**

OG198-54-3CC

Click here for more details on the EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

| Photoinitiator   |   |
|--|---|
| Partition coefficient n-octanol/water (Log Pow)              | 27.109 Source: lookchem   |
| 12.4. Mobility in soil                                       |   |
| Epoxy resin  |   |
| Organic Carbon Normalized Adsorption Coefficient<br>Log Koc) | 1.4195 (log Koc, QSAR)  |
| Ecology - soil   | Low potential for adsorption in soil. Highly mobile in soil.                                  |
| Photoinitiator   |   |
| Surface tension  | 55.9 mN/m (20 °C, 18 mg/l, EU Method A.5: Surface tension)                                    |
| 12.5. Other adverse effects                                  |   |
| No additional information available                          |   |
|  |   |
| SECTION 13: Disposal considerations                          |   |
| 13.1. Disposal methods                                       |   |
| Waste treatment methods                                      | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |
|  |   |
| SECTION 14: Transport information                            |   |
| n accordance with DOT / TDG / IMDG / IATA                    |   |
| 14.1. UN number  |   |
| Not regulated for transport                                  |   |
| 14.2. UN proper shipping name                                |   |
| Proper Shipping Name (DOT)                                   | : Not applicable  |
| Proper Shipping Name (TDG)                                   | : Not applicable  |
| Proper Shipping Name (IMDG)<br>Proper Shipping Name (IATA)   | : Not applicable<br>: Not applicable  |
| 14.3. Transport hazard class(es)                             |   |
| DOT  |   |
| Transport hazard class(es) (DOT)                             | : Not applicable  |
| TDG  |   |
| Transport hazard class(es) (TDG)                             | : Not applicable  |
| MDG  |   |
| Transport hazard class(es) (IMDG)                            | : Not applicable  |
| ATA  |   |
| Fransport hazard class(es) (IATA)                            | : Not applicable  |
| 14.4. Packing group  |   |
| Packing group (DOT)  | : Not applicable  |
| Packing group (TDG)  | : Not applicable  |







### **Manufacturer:**

**Epoxy Technology** 

## **Product Name:**

EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

## **Manufacturer Part Number:**

OG198-54-3CC

Click here for more details on the EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

## **EPO-TEK® OG198-54 PMF SYRINGE** Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Packing group (IMDG) : Not applicable Packing group (IATA) : Not applicable 14.5. Environmental hazards Other information : No supplementary information available. 14.6. Special precautions for user DOT No data available TDG No data available IMDG No data available IATA No data available 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable **SECTION 15: Regulatory information** 15.1. US Federal regulations All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory 15.2. International regulations CANADA **Epoxy resin** Listed on the Canadian DSL (Domestic Substances List) Photoinitiator Listed on the Canadian NDSL (Non-Domestic Substances List) Photoinitiator Listed on the Canadian NDSL (Non-Domestic Substances List) FU-Regulations No additional information available National regulations No additional information available 15.3. US State regulations California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm 7/1/2022 (Issue date) EN (English US) 8/9





## **Manufacturer:**

Epoxy Technology

## **Product Name:**

EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

## **Manufacturer Part Number:**

OG198-54-3CC

Click here for more details on the EPO-TEK® OG198-54 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

## **EPO-TEK® OG198-54 PMF SYRINGE**

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| SECTION 16: Other information |  |  |  |
|-------------------------------|--|--|--|
| according to Feder            | according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations |  |  |
| Full text of H-phrases        |  |  |  |
| H317                          | May cause an allergic skin reaction  |  |  |
| H319                          | Causes serious eye irritation  |  |  |
| H400                          | Very toxic to aquatic life   |  |  |
| H402                          | Harmful to aquatic life  |  |  |
| H410                          | Very toxic to aquatic life with long lasting effects   |  |  |
| H412                          | Harmful to aquatic life with long lasting effects  |  |  |

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

7/1/2022 (Issue date) EN (English US) 9

