

Manufacturer: Epoxy Technology

Product Name:

EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

Manufacturer Part Number:

OG198-55-3CC

Click here for more details on the EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

EPOXY EPO-TEK® OG198-55 PMF SYRINGE TECHNOLOGY Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Issue date: 7/6/2022 Version: 1.0 A Meridian Adhesives Group Company **SECTION 1: Identification** 1.1. Identification Product form Mixture Product name : EPO-TEK® OG198-55 PMF SYRINGE 1.2. Recommended use and restrictions on use Use of the substance/mixture : adhesives Recommended use : adhesives Restrictions on use : Not to be used for any purpose other than the one the product was designed for 1.3. Supplier Epoxy Technology, Inc. 14 Fortune Drive Billerica, MA 01821, 01821 USA T 978-667-3805 - F 978-663-9782 www.epotek.com 1.4. Emergency telephone number Emergency number : ChemTel: +1 (800) 255-3924, +1 (813) 248-0585 SECTION 2: Hazard(s) identification 2.1. Classification of the substance or mixture **GHS US classification** H317 Skin sensitization, Category 1 May cause an allergic skin reaction Hazardous to the aquatic environment - Acute Hazard Category 3 H402 Harmful to aquatic life Hazardous to the aquatic environment - Chronic Hazard Category 3 H412 Harmful to aquatic life with long lasting effects Full text of H statements : see section 16 2.2. GHS Label elements, including precautionary statements GHS US labeling Hazard pictograms (GHS US) Signal word (GHS US) : Warning Hazard statements (GHS US) : H317 - May cause an allergic skin reaction H402 - Harmful to aquatic life H412 - Harmful to aquatic life with long lasting effects Precautionary statements (GHS US) : P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. P272 - Contaminated work clothing must not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 - If on skin: Wash with plenty of water P321 - Specific treatment (see supplemental first aid instruction on this label). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P363 - Wash contaminated clothing before reuse P501 - Dispose of contents/container to hazardous or special waste collection point, in

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer: Epoxy Technology

Product Name:

EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

Manufacturer Part Number:

OG198-55-3CC

Click here for more details on the EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

EPO-TEK® OG198-55 PMF SYRINGE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Harmful dust may be released during cutting, milling or grinding process.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Epoxy resin*	CAS-No.: Trade Secret	30 - 60	Skin Sens. 1, H317 Aquatic Chronic 3, H412
Photoinitiator*	CAS-No.: Trade Secret	< 1	Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Photoinitiator*	CAS-No.: Trade Secret	< 1	Eye Irrit. 2, H319 Skin Sens. 1, H317

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Comments : Components not listed are either non-hazardous or are below reportable limits. Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation First-aid measures after skin contact	 Remove person to fresh air and keep comfortable for breathing. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact First-aid measures after ingestion	: Rinse eyes with water as a precaution. : Call a poison center/doctor/physician if you feel unwell.
4.2. Most important symptoms and ef	fects (acute and delayed)
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
4.3. Immediate medical attention and	special treatment, if necessary
Treat symptomatically.	
SECTION 5: Fire-fighting measure	29
5.1. Suitable (and unsuitable) extingu	ishing media

o. i. Suitable (and unsuitable) extinguishing med

: Water spray. Dry powder. Foam. Carbon dioxide.

Learn More

Data is subject to change without notice.

Suitable extinguishing media

Contact the professionals at Fiber Optic Center for a quote or to get more details.



Manufacturer: Epoxy Technology

Product Name:

EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

Manufacturer Part Number:

OG198-55-3CC

Click here for more details on the EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

EPO-TEK® OG198-55 PMF SYRINGE

Safety Data Sheet

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, M	arch 26, 2012 / Rules and Regulations
5.2. Specific hazards arising from the chem	ical
Hazardous decomposition products in case of fire	: Toxic fumes may be released.
5.3. Special protective equipment and prec	autions for fire-fighters
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTION 6: Accidental release measur	res
6.1. Personal precautions, protective equip	ment and emergency procedures
6.1.1. For non-emergency personnel	
Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Avoid release to the environment.	
6.3. Methods and material for containment	and cleaning up
For containment	: Collect spillage.
Methods for cleaning up Other information	: Take up liquid spill into absorbent material. : Dispose of materials or solid residues at an authorized site.
	: Dispose or materials or solid residues at an authorized site.
6.4. Reference to other sections For further information refer to section 13.	
For further information refer to section 13.	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing
Hygiene measures	dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated
	clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands
	after handling the product.
7.2. Conditions for safe storage, including	any incompatibilities
Storage conditions	: Store in a well-ventilated place. Keep cool.
SECTION 8: Exposure controls/person	al protection
8.1. Control parameters	
EPO-TEK® OG198-55 PMF SYRINGE	
No additional information available	

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer: Epoxy Technology

Product Name:

EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

Manufacturer Part Number:

OG198-55-3CC

Click here for more details on the EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

EPO-TEK® OG198-55 PMF SYRINGE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Epoxy resin
No additional information available
Photoinitiator
No additional information available
Photoinitiator
No additional information available
8.2. Appropriate engineering controls
Appropriate engineering controls : Ensure good ventilation of the work station. Environmental exposure controls : Avoid release to the environment.
8.3. Individual protection measures/Personal protective equipment
Hand protection:
Wear suitable gloves resistant to chemical penetration. Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Refer to manufacturer's information. Gloves must be replaced after each use and whenever signs of wear or perforation appear
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment





9.1. Information on basic physical and o	chemical properties
Physical state	: Liquid
Color	: milky
Odor	: slight
Odor threshold	: No data available
рН	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer: Epoxy Technology

Product Name:

EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

Manufacturer Part Number:

OG198-55-3CC

Click here for more details on the EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

EPO-TEK® OG198-55 PMF SYRINGE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available


10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological informat	ion
11.1. Information on toxicological effects	S
Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation) Epoxy resin	: Not classified : Not classified : Not classified
LD50 oral rat	4490 mg/kg (Rat, Oral)
LD50 dermal rat	> 2000 mg/kg (OECD 402: Acute Dermal Toxicity, Rat, Male / female, Experimental value, Dermal)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit, Dermal)
LC50 Inhalation - Rat	> 20 mg/l (4 h, Rat, Inhalation)
ATE US (oral)	4490 mg/kg body weight

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.







Manufacturer: Epoxy Technology

Product Name:

EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

Manufacturer Part Number:

OG198-55-3CC

Click here for more details on the EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

EPO-TEK® OG198-55 PMF SYRINGE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


Photoinitiator		
LD50 oral rat	> 5110 mg/kg body weight (EU Method B.1: Acute Toxicity (Oral), Rat, Male / female, Experimental value, Oral)	
Skin corrosion/irritation	: Not classified	
Serious eye damage/irritation	: Not classified	
Respiratory or skin sensitization	: May cause an allergic skin reaction.	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	
Reproductive toxicity	: Not classified	
STOT-single exposure	: Not classified	
STOT-repeated exposure	: Not classified	
Aspiration hazard	: Not classified	
Viscosity, kinematic	: No data available	
Symptoms/effects after skin contact	: May cause an allergic skin reaction.	

SECTION 12: Ecological information	SECTION 12	: Ecolo	gical in	formati	on
------------------------------------	------------	---------	----------	---------	----

12.1. Toxicity		
Ecology - general	: Harmful to aquatic life. Harmful to aquatic life with long lasting effects.	
Epoxy resin		
LC50 - Fish [1]	24 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value, GLP)	
EC50 - Crustacea [1]	40 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)	
Photoinitiator		
EC50 - Crustacea [1]	0.8 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia sp., Experimental value)	
ErC50 algae	0.184 mg/l (EU Method C.3, 72 h, Selenastrum capricornutum, Experimental value, GLP)	
Photoinitiator		
EC50 - Crustacea [1]	0.148 mg/l	
12.2. Persistence and degradability		
Epoxy resin		
Persistence and degradability	Biodegradability in soil: no data available. Readily biodegradable in water.	
ThOD	2.16 g O⊡/g substance	
12.3. Bioaccumulative potential		
Epoxy resin		
Partition coefficient n-octanol/water (Log Pow)	1.34 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Photoinitiator		
Partition coefficient n-octanol/water (Log Pow)	1 (Practical experience/observation, EU Method A.8: Partition Coefficient, 20 °C)	

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.







Manufacturer: Epoxy Technology

Product Name:

EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

Manufacturer Part Number:

OG198-55-3CC

Click here for more details on the EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

EPO-TEK® OG198-55 PMF SYRINGE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Photoinitiator	
Partition coefficient n-octanol/water (Log Pow)	27.109 Source: lookchem
12.4. Mobility in soil	
Epoxy resin	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.4195 (log Koc, QSAR)
Ecology - soil	Low potential for adsorption in soil. Highly mobile in soil.
Photoinitiator	
Surface tension	55.9 mN/m (20 °C, 18 mg/l, EU Method A.5: Surface tension)
12.5. Other adverse effects	
No additional information available	
SECTION 13: Disposal considerations	
13.1. Disposal methods	
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
SECTION 14: Transport information	
In accordance with DOT / TDG / IMDG / IATA	
14.1. UN number	
Not regulated for transport	
14.2. UN proper shipping name	
	: Not applicable
	: Not applicable : Not applicable
	: Not applicable
14.3. Transport hazard class(es)	
рот	
Transport hazard class(es) (DOT)	: Not applicable
TDG	
Transport hazard class(es) (TDG)	: Not applicable
IMDG	
Transport hazard class(es) (IMDG)	: Not applicable
IATA	
Transport hazard class(es) (IATA)	: Not applicable
14.4. Packing group	
Packing group (DOT)	: Not applicable
	: Not applicable

Learn More

Contact the professionals at Fiber Optic Center for a quote or to get more details.



Manufacturer: Epoxy Technology

Product Name: EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

Manufacturer Part Number:

OG198-55-3CC

Click here for more details on the EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

EPO-TEK® OG198-55 PMF SYRINGE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 /	Monday, March 26, 2012 / Rules and Regulations
Packing group (IMDG) Packing group (IATA)	: Not applicable : Not applicable
14.5. Environmental hazards	
Other information	: No supplementary information available.
14.6. Special precautions for user	
DOT No data available	
TDG No data available	
IMDG No data available	
IATA No data available	
14.7. Transport in bulk according t	to Annex II of MARPOL 73/78 and the IBC Code
Not applicable	
SECTION 15: Regulatory inform	nation
15.1. US Federal regulations	
All components of this product are present (TSCA) inventory	t and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act
15.2. International regulations	
CANADA	
Epoxy resin	
Listed on the Canadian DSL (Domestic Su	ubstances List)
Photoinitiator	
Listed on the Canadian NDSL (Non-Dome	setin Substannes List)
Listed on the Ganadian HDGE (Non-Dome	au ousances Listy
Photoinitiator	
Listed on the Canadian NDSL (Non-Dome	stic Substances List)
EU-Regulations	
No additional information available	
National regulations	
No additional information available	
15.3. US State regulations	
California Proposition 65 - This product do	

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer: Epoxy Technology

Product Name:

EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

Manufacturer Part Number:

OG198-55-3CC

Click here for more details on the EPO-TEK® OG198-55 Electrically and Thermally Insulating Epoxy, UV & Heat Cure (3cc Syringe)

EPO-TEK® OG198-55 PMF SYRINGE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information	
according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations	
Full text of H-phrases	
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.

