

Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Click the thumbnail below to navigate to the SDS.



Chemtronics Electro-Wash® PX



<u>Chemtronics Electro-Wash® MX</u> <u>Presaturated Wipes</u>





Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

SAFETY DATA SHEET

Chemtronics

Electro-Wash PX

Section 1. Identification

GHS product identifier

: Electro-Wash PX

Product code

: FS810 FS1210 FS1210A : Cleaner. Degreasers

Other means of identification

ES810, ES1210, ES1210A

ES1210 (NSN 6850-01-393-4059)

Industrial/Professional use

Product type

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Processing aid Cleaner. Degreasers

Uses advised against

Not applicable.

Supplier's details

: Manufacturer

Chemtronics

8125 Cobb Center Drive

Kennesaw, GA 30152

Tel. 770-424-4888 or toll free 800-645-5244

Emergency telephone number (with hours of

operation)

: Chemtrec - 1-800-424-9300 or collect 703-527-3887 24/7

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture FLAMMABLE AEROSOLS - Category 1 GASES UNDER PRESSURE - Compressed gas

SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

Extremely flammable aerosol

Contains gas under pressure; may explode if heated.

Causes skin irritation.

Causes serious eye irritation.

Precautionary statements

Prevention

Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Wash thoroughly after handling. Pressurized container: Do not pierce or burn, even after use.

>> Return to Page 1

: 3/13/2023 Date of issue/Date of revision 1/13 Date of previous issue : No previous validation Version :1





Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash PX

Section 2. Hazards identification

Respons

: Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage

classified

: Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 $^{\circ}\text{C}/122~^{\circ}\text{F}.$

Disposal Hazards not otherwise Not applicable.None known.

Section 3. Composition/information on ingredients

Substance/mixture

Other means of identification : Mixture

: Cleaner. Degreasers ES810, ES1210, ES1210A ES1210 (NSN 6850-01-393-4059) Industrial/Professional use

Ingredient name	%	CAS number
ethanol	≥10 - ≤25	64-17-5
Isopropyl alcohol	≤10	67-63-0
n-hexane	≤3	110-54-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

surveillance for 48 hol

Skin contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed Potential acute health effects >> Return to Page 1

rotential acute health enects

Date of issue/Date of revision : 3/13/2023 Date of previous issue : No previous validation Version : 1 2/13





Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash PX

Skin contact

Section 4. First aid measures

: Causes serious eve irritation

Inhalation : Exposure to decomposition products may cause a health hazard. Serious effects may

be delayed following exposure.

Ingestion : Do not ingest. If swallowed then seek immediate medical assistance.

Over-exposure signs/symptoms

Eve contact : Adverse symptoms may include the following:

: Causes skin irritation.

pain or irritation . watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

Skin contact : Adverse symptoms may include the following:

redness

Ingestion : Adverse symptoms may include the following:

Ingestion Seek medical attention.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

: None known.

Specific hazards arising

: Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Fire water contaminated with this material must be contained and prevented from being discharged

to any waterway, sewer or drain.

Hazardous thermal decomposition products

Decomposition products may include the following materials: carbon dioxide

carbon monoxide halogenated compounds carbonyl halides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water

spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

>> Return to Page 1

: 3/13/2023 Date of issue/Date of revision 3/13 Date of previous issue : No previous validation Version :1





Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash PX

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, : including any incompatibilities

: Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

>> Return to Page 1

Date of issue/Date of revision : 3/13/2023 Date of previous issue : No previous validation Version : 1 4/13





Electro-Wash PX

Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Section 8. Exposu	ure controls/personal protection
Control parameters	
Occupational exposure lim	<u>iits</u>
Ingredient name	Exposure limits
ethanol	ACGIH TLV (United States, 1/2022). STEL: 1000 ppm 15 minutes. NIOSH REL (United States, 10/2020). TWA: 1900 mg/m³ 10 hours. TWA: 1000 ppm 10 hours. OSHA PEL (United States, 5/2018). TWA: 1900 mg/m³ 8 hours. TWA: 1000 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 1900 mg/m³ 8 hours. TWA: 1900 mg/m³ 8 hours. TWA: 1000 ppm 8 hours.
Isopropyl alcohol	ACGIH TLV (United States, 1/2022). STEL: 400 ppm 15 minutes. TWA: 200 ppm 8 hours. NIOSH REL (United States, 10/2020). STEL: 1225 mg/m³ 15 minutes. STEL: 500 ppm 15 minutes. TWA: 980 mg/m³ 10 hours. TWA: 400 ppm 10 hours. OSHA PEL (United States, 5/2018). TWA: 980 mg/m³ 8 hours. TWA: 400 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). STEL: 1225 mg/m³ 15 minutes. STEL: 500 ppm 15 minutes. STEL: 500 ppm 15 minutes. TWA: 980 mg/m³ 8 hours. TWA: 400 ppm 8 hours.
n-hexane	ACGIH TLV (United States, 3/2020). Absorbed through skin. TWA: 50 ppm 8 hours. NIOSH REL (United States, 10/2016). TWA: 180 mg/m³ 10 hours. TWA: 50 ppm 10 hours. OSHA PEL (United States, 5/2018). TWA: 1800 mg/m³ 8 hours. TWA: 500 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 180 mg/m³ 8 hours. TWA: 50 ppm 8 hours.
Biological exposure indice	<u>s</u>
Ingredient name	Exposure indices
Isopropyl alcohol	ACGIH BEI (United States, 1/2022) BEI: 40 mg/l, acetone [in urine]. Sampling time: end of shift at end of workweek.
Appropriate engineering controls	: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
	>> 11c

: 3/13/2023



5/13

Version :1

Date of previous issue

: No previous validation

Date of issue/Date of revision



Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Flectro-Wash PX

Section 8. Exposure controls/personal protection

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use

: No previous validation

Version :1

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid. [Aerosol.] Color : Clear, Colorless,

Odor : Hydrocarbon, Characteristic, [Slight]

Odor threshold : Not available : Not available. Melting point/freezing point : Not available. **Boiling point, initial boiling** : 50°C (122°F)

point, and boiling range

Flash point : Closed cup: -29°C (-20.2°F) **Evaporation rate** : >1 (butyl acetate = 1)

Flammability : Extremely flammable in the presence of the following materials or conditions: open

Date of previous issue

flames, sparks and static discharge

Lower and upper explosion : Not available. limit/flammability limit

Date of issue/Date of revision

: 3/13/2023

: 26.4 kPa (198 mm Hg) Vapor pressure

Relative vapor density : >1 [Air = 1] Relative density : 0.7 Solubility in water : Not available

>> Return to Page 1

6/13







Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash PX

Section 9. Physical and chemical properties and safety characteristics

: Not applicable.

Partition coefficient: noctanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Heat of combustion : 19.75 kJ/g

Viscosity : Not available.

Particle characteristics

Median particle size : Not applicable.

Aerosol product

Type of aerosol : Spray

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame).

Incompatible materials : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
	LD50 Oral	Rat	7 g/kg	-
Isopropyl alcohol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-
n-hexane	LC50 Inhalation Gas.	Rat	48000 ppm	4 hours
	LD50 Oral	Rat	15840 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
	1			mg	
	Eyes - Moderate irritant	Rabbit	-	0.066666667	-
	1			minutes 100	
				mg	
	Eyes - Moderate irritant	Rabbit	-	100 uL	-
	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	400 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	
Isopropyl alcohol	Eyes - Moderate irritant	Rabbit	-	10 mg	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
				mg	
	Eyes - Severe irritant	Rabbit	-	100 mg	-

>> Return to Page 1







Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

	Skin - Mil		Rabbit	-	500 mg	-
n-hexane	Eyes - Mi	ld irritant	Rabbit	-	10 mg	-
<u>Sensitization</u>						
Not available.						
<u>Mutagenicity</u>						
Not available.						
Carcinogenicity						
Not available.						
Classification						
Product/ingredient name	OSHA	IARC	NTP			
	None.					

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available

routes of exposure

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Exposure to decomposition products may cause a health hazard. Serious effects may

be delayed following exposure.Causes skin irritation.

Ingestion : Do not ingest. If swallowed then seek immediate medical assistance.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

Skin contact

: Adverse symptoms may include the following: pain or irritation

watering redness

Inhalation : Advers

: Adverse symptoms may include the following: respiratory tract irritation

coughing

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : Adverse symptoms may include the following:

Ingestion Seek medical attention.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure >> Return to Page 1

Date of issue/Date of revision : 3/13/2023 Date of previous issue : No previous validation Version : 1 8/13







Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash PX

Section 11. Toxicological information

Potential immediate : Not available.

effects
Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

 General
 : No known significant effects or critical hazards.

 Carcinogenicity
 : No known significant effects or critical hazards.

 Mutagenicity
 : No known significant effects or critical hazards.

 Reproductive toxicity
 : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)		(vapors)	Inhalation (dusts and mists) (mg/ I)	
ethanol Isopropyl alcohol n-hexane	7000 5000 15840	N/A 12800 N/A	N/A N/A 48000	124.7 N/A N/A	N/A N/A N/A	

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
ethanol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 μg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia	48 hours
		franciscana - Larvae	
	Acute LC50 42000 μg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 100 ul/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks
Isopropyl alcohol	Acute EC50 7550 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 1400000 μg/l Marine water Acute LC50 4200 mg/l Fresh water	Crustaceans - Crangon crangon Fish - Rasbora heteromorpha	48 hours 96 hours
n-hexane	Acute LC50 2500 μg/l Fresh water	Fish - Pimephales promelas	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow		BCF		Potential		
ethanol Isopropyl alcohol n-hexane	-0.35 0.05 4		- - 501.187		low low high		
Date of issue/Date of revision	: 3/13/2023	Date of previous i	issue	: No previous validation	Version	:1	9/1

>> Return to Page 1







Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash PX

Section 12. Ecological information

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal $\,$ of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	UN1950	UN1950	UN1950	UN1950	ID8000
UN proper shipping name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable	AEROSOLS Limited quantity	Consumer commodity ID8000
Transport hazard class(es)	2.1	2.1	2.1	2.1	9
Packing group	-	-	-	-	-
Environmental hazards	Yes.	No.	No.	No.	No.

Additional information

DOT Classification

: This product is not regulated as a marine pollutant when transported on inland waterways in sizes of ≤5 L or ≤5 kg or by road, rail, or inland air in non-bulk sizes, provided the packagings meet the general provisions of §§ 173.24 and 173.24a.

TDG Classification

Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).

IATA

The environmentally hazardous substance mark may appear if required by other transportation regulations.

Quantity limitation Passenger and Cargo Aircraft: 75 kg. Packaging instructions: Y963. Cargo Aircraft Only: 150 kg. Packaging instructions: Y963. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y963.

Special precautions for user: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available to IMO instruments

>> Return to Page 1

Date of issue/Date of revision : 3/13/2023 Version : 1 10/13 Date of previous issue : No previous validation





Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash PX

Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

Clean Air Act (CAA) 112 regulated flammable substances: 1,1-diffuoroethane

Clean Air Act Section 112 : Listed

(b) Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602

: Not listed

Class I Substances
Clean Air Act Section 602

: Not listed

Class II Substances
DEA List I Chemicals

: Not listed

(Precursor Chemicals)
DEA List II Chemicals

DEA List II Chemicals (Essential Chemicals)

: Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ

: Not applicable.

SARA 311/312

Classification : FLAMMABLE AEROSOLS - Category 1

GASES UNDER PRESSURE - Compressed gas

SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

Composition/information on ingredients

Name	%	Classification
2-methylpentane	≥10 - ≤25	FLAMMABLE LIQUIDS - Category 2
1,1-difluoroethane	≥10 - ≤25	FLAMMABLE GASES - Category 1
		GASES UNDER PRESSURE - Compressed gas
3-methylpentane	≥10 - ≤25	FLAMMABLE LIQUIDS - Category 2
2,2-dimethylbutane	≥10 - ≤25	FLAMMABLE LIQUIDS - Category 2
2,3-dimethylbutane	≥10 - ≤25	FLAMMABLE LIQUIDS - Category 2
ethanol	≥10 - ≤25	FLAMMABLE LIQUIDS - Category 2
		SKIN IRRITATION - Category 2
		EYE IRRITATION - Category 2A
Isopropyl alcohol	≤10	FLAMMABLE LIQUIDS - Category 2
		EYE IRRITATION - Category 2A
Carbon dioxide, gas	≤5	GASES UNDER PRESSURÉ - Compressed gas
n-hexane	≤3	FLAMMABLE LIQUIDS - Category 2
		EYE IRRITATION - Category 2B 2

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements			≤10 ≤3
Supplier notification			≤10 ≤3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts

: The following components are listed: ISOHEXANE; DIFLUOROETHANE; 3-METHYLPENTANE; 2,2-DIMETHYLBUTANE; 2,3-DIMETHYLBUTANE; ETHYL ALCOHOL; ISOPROPYL ALCOHOL; CARBON DIOXIDE; HEXANE; N-HEXANE

New York : The following components are listed: Hexane

>> Return to Page 1

 Date of issue/Date of revision
 : 3/13/2023
 Date of previous issue
 : No previous validation
 Version
 : 1
 11/13





Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash PX

Section 15. Regulatory information

New Jersey

: The following components are listed: 2-METHYLPENTANE; ISOHEXANE; PENTANE, 2-METHYL-; 1,1-DIFLUOROETHANE; NEOHEXANE; BUTANE, 2,2-DIMETHYL-; 2,2 DIMETHYL BUTANE; 2,3-DIMETHYLBUTANE; BUTANE, 2,3-DIMETHYL-; ETHYL ALCOHOL; ISOPROPYL ALCOHOL; CARBON DIOXIDE; CARBONIC ACID GAS; n-HEXANE; HEXANE

Pennsylvania

: The following components are listed: PENTANE, 2-METHYL-; PENTANE, 3-METHYL-; BUTANE, 2,2-DIMETHYL-; BUTANE, 2,3-DIMETHYL-; ETHANOL; 2-PROPANOL;

CARBON DIOXIDE; HEXANE

California Prop. 65

▲ WARNING: This product can expose you to n-hexane, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

		Maximum acceptable dosage level
n-hexane	-	Yes.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Ingredient name	Status	
HFC-152a	Annex F, Group I	

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

Eurasian Economic Union : Russian Federation inventory: Not determined.

Japan

: Japan inventory (CSCL): All components are listed or exempted.

Thailand : Not determined.

Turkey : Not determined.

United States : All components are active or exempted.
Viet Nam : All components are listed or exempted.

>> Return to Page 1

Date of issue/Date of revision : 3/13/2023 Date of previous issue : No previous validation Version : 1 12/13





Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash PX

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Procedure used to derive the classification

Classification	Justification
FLAMMABLE AEROSOLS - Category 1	On basis of test data
GASES UNDER PRESSURE - Compressed gas	On basis of test data
SKIN IRRITATION - Category 2	Calculation method
EYE IRRITATION - Category 2A	Calculation method

History

Date of printing : 3/13/2023 Date of issue/Date of : 3/13/2023

revision

Date of previous issue : No previous validation

Version : 1

Key to abbreviations : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IBC = Intermediate Bulk Container

IMDG = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

References : Not available.

 ${f \begin{picture}(100,0) \put(0,0){\line(0,0){100}} \put(0,0){\line(0,0$

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

>> Return to Page 1

Date of issue/Date of revision : 3/13/2023 Date of previous issue : No previous validation Version : 1 13/13







Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

SAFETY DATA SHEET

Chemtronics

Electro-Wash® MX Presaturated Wipe

Section 1. Identification

GHS product identifier : Electro-Wash® MX Presaturated Wipe

Product code : CP421 : CP421 Other means of

NSN 7930-01-559-5328 identification **Product type** : Wipes/Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

: Chemtronics Supplier's details

8125 Cobb Center Drive Kennesaw, GA 30152

Tel. 770-424-4888 or toll free 800-645-5244

Emergency telephone number (with hours of operation)

: Chemtrec - 1-800-424-9300 or collect 703-527-3887

24/7

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 2 SKIN IRRITATION - Category EYE IRRITATION - Category 2A

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 75%

GHS label elements

Hazard pictograms





Signal word

: Danger

Hazard statements

Highly flammable liquid and vapor. Causes serious eye irritation. Causes skin irritation.

Precautionary statements

Prevention

: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosionproof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container

tightly closed. Wash hands thoroughly after handling.

Response

: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage : Store in a well-ventilated place. Keep cool.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations. >> Return to Page 1

: No previous validation Version : 1 Date of issue/Date of revision : 6/18/2019 Date of previous issue 1/13

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash® MX Presaturated Wipe

Section 2. Hazards identification

Hazards not otherwise

None known

classified

Section 3. Composition/information on ingredients

Substance/mixture : Mixture
Other means of : CP421

identification NSN 7930-01-559-5328

Ingredient name	%	CAS number
Isopropyl alcohol	≥10 - ≤25 ≥10 - ≤25 ≤10	64-17-5 67-63-0 109-60-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Harmful by inhalation. At very high concentrations, can displace the normal air and

cause suffocation from lack of oxygen.

Skin contact : Moderately irritating (USA)

Ingestion : Do not ingest. If swallowed then seek immediate medical assistance.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain or irritation watering

watering >> Return to Page 1

Date of issue/Date of revision : 6/18/2019 Date of previous issue : No previous validation Version : 1 2/13







Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash® MX Presaturated Wipe

Section 4. First aid measures

Inhalation

: Adverse symptoms may include the following:

drowsiness/fatigue dizziness/vertigo headache

Skin contact

: Adverse symptoms may include the following: irritation

redness

Ingestion

Adverse symptoms may include the following: Irritating to mouth, throat and stomach.

nausea or vomiting
Ingestion Seek medical attention.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

: Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

Specific hazards arising from the chemical

: Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders :

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-

emergency personnel". >> Return to Page 1

Date of issue/Date of revision : 6/18/2019 Date of previous issue : No previous validation Version : 1 3/13

Data is subject to change without notice.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash® MX Presaturated Wipe

Section 6. Accidental release measures

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, : including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

>> Return to Page 1

Date of issue/Date of revision : 6/18/2019 Date of previous issue : No previous validation Version : 1 4/13





Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

ngredient name	Exposure limits
ethanol	ACGIH TLV (United States, 3/2015). STEL: 1000 ppm 15 minutes. NIOSH REL (United States, 10/2013). TWA: 1900 mg/m³ 10 hours. TWA: 1000 ppm 10 hours. OSHA PEL (United States, 2/2013). TWA: 1900 mg/m² 8 hours. TWA: 1000 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). TWA: 1900 mg/m³ 8 hours. TWA: 1000 ppm 8 hours.
sopropyl alcohol	ACGIH TLV (United States, 3/2015). STEL: 400 ppm 15 minutes. TWA: 200 ppm 8 hours. NIOSH REL (United States, 10/2013). STEL: 1225 mg/m³ 15 minutes. STEL: 500 ppm 15 minutes. TWA: 980 mg/m³ 10 hours. TWA: 400 ppm 10 hours. OSHA PEL (United States, 2/2013). TWA: 980 mg/m³ 8 hours. TWA: 400 ppm 8 hours. OSHA PEL 1989 (United States, 3/1989). STEL: 1225 mg/m³ 15 minutes. STEL: 500 ppm 15 minutes. TWA: 980 mg/m³ 8 hours. TWA: 980 mg/m³ 8 hours.
propyl acetate	ACGIH TLV (United States, 3/2015). STEL: 1040 mg/m³ 15 minutes. STEL: 250 ppm 15 minutes. TWA: 835 mg/m³ 8 hours. TWA: 200 ppm 8 hours. NIOSH REL (United States, 10/2013). STEL: 1050 mg/m³ 15 minutes. STEL: 250 ppm 15 minutes. TWA: 840 mg/m³ 10 hours. TWA: 200 ppm 10 hours. OSHA PEL (United States, 2/2013). TWA: 840 mg/m³ 8 hours. TWA: 200 ppm 8 hours. OSHA PEL (1989 (United States, 3/1989). STEL: 1050 mg/m³ 15 minutes. STEL: 250 ppm 15 minutes. STEL: 250 ppm 15 minutes. TWA: 840 mg/m³ 8 hours. TWA: 840 mg/m³ 8 hours.

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

>> Return to Page 1

Date of issue/Date of revision : 6/18/2019 Date of previous issue : No previous validation Version : 1 5/13





Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash® MX Presaturated Wipe

Section 8. Exposure controls/personal protection

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. Color : Colorless Odor : Alcohol-like. Odor threshold : Not available нα : Not available **Melting point** : Not available. **Boiling point** : Not available. : CLOSED CUP: 7°C (44.6°F). Flash point

Evaporation rate : 1.6 (butyl acetate = 1)
Flammability (solid, gas) : Not available.

Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : 4.8 kPa (36 mm Hg) [room temperature]

Vapor density : >1 [Air = 1]
Relative density : 0.72
Solubility : Not available.
Solubility in water : Not available.
Partition coefficient: noctanol/water
Auto-ignition temperature : Not available.
Decomposition temperature : Not available.

Viscosity : Not available.

 Date of issue/Date of revision
 : 6/18/2019
 Date of previous issue
 : No previous validation
 Version
 : 1
 6/13

Data is subject to change without notice.



>> Return to Page 1



Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash® MX Presaturated Wipe

Section 9. Physical and chemical properties

Flow time (ISO 2431) : Not available

Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not

allow vapor to accumulate in low or confined areas.

Incompatible materials

: Reactive or incompatible with the following materials: oxidizing materials

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
	LD50 Oral	Rat	7 g/kg	-
Isopropyl alcohol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-
propyl acetate	LD50 Oral	Rat	9370 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	0.06666667 minutes 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	400	-
	Skin - Moderate irritant	Rabbit	-	milligrams 24 hours 20 milligrams	-
Isopropyl alcohol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	10 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
propyl acetate	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-

Date of previous issue

>> Return to Page 1 **Sensitization**

: No previous validation

Version :1

7/13

Data is subject to change without notice.



: 6/18/2019



Date of issue/Date of revision



Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash® MX Presaturated Wipe

Section 11. Toxicological information

Not available

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
ethanol	None.	-	-
Isopropyl alcohol	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available.

routes of exposure

Potential acute health effects
Eve contact

ct : Causes serious eve irritation.

Inhalation : Harmful by inhalation. At very

: Harmful by inhalation. At very high concentrations, can displace the normal air and cause suffocation from lack of oxygen.

Skin contact : Moderately irritating (USA)

Ingestion : Do not ingest. If swallowed then seek immediate medical assistance.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : Adverse symptoms may include the following:

drowsiness/fatigue dizziness/vertigo headache

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : Adverse symptoms may include the following:

Irritating to mouth, throat and stomach.

nausea or vomiting

Ingestion Seek medical attention.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

>> Return to Page 1

Date of issue/Date of revision : 6/18/2019 Date of previous issue : No previous validation Version : 1 8/13







Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash® MX Presaturated Wipe

Section 11. Toxicological information

Potential immediate : Not available. effects

Potential delayed effects : Not available. Long term exposure

Potential immediate

: Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General No known significant effects or critical hazards. Carcinogenicity : No known significant effects or critical hazards. Mutagenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. Teratogenicity $\begin{tabular}{lll} \textbf{Developmental effects} & : & No known significant effects or critical hazards. \\ \end{tabular}$ Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	13595.2 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
ethanol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 100 ul/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 0.375 ul/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks
Isopropyl alcohol	Acute LC50 1400000 to 1950000 μg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 4200 mg/l Fresh water	Fish - Rasbora heteromorpha	96 hours
propyl acetate	Acute LC50 60000 to 64000 μg/l Fresh water	Fish - Pimephales promelas	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
ethanol Isopropyl alcohol propyl acetate	-0.35 0.05 1.4	- -	low low low

>> Return to Page 1

Date of issue/Date of revision : 6/18/2019 Date of previous issue : No previous validation Version :1 9/13





Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash® MX Presaturated Wipe

Section 12. Ecological information

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-		-	
Transport hazard class(es)	-	-	-			
Packing group	-	-	-	-	-	
Environmental hazards	No.	No.	No.	No.	No.	No.
Additional information	-	-	-	Special provisions 216	Special provisions 216	IATA DGR page 348, A46

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL and

the IBC Code

: Not available.

>> Return to Page 1

Date of issue/Date of revision : 6/18/2019 Date of previous issue : No previous validation Version :1 10/13





Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash® MX Presaturated Wipe

Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): Not determined.

Clean Air Act Section 112 : Not listed

(b) Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I Substances

: Not listed

Clean Air Act Section 602

: Not listed

Class II Substances
DEA List I Chemicals

DEA List I Chemicals
(Precursor Chemicals)

: Not listed

(Precursor Chemicals)

DEA List II Chemicals (Essential Chemicals)

: Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ

: Not applicable.

SARA 311/312

Classification

: Fire hazard

Immediate (acute) health hazard

Composition/information on ingredients

Name	%	hazard	Sudden release of pressure		(acute) health	Delayed (chronic) health hazard
ethanol Isopropyl alcohol propyl acetate	≥10 - ≤25	Yes. Yes. Yes.	No.	No. No. No.	Yes. Yes. Yes.	No. No. No.

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Isopropyl alcohol	67-63-0	≥10 - ≤25
Supplier notification	Isopropyl alcohol	67-63-0	≥10 - ≤25

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts

: The following components are listed: ETHYL ALCOHOL; DENATURED ALCOHOL; ISOPROPYL ALCOHOL; 2-PROPANOL; N-PROPYL ACETATE; PROPYL ACETATE

New York

: None of the components are listed.

New Jersey

: The following components are listed: ETHYL ALCOHOL; ALCOHOL; ISOPROPYL ALCOHOL; 2-PROPANOL; n-PROPYL ACETATE; ACETIC ACID, PROPYL ESTER

Pennsylvania

: The following components are listed: DENATURED ALCOHOL; ETHANOL; ISOPROPYL ALCOHOL MANUFACTURE (STRONG-ACID PROCESS); ACETIC ACID, PROPYL ESTER

California Prop. 65

Ingredient name	Cancer	•	No significant risk level	acceptable dosage level	>> Return to Page 1
ethanol	No.	No.	Yes.	No.	

 Date of issue/Date of revision
 : 6/18/2019
 Date of previous issue
 : No previous validation
 Version
 : 1
 11/13





Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash® MX Presaturated Wipe

Section 15. Regulatory information

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed

International lists

National inventory

Australia : All components are listed or exempted

Canada : Not determined.

China : All components are listed or exempted.

Europe : All components are listed or exempted.

Japan : Japan inventory (ENCS): Not determined.

Japan inventory (ISHL): Not determined.

Malaysia : Not determined.

 New Zealand
 : All components are listed or exempted.

 Philippines
 : All components are listed or exempted.

 Republic of Korea
 : All components are listed or exempted.

 Taiwan
 : All components are listed or exempted.

 Turkey
 : All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



: 6/18/2019

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency
Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is
not the complete and official position of the National Fire Protection Association, on the referenced subject
which is represented only by the standard in its entirety.

>> Return to Page 1

: No previous validation

Date of previous issue

Version : 1 12/13

Data is subject to change without notice.

Date of issue/Date of revision

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer:

Chemtronics

Product Name:

ITW Chemtronics® FOCCUS Fiber Optic Installation and Maintenance Cleaning Kit

Manufacturer Part Number:

CFK1010

Click here for more details on the ITW Chemtronics® FOCCUS FTTH Fiber Optic Cleaning Kit

Electro-Wash® MX Presaturated Wipe

Section 16. Other information

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification	Justification	
SKIN IRRITATION - Category 2	On basis of test data Calculation method Calculation method	

History

Date of printing

Date of issue/Date of

revision

Date of previous issue : No previous validation

Version : 1

Key to abbreviations : ATE = Acute Toxicity Estimate

: 6/18/2019

: 6/18/2019

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References : Not available.

 $\overline{m{V}}$ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

>> Return to Page 1

Date of issue/Date of revision : 6/18/2019 Date of previous issue : No previous validation Version : 1 13/13

