



Manufacturer:
Jetting AB

Product Name:
Jetting VO Fiber Blowing Machine

Manufacturer Part Number:
VO-CAN

▶ [Click here for more details on the Jetting VO Fiber Blowing Machine](#)



VO FIBER BLOWING MACHINE

Extremely compact electrically operated fiber blowing machine optimized for FTTX installation of blown fiber (EPFU) and micro/nano cables, from 0.8 to 6 mm into ducts from 3 to 16 mm. A full digital control system with soft start, electronic fiber security, memory functions, combined with high-speed capability, makes the machine very easy and effective to use. Can be operated directly from its case.



**POWERFUL FTTX MACHINE FOR
CABLE 0.8 - 6 MM / MICRODUCT 3-16 MM**

- Electrically operated. Battery connected. Optional power supply.
- Electronic stopping/slipping protection within 250 ms.
- Display for current speed, distance, cable force and pressure.
- Max. speed: 820.2 ft/min
- Stepless pushing force on cable up to: 13.5 lbs.
- Adjustable clamping force.
- Works with JetLogger.
- Softstart: Enables an even smoother start protecting the fiber
- Memory: The last inserted data like pushing force will stay in the memory even if the device will be switched off or the battery need to be exchanged
- Service info: Memory of total milage/distance since machine taken into operation
- Duct air temp: Display showing the air temperature injected into the duct.
- Duct Air Release Valve, making the reduction of air from the duct very fast.
- Easy mounted drive wheel design with magnetic supported connection, make the change of drive wheels very fast.


TECHNICAL DATA

- ⊖ **Battery:**
18V, 5Ah Milwaukee connector
- ⊙ **Max pressure:**
232 psi
- ⊙ **Max speed:**
820.2 ft/min
- ⤵ **Pushing force:**
13.5 lbs
- ↻ **Cable diameter:**
0.8 - 6 mm
- ↻ **Microduct:**
3 - 16 mm
- ⚖ **Weight:**
Approx: 28.7 lbs
- ⊗ **Air connection:**
Std 3/8" Cejn
- ⊕ **WxHxD (transport box)**
23.6 x 19.7 x 11.8 inches

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com
23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.



Manufacturer:
Jetting AB

Product Name:
Jetting VO Fiber Blowing Machine

Manufacturer Part Number:
VO-CAN



▶ [Click here for more details on the Jetting VO Fiber Blowing Machine](#)




VO TRANSPORT CASE




VO FIBER BLOWING MACHINE



DUCT CLAMPS IN DIFFERENT SIZES



DRIVE WHEELS IN DIFFERENT SIZES



CABLE GUIDES IN DIFFERENT SIZES



EXTERNAL CABLE GUIDE FOR VO-SERIES CASE



DUCT AIR RELEASE



MAGNETIC DRIVE WHEEL



CONTROL PANEL

STD CONFIGURATION VO

- Transport case
- 3 drive Wheels
 - 1 pcs with rubber 0.8-3 mm
 - 1 pcs for 3.0-4.5 mm
 - 1 pcs for 4.5-6.5 mm
- Charger 230 V and 2 batteries
- 1 bottle Micro Duct Lube + Service kit
- Ground cable

ACCESSORIES FOR VO

- Cable inlet guides
- 110/240 V Power supply. No need to charge or change batteries
- Table bracket. For safe installation on working table
- Jetlogger. Electronic documentation system
- Metal drive wheel for < 2.5 mm cabel
- External cable guide for VO-series case
- 10 m. Airhose 3/8"
- Cabel seals
- Jetair 100270 Compressor
- Jetdrum KB Drum Rack

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.