



**Manufacturer:** Jetting AB

**Product Name:**Jetting VO HD Fiber Blowing Machine

**Manufacturer Part Number:** V0-HD-CAN

Click here for more details on the Jetting VO HD Fiber Blowing Machine



Extremely compact, electrically operated fiber blowing machine optimized for FTTX installation of blown fiber (EPFU) and micro/nano cables, ranging from 0.8 to 6.5 mm into ducts from 3 to 16 mm.

A fully digital control system with soft start, electronic fiber security, memory functions, combined with a powerful 45 lbs motor, makes the machine very flexible and effective to use. Can be operated directly from its case.





# POWERFUL FTTX MACHINE FOR CABLE 0,8 - 6,5 MM / DUCT 3-16 MM

- Electrically operated. Battery connected. Optional power supply.
- Electronic stopping/slipping protection within 250 ms.
- Display for current speed, distance, cable force and pressure.
- Max. speed: 820.2 ft/min
- Stepless pushing force on cable up to: 45.0 lbs.
- Adjustable clamping force.
- Works with JetLogger.
- Softstart: Enables an even smoother start protecting the fiber
- Memory: The last inserted data like pushing force will stay in the memory even if the device will be switched off or the battery need to be exchanged
- Service info: Memory of total milage/distance since machine taken into operation
- Duct air temp: Display showing the air temperature injected into the duct.
- Duct Air Release Valve, making the reduction of air from the duct very fast.
- Easy mounted drive wheel design with magnetic supported connection, make the change of drive wheels very fast.

#### **TECHNICAL DATA**

Battery: 18V, 5Ah Milwaukee connector

Max pressure: 232 psi

Max speed: 820.2 ft/min

Pushing force: up to 45.0 lbs

Cable diameter: 0.8 – 6 mm

Microduct: 3 - 16 mm

Weight:
Approx: 28.7 lbs

Air connection: Std 3/8" Cejn

WxHxD (transport box) 23.6 x 19.7 x 11.8 inches

Contact the professionals at Fiber Optic Center for a quote or to get more details.





## **Manufacturer:** Jetting AB

**Product Name:**Jetting VO HD Fiber Blowing Machine

**Manufacturer Part Number:** V0-HD-CAN

Click here for more details on the Jetting VO HD Fiber Blowing Machine



















#### **STD CONFIGURATION VO HD**

- Transport case
- 3 drive Wheels
- 1 pcs with rubber 0.8-3 mm
- 1 pcs for 3.0-4.5 mm
- 1 pcs for 4.5-6.5 mm
- Charger 230 V and 2 batteries
- 1 bottle Micro Duct Lube + Service kit
- Ground cable

#### **ACCESSORIES FOR VO HD**

- Cable inlet guides
- 110/240 V Power supply. No need to charge or change batteries
- Table bracket. For safe installation on working table
- Jetlogger. Electronic documentation system
- Metal drive wheel for < 2.5 mm cabel</li>
- External cable guide for V0-series case
- 32.8 ft Airhose 3/8"
- Cabel seals
- Jetair 100270 Compressor
- Jetdrum K8 Drum Rack

### Contact the professionals at Fiber Optic Center for a quote or to get more details.