

Manufacturer:

Opticonx

Product Name:

LightTube 1.2mm Round Breakout Tubing - PVC / Polypropylene - Pink

Manufacturer Part Number:

B12506040PK00

Click here for more details on the LightTube 1.2mm Round Breakout Tubing - PVC / Polypropylene - Pink


1.2 & 1.6mm Breakout Tubing

Opticonx LightTube $^{\text{TM}}$ 1.2 & 1.6mm Breakout tubing is used for breaking out 250 μ M buffered fiber to 1.2 or 1.6mm breakouts for terminating with any industry standard connector. The tubing is constructed with an inner tube for the inserted fiber, a layer of aramid yarn for stain relief and connector crimping and a color coded jacket.



Product Features:

- 17 Colors Available
- · Smooth fiber insertion
- Low shrinkage
- RoHS & REACH compliant
- Custom print legends and striping available
- Length markers available
- Pull string available
- Simplex or Duplex construction
- Custom constructions available



Ordering Information for 1.2mm simplex 250µM fiber:

Part	Legacy	Jacket	Inner Tube		Operating	Shrinkage	Min Bend Radius		Weight
Number	Part Number	Material	Material	OD x ID mm	Temp	@ 85° C	Install	Service	
B12506040XX00	C200151-1.2XXX	PVC	Polypropylene	600X400µm	-20C to +75C	<2%	4.01cm	2.0cm	.75kg/km

Replace 'XX' with Color Code							
BL = Blue	BR = Brown	RD = Red	VI = Violet	NA = Natural	MG = Magenta		
OR = Orange	SL = Slate (Gray)	BK = Black	PK = Pink	LM = Lime	TN = Tan		
GR = Green	WH = White	YL=Yellow	AQ = Aqua	OL = Olive			



Contact the professionals at Fiber Optic Center for a quote or to get more details.



Learn More



Manufacturer:

Opticonx

Product Name:

LightTube 1.2mm Round Breakout Tubing - PVC / Polypropylene - Pink


Manufacturer Part Number:

B12506040PK00

Click here for more details on the LightTube 1.2mm Round Breakout Tubing - PVC / Polypropylene - Pink

1.2 & 1.6mm Breakout Tubing

3.8mm x 1.6mm Duplex (Zip):



Ordering Information for 1.6mm duplex (Zip), 250µM fiber:

Part	Legacy	Jacket	Inner Tube		Operating	Shrinkage	Min Ben	Weight	
Number	Part Number	Material	Material	OD x ID mm	Temp	@ 85° C	Install	Service	
Z16509250XX00	N/A	PVC	TPE (Hytrel®)	900X500µm	-20C to +75C	<2%	3.55cm	1.78cm	2.0kg/km

Replace 'XX' with Color Code								
BL = Blue	BR = Brown	RD = Red	VI = Violet	NA = Natural	MG = Magenta			
OR = Orange	SL = Slate (Gray)	BK = Black	PK = Pink	LM = Lime	TN = Tan			
GR = Green	WH = White	YL=Yellow	AQ = Aqua	OL = Olive				



Learn More