



Manufacturer:

Fitel

Product Name:

OFS FITEL S327A High Precision Fiber Optic Cleaver

Manufacturer Part Number: S327A

Click here for more details on the OFS FITEL S327A High Precision Fiber Optic Cleaver

S327A High Precision Optical Fiber Cleaver



S327A High Precision Optical Fiber Cleaver

Features and Benefits

- The most durable blade in the market (65,000 cleaves)
- One-click Blade Rotation
- · Quickly Replaceable Blade
- Versatility Handheld or Desktop
- Switchable lid opening angle per user preference
- Consistent cleaving quality

Overview

The Fitel S327 is an ergonomically designed cleaver suitable for a variety of Telecoms and Production applications. This one-action cleaver ensures seamless and repeatable cleaving for both single and ribbon fiber. Notably, it boasts an impressive capability of 65,000 cleaves, making it a reliable choice for various professionals.

Key features of the Fitel S327 include:

- Longest Blade Life: The S327 offers the longest blade life in the market, ensuring durability and cost-effectiveness.
- Effortless Blade Replacement: Blade replacement is a breeze, taking just 1 minute and requiring no special tools or additional adjustments.
- **3. Versatile Usage:** Whether you prefer handheld operation or the traditional desktop setup, the \$327 accommodates both.
- **4. Automatic Fiber Collection:** The cleaved fiber ends are automatically collected in the waste bin, streamlining your workflow.

The Fitel S327 combines precision, longevity, and user-friendly design to enhance your fiber optic cleaving experience.



Operation by placing on your desk



Operation by holding in one hand



Blade position can be rotated without tools

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer:

Fitel

Product Name:

OFS FITEL S327A High Precision Fiber Optic Cleaver

Manufacturer Part Number:

S327A

Click here for more details on the OFS FITEL S327A High Precision Fiber Optic Cleaver

Specifications

Description	\$327A	
Applicable Fiber	Silica	
Fiber count	Single fiber	
	Ribbon fiber 250 μm: 2-12 fiber ribbon 200 μm: 2-16 fiber ribbon	
Clad diameter	125 µm	
Coating diameter	Single fiber: 0.20-3.0 mm	
	Ribbon fiber: 0.20-0.40 mm and 0.25 mm pitch 0.20-0.40 mm and 0.20 mm pitch	
Cleave length	Single fiber: 3mm*1	
	Tape: 10mm	
Cutting blade life	65,000 fiber (2,500 fiber per cutting blade position)*2	
Dimension	88Wx93Dx54H mm (Close for carrying)	
Weight	320 g	
*10		

^{*1} Cutting lengths of more than 3 mmbut less than 5 mm are only available with a coating diameter of 0.25 mm or less.
*2 The cutting blade life depends on the operation environment and condition. The number can vary and is not guaranteed. 0.20 mm pitch ribbon fiber decrease of cleaves.

Standard Package

Item	Model No.	(Qty)
S327A Main Body	S327A-01	1
Waste Bin	S327X-12	1
Hexagonal Wrench	S327X-16	1
Carrying Case	S327X-17	1
Single Fiber Adapter*3	S327X-18	1
Case Inner Sheet	\$327X-21	1
Operating Instructions	FTS-B616	1

^{*3} Single Fiber Adaptor scales 5~16 mm



S327A Main Body



Carrying Case



Waste Bin



Blade Exchange Set (Optional component)



Single Fiber Adapter



Hexagonal Wrench