



Manufacturer:
Optoplast

Product Name:
Optoplast 905 SMA Connector, 127µm (micron) Ceramic Ferrule,
3mm Black Boot

Manufacturer Part Number:
905Z-127-3B




[Learn More](#)

[Click here for more details on the Optoplast 905 SMA Connector, 127µm \(micron\) Ceramic Ferrule, 3mm Black Boot](#)

Click the thumbnail below to navigate to the datasheet.



[Technical Specifications](#)



[Ceramic Ferrules](#)

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are
subject to change without notice.*

**Manufacturer:**

Optoplast

Product Name:

Optoplast 905 SMA Connector, 127µm (micron) Ceramic Ferrule, 3mm Black Boot

Manufacturer Part Number:

905Z-127-3B




Learn More

► Click here for more details on the Optoplast 905 SMA Connector, 127µm (micron) Ceramic Ferrule, 3mm Black Boot



TECHNICAL SPECIFICATION



[>> Return to Page 1](#)

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.

**Manufacturer:**

Optoplast

Product Name:

Optoplast 905 SMA Connector, 127µm (micron) Ceramic Ferrule, 3mm Black Boot

Manufacturer Part Number:

905Z-127-3B

[Learn More](#)

▶ [Click here for more details on the Optoplast 905 SMA Connector, 127µm \(micron\) Ceramic Ferrule, 3mm Black Boot](#)

G E N E R A L

This specification covers the SMA 905 Connector Kit Crimp Type for SM, MM standard and MM large core applications according to IEC 61754-22.

M O D E L S A V A I L A B L E

The SMA 905 Connector Crimp Type is available with the following crimps, boots sizes and colours:

Cable Diameter	Ø 900 µm	1.6 mm	2.0 mm Slotted	2.5 mm	3.0 mm Slotted
Boot	Red, Black and Yellow	2mm Boot	White, Blue, Red, Black, Yellow, Beige and Green.	3mm Boot	White, Blue, Red, Black, Yellow and Beige.
Crimp	---	Available	Available	Available	Available

Special Boots

Cable Diameter	Ø 900 µm	1.6 mm	2.0 mm	2.5 mm	3.0 mm
90° Boot	---	2mm Boot	Black	3mm Boot	Black

Optoplast SMA 905 connectors are supplied, as standard in the following configurations:

	Boots for SMA 905 Connectors
Multimode	Black
Singlemode PC	Yellow

[>> Return to Page 1](#)

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.

**Manufacturer:**

Optoplast

Product Name:Optoplast 905 SMA Connector, 127µm (micron) Ceramic Ferrule,
3mm Black Boot**Manufacturer Part Number:**

905Z-127-3B

[Learn More](#)[Click here for more details on the Optoplast 905 SMA Connector, 127µm \(micron\) Ceramic Ferrule, 3mm Black Boot](#)**M E C H A N I C A L C H A R A C T E R I S T I C S**

Mating Durability	>500 connections	IEC61300-2-2
Cable Retention	100 N, 120s	IEC61300-2-4
900 µm Buffer Retention	5 N, 60s	IEC61300-2-4
Vibration	10 – 55 Hz , 1 octave / min. 3 axis of 15 cycles , 0.5h/axis amplitude 0.75mm	IEC61300-2-1
Repeated Bending Cable	100 cycles -90°/0°/+90°/0° Load = 5N	IEC61300-2-44
Repeated Bending 900 µm Buffer	100 cycles -90°/0°/+90°/0° Load = 0.2N	IEC61300-2-44
Cable Torsion	1.5kg -2.5kg for 2mm-3mm cable diameter	IEC60794-2-5
Drop	1.5m , 5 times	IEC61300-2-12
Static Side Load	1N , 1h	IEC61300-2-42
Static Side Load 900 µm Buffer	0.2N , 5min	IEC61300-2-42
Cold	-25°C , 96h	IEC61300-2-17
Dry Heat	+70°C , 96h	IEC61300-2-18
Change of temperature	-25°C to +70°C , 12 cycles	IEC61300-2-22

[>> Return to Page 1](#)**Contact the professionals at Fiber Optic Center for a quote or to get more details.**focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are
subject to change without notice.*



Manufacturer:
Optoplast

Product Name:
Optoplast 905 SMA Connector, 127µm (micron) Ceramic Ferrule,
3mm Black Boot

Manufacturer Part Number:
905Z-127-3B




[Learn More](#)


► [Click here for more details on the Optoplast 905 SMA Connector, 127µm \(micron\) Ceramic Ferrule, 3mm Black Boot](#)

TECHNICAL DRAWINGS


SMA 905 Crimp Type Connector for Ø 1,6 - 2 - 2,5 - 3 mm cables




SMA 905 Connector for Ø 900 µm buffer



SMA 905 Crimp Type Connector for Ø 1,6 - 2 - 2,5 - 3 mm cables



SMA 905 Crimp Type Connector Overall Dimensions



[>> Return to Page 1](#)

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are
subject to change without notice.*

**Manufacturer:**

Optoplast

Product Name:


Optoplast 905 SMA Connector, 127µm (micron) Ceramic Ferrule, 3mm Black Boot

Manufacturer Part Number:

905Z-127-3B

[Learn More](#)

▶ [Click here for more details on the Optoplast 905 SMA Connector, 127µm \(micron\) Ceramic Ferrule, 3mm Black Boot](#)

SMA 905 Crimp Type Connector with 90° Black Boot for Ø 2 - 3 mm cables**C O M P O N E N T S A N D M A T E R I A L S**

N°	Component		Material
1	Dust Cap		Vinyl
2	Connector Body	Ferrule	Zirconia
		Flange	Nickel Plated Zinc Alloy
		Nut	Nickel Plated Zinc Alloy
		Seeger Ring	Stainless Steel
3.a	Crimp Tube for Cable Ø 1.6 mm		Nickel Plated Zinc Alloy
3.b	Crimp Tube for Cable Ø 2.0 mm		Nickel Plated Zinc Alloy
3.c	Crimp Tube for Cable Ø 2.5 mm		Nickel Plated Zinc Alloy
3.d	Crimp Tube for Cable Ø 3.0 mm		Nickel Plated Zinc Alloy
4.a	Boot for Cable Ø 1.6 - 2 mm		Polymer
4.b	Boot for Cable Ø 2.5 - 3 mm		Polymer
4.c	90° Boot for Cable Ø 2 - 3 mm		Polymer
4	Boot for Ø 900 mm buffer		Polymer

All components of the connector are RoHS and REACH compliant.

[>> Return to Page 1](#)

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.



Manufacturer:

Optoplast

Product Name:

Optoplast 905 SMA Connector, 127µm (micron) Ceramic Ferrule, 3mm Black Boot

Manufacturer Part Number:

905Z-127-3B




Learn More

Click here for more details on the Optoplast 905 SMA Connector, 127µm (micron) Ceramic Ferrule, 3mm Black Boot

SMA 905 Ceramic Ferrules

Inner Diameter	ID Tolerance	C Concentricity	
126	≤1	≤2	SM ferrules on stock
127	≤4	≤4	
144	≤5	≤10	
176	≤5	≤10	MM ferrules on stock
180	≤5	≤10	
200	≤5	≤10	
224	≤10	≤20	MM ferrules on request
230	≤10	≤20	
235	≤10	≤20	
240	≤10	≤20	
250	≤10	≤20	
283	≤10	≤20	
300	≤10	≤20	
350	≤10	≤20	
400	≤10	≤20	MM ferrules on request
427	≤10	≤40	
430	≤10	≤40	
435	≤10	≤40	
450	≤10	≤40	
500	≤10	≤40	
600	≤10	≤40	
Max ID 720 micron			

C E R A M I C F E R R U L E A V A I L A B I L I T Y



>> Return to Page 1

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.