



Manufacturer:
Seikoh Giken

Product Name:
Seikoh Giken 20-Port IPC Polishing Fixture for CS/PC Connectors

Manufacturer Part Number:
PH55-CS-20

▶ Click here for more details on the Seikoh Giken 20-Port IPC Polishing Fixture for CS/PC Connectors

Click the thumbnail below to navigate to the datasheet.

Manufacturer:
Seikoh Giken

Product Name:
24-Port MEC/AMC Connector DPC Polishing Holder for Seikoh Giken SFP-560A Polishing Machine

Manufacturer Part Number:
PH55-MC-24

Click here for more details on the 24-Port MEC/AMC Connector DPC Polishing Holder for Seikoh Giken SFP-560A Polishing Machine

SFP-560A3
High standard
Mass production
Polishing machine

Features / Benefits

- SFP-560A3 model offers:
 - Conveniently input data of Date, Prod. Lot and Qty. can be done with barcode scanner and touch panel. (Change file service file)
 - "Auto" function manages polishing time as per usage. Provides more uniform geometry and extend life usage.
 - Precision stop-up and Fast-Align Mode available for each polishing step.
 - Motor speed adjustment range: 100-200 rpm.

Network controlled by LAN interface. Modbus TCP/IP

Specifications

Model	
SFP-560A3	
Polishing Head	24-Port (12 x 2) x 12mm (0.47 x 0.47 x 0.47 inch)
Polishing Material	Aluminum Oxide (Al ₂ O ₃)
Polishing Time	10-120 min (Adjustable)
Polishing Speed	100-200 rpm (Adjustable)
Polishing Pressure	0.1-0.5 MPa (Adjustable)
Polishing Temperature	20-40°C (Adjustable)
Polishing Humidity	40-60% RH (Adjustable)
Polishing Environment	Class 1000 (100,000 particles per cubic foot)
Polishing Power	1.5 kW (2.0 HP)
Polishing Noise	70 dB (A)
Polishing Weight	15 kg (33 lb)
Polishing Dimensions	450 x 350 x 150 mm (17.7 x 13.8 x 5.9 inch)

Contact the professionals at Fiber Optic Center for a quote or to get more details.

508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.

[560A3](#)

Manufacturer:
Seikoh Giken

Product Name:
24-Port MEC/AMC Connector DPC Polishing Holder for Seikoh Giken SFP-560A Polishing Machine

Manufacturer Part Number:
PH55-MC-24

Click here for more details on the 24-Port MEC/AMC Connector DPC Polishing Holder for Seikoh Giken SFP-560A Polishing Machine

SFP-560A3C
High standard mass
production polishing
machine with
Auto-clamping

Features / Benefits

- Auto Clamping polisher for less operator dependency. "SFP-560A3C" model offers:
 - Conveniently input data of Date, Prod. Lot and Qty. can be done with barcode scanner and touch panel. (Change file service file)
 - "Auto" function manages polishing time as per usage. Provides more uniform geometry and extend life usage.
 - Precision stop-up and Fast-Align Mode available for each polishing step.
 - Motor speed adjustment range: 100-200 rpm.
 - Network controlled by LAN interface. Modbus TCP/IP

Network controlled by LAN interface. Modbus TCP/IP

Specifications

Model	
SFP-560A3C	
Polishing Head	24-Port (12 x 2) x 12mm (0.47 x 0.47 x 0.47 inch)
Polishing Material	Aluminum Oxide (Al ₂ O ₃)
Polishing Time	10-120 min (Adjustable)
Polishing Speed	100-200 rpm (Adjustable)
Polishing Pressure	0.1-0.5 MPa (Adjustable)
Polishing Temperature	20-40°C (Adjustable)
Polishing Humidity	40-60% RH (Adjustable)
Polishing Environment	Class 1000 (100,000 particles per cubic foot)
Polishing Power	1.5 kW (2.0 HP)
Polishing Noise	70 dB (A)
Polishing Weight	15 kg (33 lb)
Polishing Dimensions	450 x 350 x 150 mm (17.7 x 13.8 x 5.9 inch)

Contact the professionals at Fiber Optic Center for a quote or to get more details.

508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.

[560A3C](#)

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.



Learn More



Manufacturer:

Seikoh Giken

Product Name:

Seikoh Giken 20-Port IPC Polishing Fixture for CS/PC Connectors

Manufacturer Part Number:

PH55-CS-20

► Click here for more details on the Seikoh Giken 20-Port IPC Polishing Fixture for CS/PC Connectors



■ Features / Benefits

“SFP-560A3” model offers;

- Consumables info input: Entry of Film, Pad, Liquid info can be done with barcode scanner and touch panel - Manages Film service life
- "Add time" feature manages polishing time as per usage - Provides more uniformed geometry and extend film usage
- Pressure ramp-up and Fixed Height Mode available for each polishing step
- Wider speed adjustment range : 10- 200 rpm
- Network connection by two methods: Modbus TCP/IP



Interface of A3C model consumables info input & control

■ Specifications

*New Technology
~DPC : Dynamic Pressure Control~
(Patent Pending.)*

Weight	22kg (48.5lb)
Dimensions	240W x 370D x 305H (mm)
Polishing Method	Rotation & Revolution
Pressure Control	2N to 200N in DPC mode
Power	100~ 240 VAC, 50/60Hz
Required Air	0.6MPa to 0.8MPa
Motor speed	Revolution: 10 to 200rpm Rotation: 1/100 of rev. speed
Process storage	48 processes
Film and Pad Size	5" (127mm)



High Volume, Multi-Axis
Intelligent Automation
Superior MT Geo.

>> Return to Page 1

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are
subject to change without notice.*

[Learn More](#)**Manufacturer:**

Seikoh Giken

Product Name:

Seikoh Giken 20-Port IPC Polishing Fixture for CS/PC Connectors

Manufacturer Part Number:

PH55-CS-20

[Click here for more details on the Seikoh Giken 20-Port IPC Polishing Fixture for CS/PC Connectors](#)**SFP-560A3 Standard Package**

Description	Part Number	Qty
Main unit	SFP-560A3	1
2A fuse (in fuse holder)	RP55-56	1
M3 × 60-SUS bolt	M14-00096	2
Power cable	RP55-30	1
Cable hanger	FP-CH	1
USB memory	FP-USB	1
Check valve	RP56A-24	1
Barcode scanner	FP-SCN56-A	1
Operation manual	FP-IM56A3	1
Process manual	FP-PM56A3	1
Maintenance manual	FP-MM56A3	1

Available Polishing Consumables**POLISHING FILMS FOR ZR POLISHNG**

Description:	Film Part #
30um Silicon Carbide	GA5D
30um Diamond	EDA5D-30U
9um Diamond	EDR5D-9U
5um Diamond	EDG5D-5U
3um Diamond	EDH5D-3U
1um Diamond	EDJ5D-1U
Silica	XF5D

Other types of films and liquid are also available up on request*POLISHING FILMS FOR MT POLISHNG**

Description:	Film Part #
Adhesive Removal & Leveling	GC5D
Rough polishing	AR5D
Fiber protrusion	GH5D
Finishing	FM5D-SOAP-2

**Consumables for slurry polishing are also available upon request*Rubber & Glass Pads Available for various Hardness & Thickness ([ask for details](#)):

60, 65, 70, 75, 80, 85 & 90 durometer

4.8, 4.9, 5.0, & 5.05 mm thickness All for 5" diameter

For MT polishing, PG5X-490-SR3, tacky glass pad is available, which PSA backing is no longer needed.

Available Fixtures & Accessories**I.P.C. HOLDERS**Description:

FC/PC
 FC/APC (Step or Conical)
 SC/PC
 SC/APC (Step or Conical)
 ST/PC
 LC/PC Simplex & Duplex
 LC/APC High Pressure
 LC/APC Duplex

VSFF Connectors New

CS/PC
 CS/APC
 MDC/PC
 MDC/APC
 SN/PC
 SN/APC
 MDCJR/APC
 SNJR/APC
 SNCOM/APC
 IP16/SN Ferrule / PC

Holder Part #

PH55-FP-20 or 24
 PH55-FP8*-18-l or 24
 PH55-CP-20, 24 or 32
 PH55-CP8*-18-l or 24 or 32
 PH55-SP-20 or 28
 PH55-PL-48DHP or 54DHP
 PH55-PL8A-48HP or 54HP
 PH55-PL8A-32DHP-POR

PH55-CS-20

PH55-CS8A-18

PH55-MDC-24

PH55-MDC8A-24

PH55-SN-24

PH55-SN8A-24

PH55-MDCJR8A-24

PH55-SNJR8A-24

PH55-SNCOM8A-24

PH55-F0423-700

FIXED D.P.C. HOLDERS (SFP-560A series only) NewDescription:

Conical SC/APC
 OptiTap
 LC/PC Simplex & Duplex
 LC/APC Simplex
 LC/APC Duplex
 MDC/PC
 MDC/APC
 CS/PC
 CS/APC
 SN/PC
 SN/APC
 MDCJR/APC
 SNJR/APC
 SNCOM/APC
 IP16/SN Ferrule / PC
 Universal ferrule holder

Holder Part #

PH55-CP8C-16FX
 PH55-OPT8C-18FX or 24FX
 PH55-PL-32DFX or 48DFX
 PH55-PL8A-24FX or 48FX
 PH55-PL8A-32DFX-POR

PH55-MDC-24FX

PH55-MDC8A-24FX

PH55-CS-20FX

PH55-CS8A-18FX

PH55-SN-24FX

PH55-SN8A-24FX

PH55-MDCJR8A-24FX

PH55-SNJR8A-24FX

PH55-SNCOM8A-24FX

PH55-F0423-700FX

PH55-F0423-210C

MT HOLDERS & ACCESSORIESDescription:

MT/PC One-lever Holder
 MT/APC One-lever Holder
 Washing station
 Cable Management
 Air Blower
 Non-woven cleaning paper

MT Holder Part #

PH55-MT-24SQ1-B

PH55-MT8A-24QD New

MT-P-WSH56-C

MT-P-CMH56-D

MT-P-BLW56-B

MT-P-NWPAPER-A

[>> Return to Page 1](#)**Contact the professionals at Fiber Optic Center for a quote or to get more details.**focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.



Learn More



Manufacturer:

Seikoh Giken

Product Name:

Seikoh Giken 20-Port IPC Polishing Fixture for CS/PC Connectors

Manufacturer Part Number:

PH55-CS-20

► Click here for more details on the Seikoh Giken 20-Port IPC Polishing Fixture for CS/PC Connectors



■ **Features / Benefits**

Auto Clamping polisher for less operator dependency, "SFP-560A3C" model offers;

- Consumables info input: Entry of Film, Pad, Liquid info can be done with barcode scanner and touch panel - Manages Film service life
- "Add time" feature manages polishing time as per usage - Provides more uniformed geometry and extend film usage
- Pressure ramp-up and Fixed Height Mode available for each polishing step
- Wider speed adjustment range : 10- 200 rpm
- Network connection by two methods: Modbus TCP/IP



Interface of A3C model consumables info input & control

■ **Specifications**

*New Technology
~DPC : Dynamic Pressure Control~
(Patent Pending)*

Weight	22kg (48.5lb)
Dimensions	240W x 370D x 305H (mm)
Polishing Method	Rotation & Revolution
Pressure Control	2N to 200N in DPC mode
Power	100~ 240 VAC, 50/60Hz
Required Air	0.6MPa to 0.8MPa
Motor speed	Revolution: 10 to 200rpm Rotation: 1/100 of rev. speed
Process storage	48 processes
Film and Pad Size	5" (127mm)



High Volume, Multi-Axis
Intelligent Automation
Superior MT Geo.

>> Return to Page 1

Contact the professionals at Fiber Optic Center for a quote or to get more details.

focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are
subject to change without notice.*

[Learn More](#)**Manufacturer:**

Seikoh Giken

Product Name:

Seikoh Giken 20-Port IPC Polishing Fixture for CS/PC Connectors

Manufacturer Part Number:

PH55-CS-20

[▶ Click here for more details on the Seikoh Giken 20-Port IPC Polishing Fixture for CS/PC Connectors](#)**SFP-560A3C Standard Package**

Description	Part Number	Qty
Main unit	SFP-560A3C	1
2A fuse (in fuse holder)	RP55-56	1
M3 × 60-SUS bolt	M14-00096	2
Power cable	RP55-30	1
Cable hanger	FP-CH	1
USB memory	FP-USB	1
Check valve	RP56A-24	1
Barcode scanner	FP-SCN56-A	1
Operation manual	FP-IM56A3C	1
Process manual	FP-PM56A3C	1
Maintenance manual	FP-MM56A3C	1

Available Polishing Consumables**POLISHING FILMS FOR ZR POLISHING**

Description:	Film Part #
30um Silicon Carbide	GA5D
30um Diamond	EDA5D-30U
9um Diamond	EDR5D-9U
5um Diamond	EDG5D-5U
3um Diamond	EDH5D-3U
1um Diamond	EDI5D-1U
Silica	XF5D

Other types of films and liquid are also available up on request*POLISHING FILMS FOR MT POLISHING**

Description:	Film Part #
Adhesive Removal & Leveling	GC5D
Rough polishing	AR5D
Fiber protrusion	GH5D
Finishing	FM5D-SOAP-2

**Consumables for slurry polishing are also available upon request*

Rubber & Glass Pads Available for various Hardness & Thickness ([ask for details](#)):

60, 65, 70, 75, 80, 85 & 90 durometer
 4.8, 4.9, 5.0, & 5.05 mm thickness All for 5" diameter
 For MT polishing, PG5X-490-SR3, tacky glass pad is available, which PSA backing is no longer needed.

Available Fixtures & Accessories**I.P.C. HOLDERS**

Description:	Holder Part #
FC/PC	PH55-FP-20 or 24
FC/APC (Step or Conical)	PH55-FP8*-18-I or 24
SC/PC	PH55-CP-20, 24 or 32
SC/APC (Step or Conical)	PH55-CP8*-18-I or 24 or 32
ST/PC	PH55-SP-20 or 28
LC/PC Simplex & Duplex	PH55-PL-48DHP or 54DHP
LC/APC High Pressure	PH55-PL8A-48HP or 54HP
LC/APC Duplex	PH55-PL8A-32DHP-POR
VSFF Connectors New	
CS/PC	PH55-CS-20
CS/APC	PH55-CS8A-18
MDC/PC	PH55-MDC-24
MDC/APC	PH55-MDC8A-24
SN/PC	PH55-SN-24
SN/APC	PH55-SN8A-24
MDCJR/APC	PH55-MDCJR8A-24
SNJR/APC	PH55-SNJR8A-24
SNCOM/APC	PH55-SNCOM8A-24
IP16/SN Ferrule / PC	PH55-F0423-700

FIXED D.P.C. HOLDERS (SFP-560A series only) New

Description:	Holder Part #
Conical SC/APC	PH55-CP8C-16FX
OptiTap	PH55-OPT8C-18FX or 24FX
LC/PC Simplex & Duplex	PH55-PL-32DFX or 48DFX
LC/APC Simplex	PH55-PL8A-24FX or 48FX
LC/APC Duplex	PH55-PL8A-32DFX-POR
MDC/PC	PH55-MDC-24FX
MDC/APC	PH55-MDC8A-24FX
CS/PC	PH55-CS-20FX
CS/APC	PH55-CS8A-18FX
SN/PC	PH55-SN-24FX
SN/APC	PH55-SN8A-24FX
MDCJR/APC	PH55-MDCJR8A-24FX
SNJR/APC	PH55-SNJR8A-24FX
SNCOM/APC	PH55-SNCOM8A-24FX
IP16/SN Ferrule / PC	PH55-F0423-700FX
Universal ferrule holder	PH55-F0423-210C

MT HOLDERS & ACCESSORIES

Description:	MT Holder Part #
MT/PC One-lever Holder	PH55-MT-24SQ1-B
MT/APC One-lever Holder	PH55-MT8A-24QD New
Washing station	MT-P-WSH56-C
Cable Management	MT-P-CMH56-D
Air Blower	MT-P-BLW56-B
Non-woven cleaning paper	MT-P-NWPAPER-A

[>> Return to Page 1](#)**Contact the professionals at Fiber Optic Center for a quote or to get more details.**focenter.com • 508-992-6464 | (800) 473-4237 • sales@focenter.com

23 Centre Street • New Bedford, MA 02740 USA

*Product specifications and data are
subject to change without notice.*