



**Manufacturer:**  
Seikoh Giken

**Product Name:**  
Seikoh Giken Pre-Radius 4 Slot Zirconia 2.5mm Ferrule 125um -360


**Manufacturer Part Number:**  
SZ-3A1512580G

>> Find Out More Details on the Seikoh Giken Pre-Radius 4 Slot Zirconia 2.5mm Ferrule 125um -360 <<

## Product Data Sheet

Page 1 of 1

### SZ-3A 2.5mm Single Mode Pre-dome Endface Zirconia Ferrule



#### Features & Benefits

- Realization of excellent wear and shock resistance, high-durability against repeated insertion, removal and highly reliable connections.
- Wide product lineup, including 2.5, 125, pred-dome, Angle PC and funnel shape types, makes it possible to respond to a diverse range of user needs.
- Reduced assembly time.
- High-quality of end face radius.



#### Specifications

End Face Radius	15 = 3/-5mm
Outside Diameter & Tolerance	2499.0 ± 0.5
Hole Eccentricity	0.7 or less (0.5 is available)
Hole Diameter Tolerance	+ 1.0/-0
Hole Diameter	S5      S5.5      S6
Hole Diameter(um)	125um    125.5um    126um

#### Ordering Information

Model Number	Type Number						
SZ-3A	1	4	1	2	5	0	0
Ferrule O.D. (mm)	1 : ø 2.5						(Required)
Flange	4 : 4-slots						
Ferrule I.D. (µm)	ø 125    ø 125.5(12F)    ø 126						
Detail Specification							
0 : SII standard							
Eccentricity = 0.7 micron or less							
8 : Eccentricity = 0.5 micron or less							

Contact the professionals at Fiber Optic Center for a quote or to get more details.

[focenter.com](http://focenter.com) • 508-992-6464 | (800) 473-4237 • [sales@focenter.com](mailto:sales@focenter.com)

23 Centre Street • New Bedford, MA 02740 USA

Product specifications and data are subject to change without notice.