



## **Manufacturer:**

Seikoh Giken

#### **Product Name:**

Seikoh Giken SFP-560A 12-Port One-Lever MT/APC Ferrule Holder

#### **Manufacturer Part Number:**

PH55-MT8A-12QD

Click here for more details on the Seikoh Giken SFP-560A 12-Port One-Lever MT/APC Ferrule Holder



## One Lever Action MT Holders New

### For SFP-550 series and SFP-560A

PH55-MT-24SQ1-B (MT/PC, 24-axis) PH55-MT-12SQ1-B (MT/PC, 12-axis) PH55-MT8A-24SQ1-B (MT/APC, 24-axis) PH55-MT8A-12SQ1-B (MT/APC, 12-axis)

## For SFP-510 series

PH51-MT-20SQ1-B (MT/PC, 20-axis)
PH51-MT-12SQ1-B (MT/PC, 12-axis)
PH51-MT8A-20SQ1-B (MT/APC, 20-axis)
PH51-MT8A-12SQ1-B (MT/APC, 12-axis)



To install just simply lock down the lever after inserting MT ferrule

Note: MT ferrule epoxy window width (A) shall be less than 3.4mm

#### ■ Features

- No more use of torque wrench for MT ferrule installation
- Only one lever action to install and detach MT ferrule (Pat. JP6192797 CN108367408 Other areas Pat. Pending)
- Approx. 30% reduction in loading and unloading time
- Fully compatible with existing polishing machines
- > Stable and flat geometry performance
- Simple 5 steps flock polishing process
- > Various optional cable managements are available

Contact the professionals at Fiber Optic Center for a quote or to get more details.





# Manufacturer:

Seikoh Giken

#### **Product Name:**

Seikoh Giken SFP-560A 12-Port One-Lever MT/APC Ferrule Holder

### **Manufacturer Part Number:**

PH55-MT8A-12QD


Click here for more details on the Seikoh Giken SFP-560A 12-Port One-Lever MT/APC Ferrule Holder


## ■ Process and Performance

# Simple 5 steps Flock Process (M/M, PPS) (SFP-560A)

Polishing Step	Polishing Condition					
	Polishing Pad	Polishing Film (service life)	Polishing Liquid	Polishing Time (sec)	Pressure(N) (*1)	1st Step Mode
1	PG5X-490-SR3	GC5D (1)	PURIFIED WATER	30(*2)	31 / 12-axis 62 / 24-axis	Pressure Ramp UP
2				10	31 / 12-axis 62 / 24-axis	N/A
3	PG5X-490-SR3	AR5D (1)	PURIFIED WATER	60	42 / 12-axis 84 / 24-axis	N/A
4	PG5X-490-SR3	GH5D (1)	PURIFIED WATER	60	42 / 12-axis 84 / 24-axis	N/A
5	PG5X-490-SR3	FM5D-SOAP (1)	PURIFIED WATER	150	42 / 12-axis 84 / 24-axis	N/A


## Stable Fiber Height





## Clean Endface

# Stable Angle



Disclaimer- 1) Polishing method with use of fibrous material is patented in the U.S (US patent No. 6106368). 2) A ferrule assembly with fiber protrusion between 0.5um and 2.5um after polishing is patented in the U.S. (US patent No. 5743785).

# Contact the professionals at Fiber Optic Center for a quote or to get more details.