



Manufacturer:

Seikoh Giken

Product Name:

Seikoh Giken SFP-560A 24-Port One-Lever MT Ferrule Holder

Manufacturer Part Number:

PH55-MT-24SO1

Click here for more details on the Seikoh Giken SFP-560A 24-Port One-Lever MT Ferrule Holder



One Lever Action MT Holders New

For SFP-550 series and SFP-560A

PH55-MT-24SQ1-B (MT/PC, 24-axis)
PH55-MT-12SQ1-B (MT/PC, 12-axis)
PH55-MT8A-24SQ1-B (MT/APC, 24-axis)
PH55-MT8A-12SQ1-B (MT/APC, 12-axis)

For SFP-510 series

PH51-MT-20SQ1-B (MT/PC, 20-axis)
PH51-MT-12SQ1-B (MT/PC, 12-axis)
PH51-MT8A-20SQ1-B (MT/APC, 20-axis)
PH51-MT8A-12SQ1-B (MT/APC, 12-axis)



To install just simply lock down the lever after inserting MT ferrule

Note: MT ferrule epoxy window width (A) shall be less than 3.4mm

■ Features

- > No more use of torque wrench for MT ferrule installation
- Only one lever action to install and detach MT ferrule (Pat. JP6192797 CN108367408 Other areas Pat. Pending)
- Approx. 30% reduction in loading and unloading time
- > Fully compatible with existing polishing machines
- > Stable and flat geometry performance
- Simple 5 steps flock polishing process
- Various optional cable managements are available

Contact the professionals at Fiber Optic Center for a quote or to get more details.





Manufacturer:

Seikoh Giken

Product Name:

Seikoh Giken SFP-560A 24-Port One-Lever MT Ferrule Holder

Manufacturer Part Number:

PH55-MT-24SQ1


Click here for more details on the Seikoh Giken SFP-560A 24-Port One-Lever MT Ferrule Holder


■ Process and Performance

Simple 5 steps Flock Process (M/M, PPS) (SFP-560A)

| Polishing Step | Polishing Condition | | | | | |
|-------------------|---------------------|----------------------------------|---------------------|----------------------------|------------------------------|---------------------|
| | Polishing Pad | Polishing Film (service life) | Polishing Liquid | Polishing Time (sec) | Pressure(N) (*1) | 1st Step Mode |
| 1 | PG5X-490-SR3 | GC5D (1) | PURIFIED WATER | 30(*2) | 31 / 12-axis 62 / 24-axis | Pressure Ramp UP |
| 2 | | | | 10 | 31 / 12-axis 62 / 24-axis | N/A |
| 3 | PG5X-490-SR3 | AR5D (1) | PURIFIED WATER | 60 | 42 / 12-axis 84 / 24-axis | N/A |
| 4 | PG5X-490-SR3 | GH5D (1) | PURIFIED WATER | 60 | 42 / 12-axis 84 / 24-axis | N/A |
| 5 | PG5X-490-SR3 | FM5D-SOAP (1) | PURIFIED WATER | 150 | 42 / 12-axis 84 / 24-axis | N/A |


Stable Fiber Height





Clean Endface

Stable Angle



Disclaimer- 1) Polishing method with use of fibrous material is patented in the U.S (US patent No. 6106368). 2) A ferrule assembly with fiber protrusion between 0.5um and 2.5um after polishing is patented in the U.S. (US patent No. 5743785).

Contact the professionals at Fiber Optic Center for a quote or to get more details.