



## **Manufacturer:**

Techcon™

### **Product Name:**

Techcon TS250 Dispensing Machine

## **Manufacturer Part Number:**

TS250

Click here for more details on the Techcon TS250 Dispensing Machine



# TS250 Series Dispenser

# Entry-Level Digital Dispenser

The TS250 Series Dispenser dispenses low, medium and high The rear DB9 interface connector has the ability to initiate the viscosity fluids, accurately and consistently.

These systems are economical, highly accurate and repeatable micro air dispensing systems.

These user friendly dispensing systems include a digital timer, with rotary timing knob, for easy setup and a vacuum control for all viscosities of fluid.

dispense cycle by an external device by way of voltage or contact closure signal.

Available in two versions of operating pressure: 0 to 100 psi (0 to 6.9bar) for general applications and 0 to 15 psi (0 to 1.0bar) for specific low viscosity applications.

Contact the professionals at Fiber Optic Center for a quote or to get more details.





## **Manufacturer:**

Techcon™

### **Product Name:**


**Techcon TS250 Dispensing Machine** 


## **Manufacturer Part Number:**

TS250

Click here for more details on the Techcon TS250 Dispensing Machine

### **FEATURES**





## SPECIFICATIONS & PART NUMBERS

Part Number:	TS250
Size (Imperial):	6" W x 7.7" L x 7.2" H
Size (Metric):	152mm x 195mm x 183mm
Weight:	2.6 lb (1200g)
Pressure Range:	0 to 100psi (0 to 6.9bar)
Cycle Rate:	600/min.
Timing Range:	0.020 - 60 seconds
Timing Tolerance:	+/- 0.001%
Input Voltage:	100 – 240 VAC
Input Frequency:	50 – 60 Hz
Cycle Modes:	Timed, Purge
Certification:	CE, TUV-GS and NRTL

The valve is shipped with the following items:

- Power Supply Foot Switch Air Hose Sample Dispense Tips
- 10cc Receiver Head 10cc Svringe. Piston & Tip Cap Svringe

#### **ACCESSORIES**

- Syringe Barrels: The dispenser can be connected to any size and color Techcon syringe barrel.
- Receiver Heads: Receiver heads connect the dispenser to syringe barrel. Available in 3ft (0.9m) or 6ft (1.8m) air hose lengths.
- Dispense Tips: All Techcon dispense tips can be use with the TS250 Series.

## Key Features & Benefits

- Universal power supply for worldwide use
- 16 x 2 LCD display with back lighting
- Digital timing from 0.020 60 seconds
- Adjustable vacuum suck back to control fluid tailing and waste

## Typical Applications

#### Dispense:

- Solder paste dots on PCBA
- UV adhesive in medical device manufacturing
- Beads of grease for lubrication purposes

171005-1200-CL