

Viavi





Viavi SmartClass™ OLP-82P Digital Video Display Pro Kit with Patch Cord, Probe Scope & Optical Power Meter

Manufacturer Part Number:

FIT-82P01-PRO

Click here for more details on the Viavi SmartClass™ OLP-82P Digital Video Display Pro Kit with Patch Cord, Probe Scope & Optical Power Meter



Data Sheet

VIAVI OLP-82/82P

SmartClass™ fiber power meter and microscope

The OLP-82 from VIAVI Solutions is the first handheld tool to combine pass/fail fiber inspection and optical power measurement (OPM) into one solution. As part of the VIAVI SmartClass Fiber family, the OLP-82 helps service providers guarantee a lifetime of system performance from their network connectivity and gives contractors an essential tool for delivering best-in-class reliable networks to their customers.

The OLP-82 is ideal for technicians at any skill level with instant pass/fail acceptance results for both end-face quality and OPM in one button push. The OLP-82 can also save test results and generate certification reports to document work quality. Integrating these capabilities into one system helps the OLP-82 drive technician behavior toward implementing today's best practices in a seamless workflow that optimizes efficiency and reliability so they complete the job right—the first time.

The handheld OLP-82 can be used anywhere today's fiber technicians go, up poles or down holes. Technicians get ultimate flexibility and performance from this powerful, easy-to-use solution that can help any technician become an instant fiber expert.



Key Benefits

- Complete jobs faster, correctly, and on time—the first time: Uniquely integrates fiber inspection and test for an efficient, easy-to-use solution that promotes best practices for handling fiber
- Analysis with pass/fail results on one handheld device: Automatically and easily certifies fiber end-face condition and measures optical power making even new technicians fiber experts
- Easily generates certification reports: Prove that work quality meets industry standards and customer specifications
- Use it anywhere: A portable, organized, hands-free carrier for easy use inside homes, at demarcation points, or up on telephone poles and cell towers

Key Features

- Field-portable OPM with multiple calibrated wavelengths from 780 to 1625 nm
- Automated pass/fail analysis for fiber inspection and test
- Supports both industry-standard and userdefinable acceptance criteria
- Available with integrated PCM
- Integrated connector certification reports
- Onboard storage for fiber inspection and test results
- Connects to a PC via mini-USB to export data and manage acceptance criteria using FiberChekPRO™ software
- Two USB ports to connect additional devices such as a P5000i microscope
- Automatic fiber-image centering
- Modern, smartphone-style user interface with touch screen
- Rugged, weather-proof design

Contact the professionals at Fiber Optic Center for a quote or to get more details.

Learn More



Viavi



Viavi SmartClass™ OLP-82P Digital Video Display Pro Kit with Patch Cord, Probe Scope & Optical Power Meter

Manufacturer Part Number:

FIT-82P01-PRO

Click here for more details on the Viavi SmartClass™ OLP-82P Digital Video Display Pro Kit with Patch Cord, Probe Scope & Optical Power Meter

Become an Instant Fiber Expert with SmartClass Fiber

Integration Combines inspection and testing

✓ Automation Pass/fail certification

Ease of use Intuitive smartphone-style user interface

Intuitive Smartphone-Style User Interface

View a high-contrast, color touch screen with menu icons.



Accurate Measurement and Simple Operation

Make quick, easy dual-wavelength measurements at 850 and 1300 nm or 1310 and 1550 nm using saved reference levels.



Store Inspection and Measurement Readings on the Device


Store up to 10,000 measurement results on the device for export to a PC.



2 OLP-82/82P

User-Definable Pass/Fail Acceptance Criteria

Whether using the IEC 61300-3-35 or customer-specific requirements, users can easily manage user-specified acceptance criteria with dedicated profiles for each requirement.



Comprehensive Data Management and Report Generation

Easily generate certification reports that prove your quality of work meets industry standards or customer specifications using FiberChekPRO PC software.

- Easily store measurement data at the press of a button
- Manage data and store results on the instrument
- Download measurement results to a PC via a USB interface



Learn More



Viavi



Viavi SmartClass™ OLP-82P Digital Video Display Pro Kit with Patch Cord, Probe Scope & Optical Power Meter

Manufacturer Part Number:

FIT-82P01-PRO

Click here for more details on the Viavi SmartClass™ OLP-82P Digital Video Display Pro Kit with Patch Cord, Probe Scope & Optical Power Meter

Inspect and Test Fiber Anywhere

Combines Inspection and Test in One Handheld Device

Use either the onboard patch-cord microscope (PCM) or connect a P5000i digital analysis microscope to inspect fiber end faces and eliminate poor-quality components from entering your network.

Benefits of Using P5000i and PCM Together

Working with both the P5000i and PCM:

- Optimizes technician performance with tools designed for workflow
- Improves network activation with a reliable, repeatable processes
- Ensures test leads are safely stored when not in use
- Enables quick and easy inspection of both female (bulkhead) and male (patch cord) fiber connectors without changing tips

Automatic Image Centering

This convenient feature centers the fiber image on the screen.

Ultimate Portability and Organization

The hands-free carrier stores all essential tools, such as the inspection microscope, visual fault locator, and cleaning materials, in an organized, portable system that you can take with you to every job.



3 OLP-82/82P

Specifications

General Technical	(typical at 25°C)
Weight	
OLP-82/HD4i	1.2 lb (0.5 kg)
OLP-82P/HD4iP	1.4 lb (0.6 kg)
Dimensions (H x V	V x D)
OLP-82/HD4i	8.2 x 4.4 x 2.5 in
	(20.8 x 11.2 x 6.4 cm)
OLP-82P/HD4iP	8.2 x 6.0 x 2.5 in
	(20.8 x 15.2 x 6.4 cm)
Video display	3.5 in color LCD, 4:3 ratio
Keypad	11+2 dome-buttons
	membrane panels
	4 LED indicators
Connector	USB 2.0 (2 x host, Type A;
	1 x device, Micro-B)
Power source	AC adaptor, battery (Alkaline or
	rechargeable Li ion), USB port
Run time	Τ.
Rechargeable Li	8 hours
ion = (minimum)	
Alkaline	5 hours
Power mode	Active, Auto-off
Auto-shutoff time	User programmable
Charge time	Τ.
AC adaptor	8 hours
USB port	16 hours
Power source	AA batteries, Li-ion battery, or
	AC power adaptor
Certification	CE, IEC/EN61326
OPM	
General Technical	
Interface	Free space (2.5 mm UPP adapter,
	1.25 mm UPP optional)
Power measureme	
1300/1310 nm	-50 to +10 dBm
850 nm	-45 to +10 dBm
Display Range	-65 to +10 dBm
Maximum permitt	ted input level
	+10 dBm
Standard	
Standard Standard	850, 980, 1300, 1310, 1490, 1550,
	850, 980, 1300, 1310, 1490, 1550, 1625 nm
Standard	
Standard wavelength settings Intrinsic	
Standard wavelength settings Intrinsic uncertainty ¹	1625 nm ±0.20 dB (±5%)
Standard wavelength settings Intrinsic	1625 nm

Under the following reference conditions: -20 dBm (CW), 1300 nm ± 1 nm, 23°C ± 3k 45 to 75% rel. humidity, 9 to 50 μm fiber.

Learn More

^{2. -5} to +45°0



Viavi



Product Name:

Viavi SmartClass™ OLP-82P Digital Video Display Pro Kit with Patch Cord, Probe Scope & Optical Power Meter

Manufacturer Part Number:

FIT-82P01-PRO

Click here for more details on the Viavi SmartClass™ OLP-82P Digital Video Display Pro Kit with Patch Cord, Probe Scope & Optical Power Meter

Included Items
Stand-Alone Units
SmartClass Fiber instrument

Wavelength and modulation			
Result display	dBm, dB, MW		
Resolution	0.01 dB		
Calibrated wavelengths	850, 1310, 1490, 1550, 1625		
Wavelength settings	780 to 1650 in 1 nm steps		
Tone detection	270 Hz, 1 kHz, 2 kHz		
Video Display			
General Technical (typical at 25°C)			
Live image	320 x 240 x 8 bit gray, 10 fps		
Light source	Blue LED, 100,000+ hour life		
Lighting technique	Coaxial		
Low-magnification field-of-view (FOV)			
Horizontal	740 µm		
Vertical	550 μm		
High-magnification	field of view (FOV)		
Horizontal	370 μm		
Vertical	275 μm		

Ordering Information

Standalone Units		
Description	Part Number	
HD4i digital handheld video display	FBP-HD4i	
HD4iP digital handheld video display, dual-mag patch cord module	FBP-HD4iP	
OLP-82 digital handheld video display, integrated optical power meter	2315/01	
OLP-82P digital handheld video display, dual-mag patch cord module, integrated OPM	2316/01	
Kits		
HD4i basic kit	FBP-SD4i	
HD4i pro kit	FBP-SD4i-PRO	
HD4iP basic kit	FBP-SD4iP	
HD4iP pro kit	FBP-SD4iP-PRO	
OLP-82 basic kit	FIT-8201	
OLP-82 pro kit	FIT-8201-PRO	
OLP-82P basic kit	FIT-82P01	
OLP-82P pro kit	FIT-82P01-PRO	

SmartClass Fiber instrument		
Soft bag for SmartClass Fiber and accessories		
Power supply for SmartClass Fiber (12 V)		
USB cable USB-A to micro-USB		
QuickStart manual and safety in	structions	
Dry batteries (8x)		
Additional Items in Basic Kits		
P5000i Digital Inspection Microscope		
Inspection tips and adapters (bulkhead: SC and LC, patch cord: 2.5 and 1.25 mm)		
1.25 mm OPM adapter OLP-82/82P		
Hands-free carrier for SmartClass Fiber		
Additional Items in Pro Kits		
P5000i Digital Inspection Microscope		
Inspection tips and adapters (bulkhead: SC and LC, patch cord: 2.5 and 1.25 mm)		
1.25 mm OPM adapter OLP-82/82P		
Cleaning materials for 2.5 and 1.2 patch cord)	25 mm (bulkhead and	
Hands-free carrier for SmartClass Fiber		
Rechargeable battery for SmartClass Fiber (Li ion)		
FFL-050 Visual Fault Locator wit adapter	h 2.5 and 1.25 mm	
Accessories		
Description	Part Number	
Kit, RBP2 rechargeable battery (Li ion) and FBPP-PS4 power supply (12V)	FITP-RCG1	
Power supply for SmartClass Fiber (12V)	FBPP-PS4	
Rechargeable battery for SmartClass Fiber (Li ion)	FITP-RBP2	
UC4 hands-free carrier for SmartClass Fiber	FITP-UC4	
UC4P hands-free carrier for	FITP-UC4P	
SmartClass Fiber with PCM	FITP-UC4P	
SmartClass Fiber with PCM Adapter U12 for OLP-82/82P	VPP-UPP12	

VPP-UPP25

FBPP-SCASE2

Adapter U25 for OLP-82/82P SCASE2 soft shoulder case for

SmartClass Fiber tools

4 OLP-82/82P